

MATERIAL SAFETY DATA SHEET

SECTION I PRODUCT IDENTIFICATION AND USE

PRODUCT NAME / IDENTIFICATION

225 & 226 STIK-UMM

W.H.M.I.S. STATUS

CONTROLLED

W.H.M.I.S. CLASSIFICATION

CLASS B-2 FLAMMABLE, D2B TOXIC

PRODUCT IDENTIFICATION NUMBER

MIXTURE

PRODUCT DESCRIPTION

ADHESIVE

MANUFACTURER

INTERNATIONAL EPOXIES & SEALERS
30241 COMMERCE DR.
SAN ANTONIO, FL 33576

24 HOUR EMERGENCY PHONE

INFOTRAC: (800) 535-5053

SUPPLIER

INTERNATIONAL EPOXIES & SEALERS
30241 COMMERCE DR.
SAN ANTONIO, FL 33576

INFORMATION PHONE: 800-451-7206

SECTION II HAZARDOUS INGREDIENTS

%	HAZARDOUS INGREDIENTS	UNI/CAS#	LC50(TLV)	LD50(ORAL)	LD50(DERMAL)
10-15	HEXANE	110-54-3	(50 ppm)	N/D	N/D
25-35	TOLUENE	108-88-3	*8000 ppm/4 HR	2500 mg/kg	14,000 mg/kg
55-65	SYNTHETIC ELASTOMER & RESINS	NON-HAZARDOUS			

Actual LC 50 numbers are preceded by an asterisk *. Where this information is not available a Threshold Limit value (ppm in brackets) may be provided as an indication of the inhalation severity of the ingredient.

SECTION III PHYSICAL DATA

PHYSICAL STATE	COLOR			ODOR THRESHOLD (ppm)
GEL	WATER WHITE WITH MILD SOLVENT ODOR			N/D
VAPOR PRESSURE (mm Hg)	VAPOR DENSITY (Air=1)	EVAPORATION RATE	BOILING POINT (C)	FREEZING POINT
23 @ 20 DEG C	3.2	N/D	99	N/D
pH	SPECIFIC GRAVITY (Kg/l)	COCIT. WATER/OIL DIST.	SOLUBILITY IN WATER (20 C)	
N/D	0.85-0.91	N/D	NOT SOLUBLE	

SECTION IV FIRE AND EXPLOSION DATA


FLASH POINT
YES ☒ NO ☐ IF YES, UNDER WHICH CONDITIONS?
ON CONTACT WITH IGNITION SOURCE, FLAME OR TEMPERATURE ABOVE FLASH POINT

MEANS OF EXTINCTION

☒ CARBON DIOXIDE☒ FOAM☐ FOG SPRAY☒ DRY CHEMICAL☐ WATER STREAM☐ OTHER (SEE SPECIAL PROCEDURES)

SPECIAL PROCEDURES

FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. FOG NOZZLE FOR COOLING DRUMS.

FLASHPOINT (C) (METHOD)	LOWER FLAMMABLE LIMIT (% BY VOLUME)	UPPER FLAMMABLE LIMIT (% BY VOLUME)
-6	1.27	6.7
AUTO-IGNITION TEMPERATURE (C)	HAZARDOUS COMBUSTION PRODUCTS	
552	OXIDES OF CARBON	
EXPLOSIVE DATA 	SENSITIVITY TO IMPACT	SENSITIVITY TO STATIC DISCHARGE
	NONE	YES

SECTION V REACTIVITY DATA

CHEMICAL STABILITY	IF NO, UNDER WHICH CONDITIONS
YES ☒ NO ☐	
INCOMPATIBLE SUBSTANCES	IF YES, WHICH ONES
YES ☒ NO ☐	STRONG OXIDIZING AGENTS
REACTIVITY AND UNDER WHICH CONDITIONS?	NONE KNOWN
HAZARDOUS DECOMPOSITION	OXIDES OF CARBON

SECTION VI TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY



SKIN CONTACT



SKIN ABSORPTION



EYE CONTACT



INHALATION



INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT

IRRITATION OF EYES, NOSE, THROAT AND LUNGS. HEADACHE, DIZZINESS, IMPAIRMENT OF CO-ORDINATION. SKIN DERMATITIS POSSIBLE.

EFFECTS IF CHRONIC EXPOSURE TO PRODUCT

EXCESSIVE EXPOSURE CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.

LD-50-(ORAL)

N/D

LD-50-(DERMAL)

N/D

LC-50

N/D

EXPOSURE LIMITS

100 ppm (TLV)

IRRITANCY OF PRODUCT

MODERATE

SENSITIZATION

NON-SENSITIZER

CARCINOGENICITY

NON-CARCINOGENIC

TERATOGENICITY

NON-TERATOGENIC

REPRODUCTIVE TOXICITY

NONE KNOWN

MUTAGENICITY

NONE KNOWN

SYNERGISTIC PRODUCTS

NONE KNOWN

SECTION VII PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

SELF CONTAINED RESPIRATOR IF VENTILATION IS INADEQUATE. WEAR GOGGLES, FACE SHIELD AND RUBBER GLOVES WHEN HANDLING.

ENGINEERING CONTROLS

USE WITH ADEQUATE VENTILATION. ELECTRICAL AND MECHANICAL EQUIPMENT SHOULD BE SPARK PROOF.

LEAK AND SPILL PROCEDURES

REMOVE ALL IGNITION SOURCES, TURN OFF ALL ELECTRIC MOTORS, ABSORB WITH INERT MATERIAL. TRANSFER TO SECURE CONTAINERS FOR PROPER DISPOSAL. KEEP SPILLS AWAY FROM MUNICIPAL SEWERS.

WASTE DISPOSAL

INCINERATE IN ACCORDANCE WITH LOCAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT

KEEP CONTAINER CLOSED WHEN NOT IN USE.

STORAGE REQUIREMENTS

STORE IN FLAMMABLE GOODS AREA AWAY FROM ALL SOURCES OF DIRECT HEAT AND IGNITION.

SPECIAL SHIPPING INSTRUCTIONS

NONE

SECTION VIII FIRST AID MEASURES

EYE CONTACT

FLUSH EYES WITH GENTLE STREAM OF WATER FOR AT LEAST 15 MINUTES. CONTACT A PHYSICIAN.

SKIN CONTACT

RINSE EFFECTED AREAS WITH MILD SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. AND DISCARD CONTAMINATED SHOES. WASH CLOTHING BEFORE REUSE.

INHALATION

REMOVE VICTIM TO FRESH AIR. PROVIDE CPR AND OXYGEN IF NECESSARY.

ASPIRATION / INGESTION

DO NOT INDUCE VOMITING. IF VOMITING IS SPONTANEOUS, KEEP HEAD BELOW WAIST TO PREVENT ENTRY INTO LUNGS.

OTHER

IN ALL CASES SEE A PHYSICIAN IF ANY PROBLEMS PERSIST.

SECTION IX PREPARATION DATE OF MSDS

PREPARED BY

INTERNATIONAL EPOXIES & SEALERS

PHONE (800) 451-7206

DATED

NOV 1, 2001

WARRANTY AND DISCLAIMER: The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Pro Form Products knowledge. The information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Customer should read and understand this MSDS sheet and package labeling before using the product. SELLER DISCLAIMS ANY IMPLIED WARRANTIES OR MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Seller will at its option, either replace the goods sold or refund the purchase price. No warranty will apply if the goods are in any way altered or modified after delivery by the seller.