

MATERIAL SAFETY DATA SHEET

612
7/27/2005

Product Number: 612

Product Name: QUICK-WELD # 1 (Cyanoacrylate Adhesive)

Wesmar Products, Inc.
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

EMERGENCY PHONE: (INFOTRAC) (800) 535-5053
Information Phone (IES) (800) 451-7206

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Cyanoacrylate Adhesive
Product Type: Modified Cyanoacrylate Ester

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS NO.	%
Cyanoacrylate ester	Proprietary	90-95
Poly (methyl methacrylate)	9011-14-7	5-10
HYDROQUINONE	123-31-9	0.1-1

Ingredients, which have exposure limits

Exposure Limits: Ingredients	(TWA) ACGIH (TLV)	OSHA (PEL)	OTHER
Cyanoacrylate ester	None	None	0.2 ppm TWA
HYDROQUINONE	2mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWA 4 mg/m3 STEL

3. HAZARDS IDENTIFICATION

Toxicity: Skin contact may cause burns
Bonds skin rapidly and strongly
Skin and eye irritant

Primary Routes of Entry: None Known

Signs and Symptoms Of Exposure: Vapor is irritating to eyes and mucous membranes above TLV.
Exposure to vapors above the established limits may cause
Symptoms of non-allergic asthma.

Existing Conditions

Aggravated by Exposure: None Known

Ingredients	Literature Referenced Target organ and other Health Effects	Carcinogen NTP IARC OSHA
Cyanoacrylate ester	ALG IRR	NO NO NO
Poly (methyl methacrylate)	IRR	NO N/A NO
Cyanoacetate	NTO	NO NO NO

HYDROQUINONE BLO BNM CNS IMM IRR LIV MUT NO N/A NO SKI THY

Abbreviations

N/A Not Applicable	LIV Liver	BNM Bone Marrow	SKI Skin
BLO Blood	NTO No Target Organs	EYE eyes	
CNS Central nervous system	THY Thyroid	IRR Irritant	
IMM Immune System	ALG Allergen	MUT Mutagen	

MATERIAL SAFETY DATA SHEET

612
7/27/2005

4. First Aid Measures

Ingestion: Ingestion is not likely. See page 5 for emergency procedures.
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Soak in warm water. See page 5 for emergency procedures.
Eye Contact: Flush with water. See page 5 for emergency procedures.

5. Fire Fighting Measures

Flash Point: 185° F Method: Tag Closed Cup
Recommended
Extinguishing Agents: Carbon dioxide, foam, dry chemical
Special Firefighting
Procedures: Not Available
Hazardous Products Formed
By fire or thermal, decomp Irritating Organic vapors
Unusual fire or explosion Hazards None

Explosive Limits:
(% by volume in air) Lower Not Available
(% by volume in air) Upper Not Available

6. Accidental Release Measures

Steps to be taken in case
Of spill or leak: Flood with water to polymerize. Soak up with an inert Absorbent

7. Handling Controls, Personal Protection

Safe Storage: Store below 75° F
Handling: Avoid skin or eye contact. Avoid breathing vapor.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Safety glasses or goggles
Skin: Nitrile or polyethylene gloves and aprons
Do not use cotton
See supplemental page for additional information
Ventilation: Local ventilation may be desirable when using large amounts in a confined area.
Respiratory Not Available

See section 2 for Exposure Limits

9. Physical and Chemical Properties

Appearance: Water white to straw colored liquid
Odor: Negligible
Boiling Point: More than 300° F
Ph: Does not apply
Solubility in Water: Polymerized by water
Specific Gravity: 1.1
Volatile Organic Compound
(EPA Method 24) 32.9%; 345 grams per liter
Less than 20 g/l (California SCAQMD method 316B)
Vapor Pressure: Less than 0.02 mm Hg
Vapor Density: Not Available
Evaporation Rate:
(Ether=1) Not Available

MATERIAL SAFETY DATA SHEET

612
7/27/2005

10. Stability and Reactivity

Stability: Stable
Hazardous
Polymerization: Will not occur
Incompatibility: Polymerized by contacts water, alcohols, amines or alkalis
Conditions to avoid: Not Available
Hazardous
Decomposition
Products (non-thermal): None

11. Toxicological Information:

Estimated oral LD50 more than 5000 mg/kg
Estimated dermal LD50 more than 2000 mg/kg

12. Ecological Information

No Data Available

13. Disposal Considerations

Recommended methods of Disposal: Polymerize as above. Incinerate following EPA and local Regulations

EPA Hazardous waste Number: NH- Not a RCRA Hazardous waste Material

14. Transportation Information

DOT (49 CFR 172)

Domestic Ground Transport

Proper Shipping Name: Unrestricted (not more than 450 liters); Combustible Liquid
(More than 450 liters)

Identification Number: None (Not more than 450 liters);
NA 1993 (more than 450 liters)

Marine Pollutant: None

IATA

Proper Shipping Name: Unrestricted (Not more than one pint)
Aviation regulated liquid, n.o.s., (Cyanoacrylate Ester) (More than one pint)

Class or Division: Unrestricted (Not more than one pint);
Class 9 (More than one pint)

UN or ID Number: None (Not More than one pint)
UN 3334 (More than one pint)

15. Regulatory Information

CA Proposition 65: No California Proposition 65 chemicals are known to be present.

16. Other Information

Estimated NFPA(R) Code:

Health Hazard: 2

Fire Hazard: 2

Reactivity Hazard: 1

Specific Hazard: Does not apply

Estimated HMIS (R) Code:

Health Hazard: 2

MATERIAL SAFETY DATA SHEET

612
7/27/2005

Flammability Hazard: 2

16. Other Information

Reactivity Hazards: 1

Personal Protection: See Section 8

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

DISCLAIMER:

The information contained within this MSDS applies only to the product to which the sheet relates. The information provided is based on our best knowledge at the time of issue.

The information contained within this MSDS is believed to be accurate and is given in good faith. However, no warranty is made, either express or implied, regarding its accuracy or any liability arising out of the use of the information herein or the product supplied.

When used in other preparations, formulations, or in mixtures, it is necessary to ascertain whether the classifications of the hazards have changed. The attention of the user is drawn to the possibility of creating other hazards when the product is used for purpose other than that for which it was recommended. In such cases, a reassessment may be necessary and should be made by the user.

This safety data sheet should only be used and reproduced in order that the necessary measures are taken relating to the protection of health and safety at work.

It is the responsibility of the handlers to pass on the totality of the information contained within this document to any subsequent person(s) who will come in to contact with, handle or use this product in any way.

They should check the adequacy of the information provided within this MSDS before passing it on to their customers/staff.

INFORMATION FOR FIRST AID AND CASUALTY ON TREATMENT FOR ADHESION OF HUMAN SKIN TO ITSELF IF: CAUSED BY CYANOACRYLATE ADHESIVES

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue including skin in seconds. Experience has shown that accidents due to cyanoacrylates are handled best by passive, non-surgical first aid. Treatment of specific types of accidents are given below.

SKIN ADHESION

First immerse the bonded surfaces in warm soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g. a spatula or a teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action.

EYELID TO EYELID OR EYEBALL ADHESION

In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation.

ADHESIVE ON THE EYEBALL

Cyanoacrylate introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, generally covering several hours. This will cause periods of weeping until clearance is achieved. During the period of contamination, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

MOUTH

If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in ½ to 2 days. In case a lump forms in the mouth, position the patient to prevent ingestion of the lump when it detaches

BURNS

Cyanoacrylates give off heat on solidification. In rare cases a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.

SURGERY

It should never be necessary to use such drastic method to separate accidentally bonded skin.