

SF 1560

MATERIAL SAFETY DATA SHEET
acc. to ISO/DIS 110141560
9/18/2002

1 Identification of substance PRODUCT MANUFACTURED AFTER 8/16/2002

PRODUCT NUMBER: 1560

PRODUCT NAME: INTEGRA-360 (BLACK) URETHANE ADHESIVE & SEALANT

Application of the substance / the preparation : Polyurethane-sealant

Wesmar Products, Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

INFORMATION PHONE : (800) 451-7206

MSDS REVIEWED ON 9/18/2002

2 Composition/Data on components

Chemical characterization

Description:

Adhesive containing a polyurethane prepolymer based on
diphenylmethanediisocyanate

Dangerous components:

1330-20-7 xylene, mixed isomers, pure
Xn; R 10-20/21-38

5 ± 3 %

64742-47-8 Distillates (petroleum), hydrotreated light
Xn; R 65

<2 %

101-68-8 diphenylmethane-4,4'-diisocyanate
Xn; R 20-36/37/38-42/43

<0.1 %

Additional information:

For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

Information pertaining to particular dangers for man and environment:
Contains isocyanates. See information supplied by the manufacturer.

Classification system:

The classification was made according to the latest editions of
international substances lists, and expanded upon from company and
literature data.

4 First aid measures

General information:

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep
patient warm. Consult doctor if symptoms persist.In case of unconsciousness, stabilize patient in side position for
transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

The following symptoms may occur:

Dizziness

Headache

Dizziness

Nausea

5 Fire fighting measures

Suitable extinguishing agents:

Carbon dioxide

Foam

MATERIAL SAFETY DATA SHEET

acc. to ISO/DIS 11014

1560
9/18/2002

Fire-extinguishing powder

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards caused by the material, its products of combustion or resulting gases:
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NOx)
In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)
Isocyanates
- Protective equipment:
Wear self-contained respiratory protective device.

6 Accidental release measures

- Person-related safety precautions:
Ensure adequate ventilation
Keep away from ignition sources
- Measures for environmental protection:
Do not allow product to reach sewage system or any water course.
- Measures for cleaning/collecting:
Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Do not close them (reaction with water forming carbon dioxide)

7 Handling and storage

- Handling:
• Information for safe handling:
Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
- Storage:
• Requirements to be met by storerooms and receptacles:
Provide ventilation for receptacles.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
Keep receptacle tightly sealed.
Store in dry conditions.
Store in a cool place.

8 Exposure controls and personal protection

- Additional information about design of technical systems:
No further data; see item 7.
Components with limit values that require monitoring at the workplace:
1330-20-7 xylene, mixed isomers, pure
PEL: 435 mg/m³, 100 ppm
REL: Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
(o-, m-, & p-isomers)
TLV: Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI
- Additional information:
The lists that were valid during the creation were used as basis.
- Personal protective equipment:
• General protective and hygienic measures:
Avoid close or long term contact with the skin.
Wash hands before breaks and at the end of work.
Do not eat, drink or smoke while working.
Do not inhale gases / fumes / aerosols.

MATERIAL SAFETY DATA SHEET

acc. to ISO/DIS 11014

1560
9/18/2002

Pregnant women should strictly avoid inhalation or skin contact.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter AB

Protection of hands:

PVA, natural, butyl, nitrile or polychloroprene rubber gloves of superior quality

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

9 Physical and chemical properties

General Information

Form: Pasty

Color: Black

Odor: Light

	Value/Range	Unit	Method
--	-------------	------	--------

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 137 ° C

Flash point: 40-55 ° C

Flammability (solid, gaseous):

The product is not subject to classification because its speed of combustion is lower than the limit

Ignition temperature: 455 ° C

Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits:

Lower: 0.6 Vol %

Upper: 8 Vol %

Density: at 20 ° C 1.17

Solubility in / Miscibility with

Water: Insoluble.

10 Stability and reactivity

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Materials to be avoided:

Dangerous reactions

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with water forming carbon dioxide. Danger of receptacles bursting because of vapor overpressure.

Dangerous products of decomposition:

No dangerous decomposition products known.

MATERIAL SAFETY DATA SHEET

acc. to ISO/DIS 11014

1560
9/18/2002

11 Toxicological information

- Acute toxicity:
LD/LC50 values that are relevant for classification:
1330-20-7 xylene, mixed isomers, pure
Oral: LD50: 8700 mg/kg (rat)
Dermal: LD50: 2000 mg/kg (rbt)
Inhalative: LC50/4 h: 6350 mg/l (rat)
- Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
The product is not subject to classification according to internally approved calculation methods for preparations:

12 Ecological information

- General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- Product:
- Recommendation:
Must be disposed of in an incinerator for hazardous waste according to official regulations.
- Uncleaned packaging:
- Recommendation:
Disposal must be made according to official regulations.

14 Transport information

- DOT regulations:
- Hazard class: -
- Land transport ADR/RID (cross-border):
- ADR/RID class: -
- Maritime transport IMDG:
- IMDG Class: -
- Marine pollutant: No
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: -

* 15 Regulations

- Sara
Section 355 (extremely hazardous substances):
None of the ingredient is listed.
Section 313 (Specific toxic chemical listings):
1330-20-7 xylene, mixed isomers, pure
TSCA (Toxic Substances Control Act):
All ingredients are listed.
- Proposition 65
Chemicals known to cause cancer:
None of the ingredients is listed.
None of the ingredients is listed.

- | · Cancerogenity categories
- | EPA (Environmental Protection Agency)
- | 1330-20-7 xylene, mixed isomers, pure: D
- | IARC (International Agency for Research on Cancer)
- | 1330-20-7 xylene, mixed isomers, pure: 3
- | NTP (National Toxicology Program)
- | None of the ingredients is listed.
- | TLV (Threshold Limit Value established by ACGIH)
- | 1330-20-7 xylene, mixed isomers, pure: A4
- | MAK (German Maximum Workplace Concentration)
- | 101-68-8 diphenylmethane-4,4'-diisocyanate: 3
- | NIOSH-Ca (National Institute for Occupational Safety and Health)
- | None of the ingredients is listed.
- | OSHA-Ca (Occupational Safety & Health Administration)
- | None of the ingredients is listed.
- | · Product related hazard information:
- | The product has been classified and marked in accordance with
- | directives on hazardous materials.
- | · Special labelling of certain preparations:
- | Contains isocyanates. See information supplied by the manufacturer.
- | · National regulations:
- | · Classification according to Vbf: Void
- | · Water hazard class:
- | Water hazard class 2 (Self-assessment): hazardous for water.

| 16 Other information

| The information and recommendations provided herein are believed to be accurate as of
the date hereof. However, such information and recommendations are provided without
warranty of any kind and International Epoxies & Sealers disclaims any and all liability
or legal responsibility or use or reliance upon same.

—USA—