

Material Safety Data Sheet
acc. to ISO/DIS 11014

Manufactured After 12/11/2002

Reviewed on 04/14/2003

1 Identification of substance

Trade name: GLOSS BLACK ENAMEL
Product code: 4193
Manufacturer/Supplier: Wesmar Products
 1440 NW 45th St
 Seattle, WA 98107
 (206) 782-8186

2 Composition/Data on components**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

67-64-1	acetone	✗ Xi, F; R 11-36-66-67	21.18%
74-98-6	propane	F+; R 12	18.91%
108-88-3	toluene	✗ Xn, F; R 11-20	15.97%
106-97-8	n-butane	F+; R 12	11.11%
64742-89-8	VM&P Naptha	✗ Xn; R 20/22	7.0%
64742-47-8	Mineral Spirits	✗ Xn, F; R 11-65	2.95%
67-63-0	isopropyl alcohol	✗ Xi, F; R 11-36-67	2.48%
108-65-6	PM acetate	✗ Xi; R 10-36	1.78%

Additional information: For the wording of the listed risk phrases refer to section 3.**3 Hazards identification****Hazard description:**Xn Harmful
F+ Extremely flammable**Physical and environmental dangers:**

Warning! Pressurized container.
 R 12 Extremely flammable.
 R 20 Harmful by inhalation.
 R 36 Irritating to eyes.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
 Keep out of the reach of children.

NFPA ratings (scale 0 - 4): Health = 1

Fire = 4

Reactivity = 3

HMIS-ratings (scale 0 - 4): Health = 1

Fire = 3

Physical Hazard = 3

4 First aid measures**General information:**

Symptoms of poisoning may occur even after several hours. Medical observation for at least 48 hours after the accident is recommended.

After inhalation:

In case of unconsciousness, place patient in side position for transportation. Supply fresh air. If necessary, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Consult a doctor if symptoms persist.

5 Fire fighting measures**Extinguishing agents:**

CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment:

Mount respiratory protective device.

6 Accidental release measures**Personal safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Environmental safety precautions:

Do not allow product to reach sewage systems or ground water. Inform appropriate authorities in case of seepage into water course or sewage system.

(Contd. on page 2)
- USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Manufactured After 12/11/2002

Reviewed on 04/14/2003

Trade name: GLOSS BLACK ENAMEL

(Contd. of page 1)

Measures for cleaning/collecting:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage**Safe handling information:**

Ensure good ventilation/exhaustion at the workplace.
Handle carton and cans with care.

Fire/explosion protection:

Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

Storage requirements:

Observe official regulations on storing packagings with pressurized containers. Consult with your local authorities.
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:**Components with limit values that require monitoring at the workplace:****67-64-1 acetone**

PEL 2400 mg/m³, 1000 ppm
REL 590 mg/m³, 250 ppm
TLV Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 1188 mg/m³, 500 ppm
BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
REL 1800 mg/m³, 1000 ppm
TLV 4508 mg/m³, 2500 ppm

108-88-3 toluene

PEL Short-term value: C 300; 500* ppm
Long-term value: 200 ppm
*10-min peak per 8-hr shift
REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
TLV 188 mg/m³, 50 ppm
Skin; BEI

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
TLV 1900 mg/m³, 800 ppm

67-63-0 isopropyl alcohol

PEL 980 mg/m³, 400 ppm
REL Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm
TLV Short-term value: (1230) mg/m³, (500) ppm
Long-term value: (983) mg/m³, (400) ppm
NIC-200; 491; 400; 984; A 4

Protective hygienic measures:

Keep away from foodstuffs, beverages, and animal feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

Breathing equipment:

For episodes of brief exposure, use a respiratory filter device. In cases of intensive or longer exposures, use a respiratory protective device that is independent of circulating air.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties:**General Information:**

Form: Aerosol
Color: According to trade name description in section 1.
Boiling point/Boiling range: -44°C (-47°F)
Flash point: -19°C (-2°F)
Ignition temperature: 365.0°C (689°F)

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Manufactured After 12/1/2002

Reviewed on 04/14/2003

Trade name: GLOSS BLACK ENAMEL

(Contd. of page 2)

Auto igniting:	Product is not self-igniting.
Danger of explosion:	Heating may cause an explosion. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.2 Vol %
Upper Explosion Limit:	13.0 Vol %
Vapor pressure at 20°C (68°F):	8300.0 hPa (6226 mm Hg)
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	0.60 kg/l / 5.02 lb/gal
VOC in weight percent (less acetone):	60.2 %
Solids content:	18.7 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Dangerous reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect.
Primary effect on the eye: Irritating effect.
Sensitization: No sensitizing effects known.
Additional toxicological information: Harmful

12 Ecological information

Other information: This product does not contain any chlorinated solvents or lead. No specific ecological data is available for this product.
Aquatic toxicity: Harmful to aquatic organisms.
Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Do not dispose with household garbage. Do not allow product to reach sewage system.

14 Transport information:

Hazard class: 2.1
Identification number: N/A
Label: 2.1
ADR/RID class: 2 5F Gases
UN-Number: 1950
IMDG Class: 2.1
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No
ICAO/IATA Class: 2.1
Proper shipping name: Aerosols, Flammable
Consumer Commodity ORM-D

15 Regulations**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 toluene

67-63-0 isopropyl alcohol

TSCA (Toxic Substances Control Act):

67-64-1 acetone

74-98-6 propane

108-88-3 toluene

106-97-8 n-butane

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Manufactured After 12/11/2002

Reviewed on 04/14/2003

Trade name: GLOSS BLACK ENAMEL

(Contd. of page 3)

71243-64-6	V.T. Alkyd Resin
64742-89-8	VM&P Naptha
68240-01-7	Hydrocarbon Resin
64742-47-8	Mineral Spirits
67-63-0	isopropyl alcohol
108-65-6	PM acetate
1333-86-4	Carbon black

PROPOSITION 65 Chemicals known to cause cancer:

None of the ingredients in this product are listed.

PROPOSITION 65 Chemicals known to cause reproductive toxicity:

108-88-3 | toluene

Canadian WHMIS: This product has been classified according to the Controlled Product Regulations and the MSDS contains all the necessary information required by the CPR.

EPA:

Class B, D5---Flammable Aerosols

A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1	acetone	D
108-88-3	toluene	D

IARC:

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	toluene	3
67-63-0	isopropyl alcohol	3
1333-86-4	Carbon black	2B

ACGIH TLVs:

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1	acetone	A4
108-88-3	toluene	A4
1333-86-4	Carbon black	A4

NIOSH:

1333-86-4	Carbon black
-----------	--------------

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

—USA—