

SF 4514

6/22/01

4514

MATERIAL SAFETY DATA SHEET

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

SECTION I - PRODUCT IDENTIFICATION

PART NUMBER: 4514
PRODUCT NAME: Belt Dressing
TRADE NAME/SYNONYMS: Belt Dressing

Health	2
Flammability	4
Reactivity	0
Special	

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	STEL	%
*Heptane	142-82-5	500 PPM	400 PPM	500 PPM	1-5
*Methylene Chloride	75-09-02	25 PPM	25 PPM		30-55
Propane/Isobutane/ N-Butane	68476-86-8	800 PPM	800 PPM		5-15

* See Section VIII ADDITIONAL INFORMATION

DOT Shipping - Consumer Commodity ORM-D

SECTION III - PHYSICAL DATA

Appearance/Odor: Black Liquid, Solvent Odor	Solubility In Water: Nil
Boiling Point Range: -40°F to 209°F	Specific Gravity: 1.101 H ₂ O=1 at STP
Vapor Pressure PSIG @ 70°F: 30-40	Melting Point - Liquid: N/A
Vapor Density (Air=1) Heavier than air: Yes	Evaporation Rate (Water=1): Slower

SECTION IV - FIRE AND EXPLOSION HAZARD / REACTIVITY DATA

Flash Point (Method Used): -156°F PROPELLANT	Flammable Limits	LEL	UEL
PRODUCT HAS A FLASH POINT OF 15°F		: 1.8	: 9.5

Extinguishing Media: Use water fog, dry chemical or carbon dioxide.

Special Fire Fighting Procedures: Fire fighters should wear NIOSH approved positive pressure self-contained breathing apparatus. Aerosol cans may rupture when heated.

Unusual Fire & Explosion Hazards: Heated cans may burst.

Stability: Stable.

Conditions To Avoid: All sources of ignition.

Incompatibility (Materials To Avoid): Strong Acids, Alkalis, Oxidizers.

Hazardous Decomposition or Byproducts: Carbon Dioxide, Carbon Monoxide and other noxious gases from burning hydrocarbons.

Hazardous Polymerization: Will not occur.

Conditions To Avoid: None.

SECTION V - HEALTH HAZARD DATA

Routes Of Entry: Inhalation, Skin, Ingestion.

Health Hazards (Acute and Chronic): May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long term exposure (years) to vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system: HEPTANE, METHYLENE CHLORIDE

Carcinogenicity	NTP?	IARC Monographs	OSHA Reg.?
METHYLENE CHLORIDE	2B	2B	Yes

continued

SECTION V - HEALTH HAZARD DATA (CONTINUED)

Signs And Symptoms Of Overexposure: INHALATION: Difficulty in breathing. SKIN: Redness. INGESTION: Vomiting.

- Alcohol consumed before or after exposure may increase adverse effects.
- Over exposure may cause dizziness and loss of concentration.

Medical Conditions: Generally aggravated by overexposure. See Section VIII.

Emergency and First Aid Procedures: Give oxygen - do not induce vomiting - gastric lavage - wash eyes and skin with water. Remove to fresh air, contact physician immediately.

SECTION VI - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Use absorbent sweeping compound to soak up material. Pour into container. Dispose as hazardous waste.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

Precautions To Be Taken In Handling And Storing: Keep away from heat, sparks or open flame. Store at temperatures below 120° F.

Other Precautions: Avoid prolonged breathing of vapors. Always use with adequate ventilation.

SECTION VII - EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Respiratory Protection: Self contained breathing apparatus if above TLV limits are exceeded.

Ventilation: Local exhaust: YES Mechanical: NONE Special: NONE Other: NONE.

Protective Gloves: Suggested, but none required if spraying.

Eye Protection: Safety glasses or goggles.

Other Protective Clothing Or Equipment: Long sleeves and long pants or coveralls.

Do not smoke while using. Wash hands after use.

- Concentrated vapors of this product are heavier than air and will collect in low areas, pits, storage tanks and other confined spaces. Do not enter these areas.
- Avoid breathing vapors.
- Keep out of the reach of children.
- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage and nervous system damage. Intentional misuse by concentrating and inhaling this product may be harmful or fatal.
- If you have a medical condition consult with a physician prior to using this product.

SECTION VIII - ADDITIONAL INFORMATION

* Starred items are subject to the reporting requirements of SARA 313 and 40 CFR 372. If any of the components in Section II are preceded by a star (*) you must notify each person to whom this product is sold.

CALIFORNIA PROPOSITION 65

Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

CAS No.	Chemical Compound	%
75-09-2	Methylene Chloride	30-55

NEW JERSEY RIGHT TO KNOW: See Section II

ADDITIONAL INFORMATION: % VOC: 57.125

#/GAL VOC: 5.238

DOT: Ship as ORM-D

HMIS RATING

Health: 2

Flammability: 4

Reactivity: 0

Personal Protection: B

DISCLAIMER

The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and INTERNATIONAL EPOXIES & SEALERS disclaims any and all liability or legal responsibility or use or reliance upon same.