

SF 4586

1/18/00

4586

MATERIAL SAFETY DATA SHEET

Wesmar Products, Inc.
1440 NW 45th St
Seattle, Wa 98107
(206) 782-8186

24 HOUR EMERGENCY EPHONE (INFOTRAC) 800-535-5053

INFORMATION PHONE: (800) 451-7206

SECTION I - PRODUCT IDENTIFICATION

PART NUMBER: 4586
PRODUCT NAME: Battery Cleaner & Leak Detector
TRADE NAME/SYNONYMS: Battery Cleaner / Acid Detector

Health	2
Flammability	4
Reactivity	0
Special	

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	STEL	%
*2-Butoxyethanol	111-76-2	50 PPM	50 PPM	SKIN	0.5-1
Propane/Isobutane/ N-Butane	68476-86-8	800 PPM	800 PPM		5-15
Teiethanolamine	102-71-6	NE	5 MG/M3		0.1-2

* See Section VIII ADDITIONAL INFORMATION

DOT Shipping: Consumer Commodity ORM-D

SECTION III - PHYSICAL DATA

Appearance/Odor: Yellowish Liquid, Amine/Solvent Odor
Boiling Point Range: -40°F to 340°F
Vapor Pressure PSIG @ 70°F: 30-40
Vapor Density (Air=1) Heavier than air: Yes

Solubility In Water: Complete
Specific Gravity: 1.047 H2O=1 at STP
Melting Point - Liquid: N/A
Evaporation Rate (Water=1): Equal

SECTION IV - FIRE AND EXPLOSION HAZARD / REACTIVITY DATA

Flash Point (Method Used): -156°F PROPELLANT Flammable Limits LEL UEL
Water base product, not expected to burn. : 1.8 : 9.5

Extinguishing Media: Use water fog, dry chemical or carbon dioxide.

Special Fire Fighting Procedures: Fire fighters should wear NIOSH approved positive pressure self-contained breathing apparatus. Aerosol cans may rupture when heated.

Unusual Fire & Explosion Hazards: Heated cans may burst.

Stability: Stable.

Conditions To Avoid: All sources of ignition.

Incompatibility (Materials To Avoid): Strong Acids, Alkalis, Oxidizers.

Hazardous Decomposition or Byproducts: Carbon Dioxide, Carbon Monoxide, Oxides of Nitrogen and other by-products of incomplete combustion.

Hazardous Polymerization: Will not occur.

Conditions To Avoid: None.

SECTION V - HEALTH HAZARD DATA

Routes Of Entry: Inhalation, Skin, Ingestion.

Health Hazards (Acute and Chronic): May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long term exposure (years) to vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system: 2-Butoxyethanol

Carcinogenicity NTP? IARC Monographs OSHA Reg.?
2-Butoxyethanol (Animal Testing Only)

continued

SECTION V - HEALTH HAZARD DATA CONTINUED

Signs And Symptoms Of Overexposure: INHALATION: Difficulty in breathing. SKIN: Redness. INGESTION: Vomiting.

- Alcohol consumed before or after exposure may increase adverse effects.
- Over exposure may cause dizziness and loss of concentration.

Medical Conditions: Generally aggravated by overexposure. See Section VIII.

Emergency and First Aid Procedures: Give oxygen - do not induce vomiting - gastric lavage - wash eyes and skin with water. Remove to fresh air, contact physician immediately.

SECTION VI - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Use absorbent sweeping compound to soak up material. Pour into container. Dispose as hazardous waste.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

Precautions To Be Taken In Handling And Storing: Keep away from heat, sparks or open flame. Store at temperatures below 120°F.

Other Precautions: Avoid prolonged breathing of vapors. Always use with adequate ventilation.

SECTION VII - EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Respiratory Protection: Self contained breathing apparatus if above TLV limits are exceeded.

Ventilation: Local exhaust: YES Mechanical: NONE Special: NONE Other: NONE.

Protective Gloves: Suggested, but none required if spraying.

Eye Protection: Safety glasses or goggles.

Other Protective Clothing Or Equipment: Long sleeves and long pants or coveralls.

Work/Hygenic Practices: Do not smoke while using. Wash hands after use.

- Concentrated vapors of this product are heavier than air and will collect in low areas, pits, storage tanks and other confined spaces. Do not enter these areas.
- Avoid breathing vapors.
- Keep out of the reach of children.
- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage and nervous system damage. Intentional misuse by concentrating and inhaling this product may be harmful or fatal.
- If you have a medical condition consult with a physician prior to using this product.

SECTION VIII - ADDITIONAL INFORMATION

- * Starred items are subject to the reporting requirements of SARA 313 and 40 CFR 372. If any of the components in Section II are preceded by a star (*) you must notify each person to whom this product is sold.

CALIFORNIA PROPOSITION 65:

Warning: This product Does not contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

NEW JERSEY RIGHT TO KNOW: See Section II

ADDITIONAL INFORMATION: % VOC: 15.563

#/GAL VOC: 1.358

DOT: Ship as ORM-D

HMIS RATING:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

DISCLAIMER

The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and International Epoxies & Sealers disclaims any and all liability or legal responsibility or use or reliance upon same.