

SF 8500

MATERIAL SAFETY DATA SHEET

8500

..... 09-15-03

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107

(206) 782-8186

PRODUCT IDENTIFICATION

Product Name: **8500A** Acrylic Structural Adhesive

Product Type: Structural Acrylic

1. COMPOSITION

<u>Ingredients</u>	<u>Cas #</u>	<u>%</u>
Polyurethane methacrylate resin	Trade secret	20-30
High boiling acrylate	7534-94-3	20-25
Hydroxyalkyl methacrylate	868-77-9	40-60
METHACRYLIC ACID	79-41-4	5-10
Modified silicone dioxide	11295-52-5	1-5
tert-BUTYL PEROXYBENZOATE	614-45-9	0.1-1.0
MALEIC ACID	110-16-7	0.1-1.0
SACCHARIN	81-07-2	0.1-1.0

2. CHEMICAL AND PHYSICAL PROPERTIES

Vapor Pressure:	Less than 10mm @ 80°F
Vapor Density:	Not available
Solubility in Water:	Slight
Specific Gravity:	1.08 @ 80°F
Boiling Point:	More than 300°F
Volatile Organic Compound	0 %
Evaporation Rate (Ether = 1)	Not available
pH:	Does not apply
Appearance:	Translucent amber tan paste
Odor:	Sharp, irritating

3. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash Point: 200°F Method:	(PMCC)
Estimated NFPA Code:	
Health Hazard:	2
Fire Hazard:	1
Reactivity Hazard:	1
Specific Hazard:	Does not apply
Estimated HMIS Code:	
Health Hazard:	2
Flammability Hazard:	1
Reactivity Hazard:	1
Personal Protection:	See Section 9

Explosive Limits:	
(% by volume in air)	Lower Not available
(% by volume in air)	Upper Not available
Recommended Extinguishing Agents:	Carbon dioxide, foam, dry chemical
Hazardous Products Formed by Fire or Thermal Decomposition:	Irritating organic vapors & oxides of carbon & nitrogen
Unusual Fire or Explosion Hazards:	None
Compressed Gases:	None
Pressure at Room Temp.:	Does not apply

***** 09-15-03

4. SPILL OR LEAK AND DISPOSAL PROCEDURES

Steps to be taken in case of spill or leak: Remove sources of ignition. Maintain adequate ventilation. Soak up with an inert absorbent. Store in a partly filled, closed container until disposal. Recommended methods of disposal: Incinerate following EPA and local regulations.

5. STORAGE AND HANDLING PROCEDURES

Storage: Store at or below 100°F to preserve shelf life.
Handling: Avoid prolonged breathing of vapors. Keep away from eyes. Avoid prolonged skin contact. Keep away from sources of ignition.

6. SHIPPING REGULATIONS

DOT and IATA Hazard Classification: Not Restricted Article
Proper DOT Shipping Name: Unrestricted
Identification Number: DOT - None IATA - None

7. REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will not occur.
Hazardous Decomposition Products
(non-thermal): None
Incompatibility: None

8. EMERGENCY TREATMENT PROCEDURES

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Wash with soap and water.
Eye Contact: Flush with water for at least 15 minutes. Obtain medical attention.

9. PERSONAL PROTECTION

Eyes: Safety glasses or goggles.
Skin: Rubber or plastic gloves.
Ventilation: Sufficient to maintain vapor concentration below TLV.

10. HEALTH HAZARD DATA

Toxicity: Eye and skin irritant. Estimated oral LD50 more than 5,000 mg/kg. Estimated dermal LD50 more than 2,000 mg/kg.
Primary Routes of Entry: None known
Signs and Symptoms of Exposure: May cause dermatitis on prolonged contact in sensitive individuals.

Existing Conditions Aggravated
By Exposure: None known.

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (TLV)	OTHER
High boiling acrylate	None	None	5 ppm
Hydroxyalkyl methacrylate	None	None	3 ppm
METHACRYLIC ACID	20 ppm skin	20 ppm skin	None
Modified Silicone Dioxide	10 mg/m ³	6 mg/m ³	3 mg/m ³

MATERIAL SAFETY DATA SHEET

8500

***** 09-15-03

Exposure Limits (STEL)	ACGIH	OSHA
Ingredients	6(TLV)	(PEL)

Ingredients for which no Exposure Limits have been established are not listed above.

Ingredients	Literature Referenced Target Organ and Other Health Effects	Carcinogen		
		NTP	IARC	OSHA
Polyurethane methacrylate resin	No Data	NO	NO	NO
High boiling acrylate	No Data	NO	NO	NO
Hydroxyalkyl methacrylate	No Data	NO	NO	NO
METHACRYLIC ACID	IRR	NO	NO	NO
Modified silicone dioxide	No Data	NO	NO	NO
Tert-BUTYL PEROXYBENZOATE	MUT	NO	NO	NO
MALEIC ACID	IRR	NO	NO	NO
SACCHARIN	MUT	YES	2B	NO

Abbreviations

2B	Possibly carcinogenic to humans	IRR	Irritant
MUT	Mutagen		

DISCLAIMER

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND INTERNATIONAL EPOXIES & SEALERS DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.

***** 09-15-03

INTERNATIONAL EPOXIES & SEALERS

30241 Commerce Drive, San Antonio, FL 33576

24 Hour Emergency call Infotrac : 800-535-5053

Information Phone: 800-451-7206

PRODUCT IDENTIFICATIONProduct Name: **8500P** Activator / Primer

Product Type: Activator

1. COMPOSITION

<u>Ingredients:</u>	<u>Cas #</u>	<u>%</u>
Acetone	67-64-1	70-85
Aldehyde-amine condensation	Proprietary	5-25
Adhesion Promotion Agent	Proprietary	1-5

2. CHEMICAL AND PHYSICAL PROPERTIES

Vapor pressure:	Not Defined
Vapor density:	2.0
Solubility in water:	High
Specific gravity:	0.815
Boiling point:	56 C
Volatile Organic Compound	NA
Evaporation rate: (Ether = 1)	Not Available
pH:	Does not apply
Appearance:	Amber liquid
Odor:	Acetone

3. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash point:	Approximately 0°F Method: TCC
Estimated NFPA Code:	
Health hazard:	2
Fire hazard:	3
Reactivity hazard:	0
Specific hazard:	Does not apply
Estimated HMIS Code:	
Health hazard:	2
Flammability hazard:	3
Reactivity hazard	0
Personal Protection	See Section 9
Recommended extinguishing agents:	Carbon dioxide, dry chemical, foam
Hazardous products formed by	
fire/thermal decomposition:	Irritating organic vapors
Compressed gases:	None
Pressure at room temperature:	Does not apply

4. SPILL OR LEAK AND DISPOSAL PRODUCERS

Steps to be taken in case of spill or leak:	Avoid flame and sparks. Maintain adequate ventilation. Soak up in an inert absorbent and store in a closed container until disposal.
Recommended methods of disposal:	Follow EPA and local regulations.

***** 09-15-03

5. STORAGE AND HANDLING PROCEDURES

Storage: Store away from flames and sparks. Store below 80°F to preserve shelf life.
Handling: Avoid prolonged breathing of vapors. Avoid prolonged skin contact. Keep away from eyes.

6. SHIPPING REGULATIONS

DOT (49 CFR 172)

Proper shipping name	Ground: Consumer Commodity (Not more than one quart); Air: Consumer Commodity (Not more than one quart); Acetone solution (More than 1 quart).
Hazard class of division	Ground: ORM-D (Not more than one quart); Flammable liquid (More than one quart) Air: ORM-D (Not more than one quart); Flammable liquid (More than one quart)
Identification number	None (Not more than one quart) UN 1090 (More than one quart)
Proper shipping name	Acetone solution
Class or division	Class 3, Packing Group II
UN or ID number	UN 1090
IMO	
Substance	Not available
Marine	Pollutant Status Not available
Class	Not available
Subsidiary Risk Label	Not available
IMDG Code Page	Not available
UN Number	Not available

7. REACTIVITY DATA

Stability:	Stable Hazardous polymerization: Will not occur
Hazardous decomposition products (non-thermal)	None
Incompatibility:	Strong oxidizers

8. EMERGENCY TREATMENT PROCEDURES

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.
Skin contact: Wash with soap and water.
Eye contact: Flush at least 15 minutes with water. Obtain medical attention.

9. PERSONAL PROTECTION

Eyes: Safety glasses or goggles
Skin: Rubber or plastic gloves
Ventilation: Sufficient to maintain vapor concentration below TLV.

10. HEALTH HAZARD DATA

Toxicity: Possible eye irritant. Moderately toxic by ingestion.
Estimated dermal LD50 greater than 2000 mg/kg.
Primary Routes of Entry: Inhalation, ingestion, contact.
Signs & Symptoms of Exposure: Vapors irritate eyes, nose and throat. Liquid is an eye irritant and may irritate skin.

MATERIAL SAFETY DATA SHEET

8500

..... 09-15-03

Existing Conditions Aggravated by Exposure: Eye disorders from aldehyde-amine condensation.

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Acetone	750 ppm TWA 1780 mg/m ³	1000 ppm TWA 2400 mg/m ³	None
Aldehyde-amine condensation	None	None	None
Adhesion Promotion agent	None	None	None

Literature Referenced Carcinogen

Ingredients	Target Organ and Other Health Effects	NTP	IARC	OSHA
Acetone	IRR KID LIV MET NER	NO	NO	NO
Aldehyde-amine Condensation	Irritant	NO	NO	NO
Adhesion Promotion	Irritant	NO	NO	NO

Abbreviations

N/A Not Applicable NER Nervous System IRR Irritant
KID Kidney LIV Liver MET Metabolic

DISCLAIMER

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND INTERNATIONAL EPOXIES & SEALERS, DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.