

SF 8505

MATERIAL SAFETY DATA SHEET

8505

Date of Preparation: 10/01/03

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: INTER-WELD 5 MSA Part A Activator

Item Numbers 8505 Part A

Product Use/Class: Methacrylate Structural Adhesive

MANUFACTURER: Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

24 HOUR EMERGENCY PHONE (INFOTRAC) (800) 535-5053
INFORMATION PHONE (800) 451-7206

SECTION 2. - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT.
1	Methyl Methacrylate (MMA)	80-62-6	40-75
2	Amine condensate	Trade Secret	1-10

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)**EXPOSURE LIMITS 8 hrs. TWA (ppm)**

ITEM	ACGIH TLV	OSHA PEL	OTHER
1	100ppm	100ppm	100ppm (Canada)

SECTION 3. - HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW:**

PHYSICAL STATE: Liquid. COLOR: Milky white. ODOR: Pungent. Acrylic.

WARNING! FLAMMABLE LIQUID AND VAPOR. MAY CAUSE ALLERGIC SKIN REACTION

MAY CAUSE EYE, SKIN, AND RESPIRATORY TRACT IRRITATION

POTENTIAL HEALTH EFFECTS:**EYE:**

Moderate eye irritation. Redness. Excess tearing.

SKIN:

Allergic skin reaction. Itching. Moderate skin irritation. Redness.

INGESTION:

Toxicity by ingestion is not likely to occur.

INHALATION:

Moderate respiratory tract irritation. Shortness of breath. Coughing.

CHRONIC:

Detailed information provided in section 11.

CONDITIONS AGGRAVATED BY EXPOSURE: Respiratory disorders. Skin disorders. Eye disorders

MATERIAL SAFETY DATA SHEET

8505

..... Date of Preparation: 10/01/03

SECTION 4. - FIRST AID MEASURES

EYE:

Immediately flush eyes with water for at least 20 minutes. Get immediate medical attention.

SKIN:

Wash thoroughly with soap and water. Discard contaminated clothing. Do not use organic solvents. If irritation occurs, get medical attention.

INHALATION:

Remove person to fresh air or apply artificial respiration if not breathing. Get medical attention if short of breath or if respiratory symptoms develop.

INGESTION:

Give 1-2 glasses of milk or water to conscious person. Get immediate medical attention. **DO NOT INDUCE VOMITING.**

SECTION 5. - FIRE FIGHTING MEASURES

Flashpoint and Method: 51F (TCC)

Autoignition Temperature: NA

Flammable Limits: 2.1 MMA, Upper 12.5 for MMA

EXTINGUISHING MEDIA: Flammable liquid, insoluble in water. Use DRY chemical powder

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

HAZARDOUS COMBUSTION PRODUCTS:

Oxides of carbon and nitrogen. Hydrogen cyanide. Methylene bisphenyl isocyanate. Hydrocarbons. Smoke.

Cyclopentanone. Butanediol. Tetrahydrofuran.

SECTION 6. - ACCIDENTAL RELEASE MEASURES

Remove sources of ignition. Use with ventilation. Dike area to prevent spreading. Absorb on vermiculite, sand or other inert absorbing material. Dispose of as chemical waste in accordance with current local, state, and federal regulations. Do not discharge into water. Incineration recommended. Wash spill area with strong detergent. After proper mixing of resin and activator sides, the material will polymerize into a cured solid state which can be treated as a nonhazardous solid. Applicable CERCLA/RCRA waste code:0001(ignitability) U162 (MMA)

SECTION 7. - HANDLING AND STORAGE

HANDLING:

Avoid prolonged or repeated breathing of vapor. Avoid contact with skin and eyes. Wash hands before smoking or eating.

STORAGE:

Avoid storage over 100F, contamination with incompatible materials. Store in cool place. Do not store in direct sunlight.

Recommended storage in flammable material containment area

SECTION 8. - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Use local exhaust ventilation if the potential for airborne exposure exists

PERSONAL PROTECTION:

RESPIRATORY PROTECTION:

Use NIOSH approved respirator if there is potential to exceed any exposure limit(s).

SKIN PROTECTION: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

MATERIAL SAFETY DATA SHEET

8505

..... Date of Preparation: 10/01/03

EYE PROTECTION: Chemical splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: NA

SECTION 9. - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: 29mm at 20C

Vapor Density: >1 Heavier than air, 3.5 for MMA

Solubility in H2O: Slight

Specific Gravity: 0.94-1.0

Boiling Point: 214F for MMA

Freezing Point: NA

Physical State: Liquid

pH: NA

Odor: Pungent. Acrylic

Appearance: Light gel, milky white in color

VOC: 1.98%; 1.92 g/l (adhesive & activator mixed)

SECTION 10. -STABILITY AND REACTIVITY

STABILITY: Stable

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

No known conditions to avoid. Oxidizing agents, Alkalies, Moisture. Strong acids. Strong bases. Reducing agent.

Ultraviolet radiation. Amines

HAZARDOUS POLYMERIZATION:

May occur. Excessive aging. Excessive heat. Polymerization catalysts. Oxygen-free atmosphere. Inhibitor depletion. Direct sunlight.

HAZARDOUS DECOMPOSITION PRODUCTS:

None known

SECTION 11. - TOXICOLOGICAL INFORMATION

PRODUCT TOXICOLOGY DATA: Not available

Ingredients	Carcinogen		
	NTP	IARC	OSHA
Methyl methacrylate	No	N/A	No
Amine condensate	No	No	No

Ingredients	Target Organ and other health effects
Methyl methacrylate	Allergen. Irritant. Nervous System. Respiratory. Kidney. Liver
Amine condensate	Not available

SECTION 12. - ECOLOGICAL INFORMATION

Not available

SECTION 13. - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Dispose according to EPA and local governmental regulations. EPA Hazardous waste # 0001;UI62;DO03

MATERIAL SAFETY DATA SHEET

8505

..... Date of Preparation: 10/01/03

SECTION 14. - TRANSPORT INFORMATION DOT (49 CFR 172)

PROPER SHIPPING NAME: Adhesives

IDENTIFICATION NUMBER: Un1133

HAZARD CLASS: 3

PACKING GROUP II

EXCEPTIONS: Single unit less than or equal to 1 liter

PROPER SHIPPING NAME: Consumer Commodity

CLASS / DIVISION: ORM-D

INTERNATIONAL AIR TRANSPORTATION (IATA)

PROPER SHIPPING NAME: Adhesives

IDENTIFICATION NUMBER: UN1133

PACKING GROUP: II

CLASS/DIVISION: 3

EXCEPTIONS: Consumer Commodity, Class 9, ID 8000, less than 500ml.

SECTION 15. - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act):

All components are listed on or exempt from listing on the Toxic Substances Control Act Inventory,

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act): NA

SARA TITLE III (Superfund Amendments and Reauthorization Act):

313 Reportable Ingredients: Methyl Methacrylate

CANADIAN INVENTORY STATUS:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List

CALIFORNIA PROPOSITION 65:

This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm

SECTION 16. - OTHER INFORMATION

NFPA

Health 2 Fire 3 Reactivity 2 Special None

Hazardous Materials Information System (HMIS) Ratings:

Health 2 Flammability 3 Reactivity 2 Protective Equipment: see section 8

REVISION SUMMARY: Change to 16-section format.

PREPARED BY: Steve Busch

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Supplier's knowledge, or is obtained from sources believed by the Supplier to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Supplier assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the Supplier assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

MATERIAL SAFETY DATA SHEET

8505

Date of Preparation: 10/01/03

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: INTER-WELD 5 MSA Part B Resin

Item Numbers 8505 Part B

Product Use/Class: Methacrylate Structural Adhesive

MANUFACTURER: INTERNATIONAL EPOXIES AND SEALERS
30241 COMMERCE DRIVE
SAN ANTONIO, FL 33576

24 HOUR EMERGENCY PHONE (INFOTRAC) (800) 535-5053
INFORMATION PHONE (800) 451-7206

SECTION 2. - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT.
1	Methyl Methacrylate (MMA)	80-62-6	40-75
2	Cumene hydroperoxide	80-15-9	1-10
3	p-toluenesulfonyl chloride	98-59-9	1-10
4	Methacrylic acid	79-41-4	1-10

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

EXPOSURE LIMITS 8 hrs. TWA (ppm)

ITEM	ACGIH TLV	OSHA PEL	OTHER
1	100ppm	100ppm	100ppm (Canada)
2	NONE	NONE	SKIN
3	NA	NA	NA
4	20ppm (Skin)	20ppm (Skin)	NONE

SECTION 3. - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

PHYSICAL STATE: Liquid. COLOR: Milky white. ODOR: Pungent. Acrylic.

WARNING! FLAMMABLE LIQUID AND VAPOR. MAY CAUSE ALLERGIC SKIN REACTION

MAY CAUSE EYE, SKIN, AND RESPIRATORY TRACT IRRITATION

POTENTIAL HEALTH EFFECTS:

EYE: Moderate eye irritation. Redness. Excess tearing.

SKIN:

Allergic skin reaction. Itching. Moderate skin irritation. Redness.

INGESTION:

Toxicity by ingestion is not likely to occur.

INHALATION:

Moderate respiratory tract irritation. Shortness of breath. Coughing.

CHRONIC:

Detailed information provided in section 11.

8505

CONDITIONS AGGRAVATED BY EXPOSURE: Respiratory disorders. Skin disorders. Eye disorders

EYE:

Immediately flush eyes with water for at least 20 minutes. Get immediate medical attention.

SKIN:

Wash thoroughly with soap and water. Discard contaminated clothing. Do not use organic solvents. If irritation occurs, get medical attention.

INHALATION:

Remove person to fresh air or apply artificial respiration if not breathing. Get medical attention if short of breath or if respiratory symptoms develop.

INGESTION:

Give 1-2 glasses of milk or water to conscious person. Get immediate medical attention. **DO NOT INDUCE VOMITING.**

Flashpoint and Method: 51F (TCC)

Autoignition Temperature: NA

Flammable Limits: 2.1 MMA, Upper 12.5 for MMA

EXTINGUISHING MEDIA: Flammable liquid, insoluble in water. Use DRY chemical powder

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

HAZARDOUS COMBUSTION PRODUCTS:

Oxides of carbon and nitrogen. Hydrogen cyanide. Methylene bisphenyl isocyanate. Hydrocarbons. Smoke. Cyclopentanone. Butanediol. Tetrahydrofuran.

SECTION 6. - ACCIDENTAL RELEASE MEASURES

Remove sources of ignition. Use with ventilation. Dike area to prevent spreading. Absorb on vermiculite, sand or other inert absorbing material. Dispose of as chemical waste in accordance with current local, state, and federal regulations. Do not discharge into water. Incineration recommended. Wash spill area with strong detergent. After proper mixing of resin and activator sides, the material will polymerize into a cured solid state which can be treated as a nonhazardous solid. Applicable CERCLA/RCRA waste code:0001(ignitability) U162 (MMA)

HANDLING:

Avoid prolonged or repeated breathing of vapor. Avoid contact with skin and eyes. Wash hands before smoking or eating.

STORAGE:

Avoid storage over 100°F, contamination with incompatible materials. Store in cool place. Do not store in direct sunlight.

Recommended storage in flammable material containment area

SECTION 8. - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Use local exhaust ventilation if the potential for airborne exposure exists

PERSONAL PROTECTION:

RESPIRATORY PROTECTION:

Use NIOSH approved respirator if there is potential to exceed any exposure limit(s).

SKIN PROTECTION: Use chemical resistant, impermeable clothing including gloves and either an apron or

MATERIAL SAFETY DATA SHEET

8505

..... Date of Preparation: 10/01/03
body suit to prevent skin contact.

EYE PROTECTION: Chemical splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: NA

SECTION 9. - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: 29mm at 20C Vapor Density: >1 Heavier than air, 3.5 for MMA
Solubility in H2O: Slight Specific Gravity: 0.94-1.0
Boiling Point: 214F for MMA Freezing Point: NA
Physical State: Liquid pH: NA
Odor: Pungent. Acrylic Appearance: Light gel, milky white in color
VOC: 1.98%; 1.92 g/l (adhesive & activator mixed)

SECTION 10. -STABILITY AND REACTIVITY

STABILITY: Stable

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

No known conditions to avoid. Oxidizing agents, Alkalies, Moisture. Strong acids. Strong bases. Reducing agent.
Ultraviolet radiation. Amines

HAZARDOUS POLYMERIZATION:

May occur. Excessive aging. Excessive heat. Polymerization catalysts. Oxygen-free atmosphere. Inhibitor depletion. Direct sunlight.

HAZARDOUS DECOMPOSITION PRODUCTS: None known

SECTION 11. - TOXICOLOGICAL INFORMATION

PRODUCT TOXICOLOGY DATA: Not available

Ingredients	Carcinogen		
	NTP	IARC	OSHA
Methyl methacrylate	No	N/A	No
Cumene hydroperoxide	No	No	No
Methacrylic acid	No	No	No

Ingredients	Target Organ and other health effects
Methyl methacrylate	Allergen. Irritant. Nervous System. Respiratory. Kidney. Liver
Cumene hydroperoxide	Allergen Centralnervous sstem. Corrosive. Irritant. Mutagen
Methacrylic acid	Allergen. Corrosive. Irritant.

SECTION 12. - ECOLOGICAL INFORMATION Not available

SECTION 13. - DISPOSAL CONSIDERATIONS DISPOSAL METHOD

MATERIAL SAFETY DATA SHEET

8505

..... Date of Preparation: 10/01/03
Dispose according to EPA and local governmental regulations. EPA Hazardous waste # 0001;UI62;DO03

SECTION 14. - TRANSPORT INFORMATION DOT (49 CFR 172)

PROPER SHIPPING NAME: Adhesives

IDENTIFICATION NUMBER: Un1133 HAZARD CLASS: 3 PACKING GROUP II

EXCEPTIONS: Single unit less than or equal to 1 liter PROPER SHIPPING NAME: Consumer Commodity

CLASS / DIVISION:ORM-D

INTERNATIONAL AIR TRANSPORTATION (IATA) PROPER SHIPPING NAME:Adhesives

IDENTIFICATION NUMBER: UN1133 PACKING GROUP: II CLASS/DIVISION: 3

EXCEPTIONS: Consumer Commodity, Class 9, ID 8000, less than 500ml.

SECTION 15. - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act):

All components are listed on or exempt from listing on the Toxic Substances Control Act Inventory,

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act): NA

SARA TITLE III (Superfund Amendments and Reauthorization Act):

313 Reportable Ingredients: Methyl Methacrylate

CANADIAN INVENTORY STATUS:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List

CALIFORNIA PROPOSITION 65:

This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm

SECTION 16. - OTHER INFORMATION

NFPA

Health 2 Fire 3 Reactivity 2 Special None

Hazardous Materials Information System (HMIS) Ratings:

Health 2 Flammability 3 Reactivity 2 Protective Equipment: see section 8

REVISION SUMMARY: Change to 16-section format.

PREPARED BY: Steve Busch

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Supplier's knowledge, or is obtained from sources believed by the Supplier to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Supplier assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the Supplier assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.