

2301-2335
Fast Hardener

U-POLTM

SAFETY DATA SHEET

UP2301, UP2302, UP2303, UP2304, UP2305, UP2306 2K SYSTEM 20 FAST HARDENER

Page 1

Issued: 03/01/2005

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UP2301, UP2302, UP2303, UP2304, UP2305, UP2306 2K SYSTEM 20 FAST HARDENER

Product code: S2030

Use / description of product: FAST HARDENER

Company name:

Wesmar Products, Inc.
1440 NW 45th St
Seattle, Wa 98107
(206) 782-8186

Emergency tel: 1-800-424-9300 (CHEMTREC)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ALIPHATIC POLYISOCYANATE 30-50%

CAS: 28182-81-2

[Sens.] R43

- TOLUENE 50-70%

EINECS: 203-625-9 CAS: 108-88-3

[F] R11; [Xn] R20

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation. May cause sensitisation by inhalation and skin contact.

Other hazards: Harmful in contact with skin. May cause sensitisation by skin contact.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

[cont...]

- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.
- Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Highly flammable.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

- Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** TOLUENE
TWA (8 hr exposure limit): 191 mg/m³ STEL (15 min exposure limit): 574 mg/m³ (OES)
- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Compressed airline breathing apparatus (EN139).
- Hand protection:** Nitrile gloves.
- Eye protection:** Face-shield.
- Skin protection:** Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Liquid
- Colour:** Colourless
- Odour:** Aromatic
- Evaporation rate:** Moderate
- Solubility in water:** Insoluble
- Also soluble in:** Most organic solvents.
- Viscosity:** Non-viscous
- Viscosity value:** 100 cps
- Flammability limits %:** lower: 1.20
upper: 7.0

Flash point°C: 4
Autoflammability°C: 535
Relative density: 1.0
VOC g/l: 595

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat. Sources of ignition. Flames.
Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: TOLUENE
IVN RAT LD50 1960 mg/kg
ORL MUS LD50 2 gm/kg
ORL RAT LD50 6900 mg/kg
Chronic toxicity: May cause sensitisation by skin contact.
Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.
Persistence and degradability: Not biodegradable.
Bioaccumulative potential: No data available.
Other adverse effects: Very toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D10 Incineration on land.
R1 Solvent reclamation/regeneration.
Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no:	1263	ADR Class:	3
Packing group:	II	Classification code:	F1
Shipping name:	PAINT RELATED MATERIAL		
Labelling:	3	Hazard ID no:	33

IMDG / IMO

UN no:	1263	Class:	3
Packing group:	II	EmS:	F-E,S-E
Marine pollutant:	.	Labelling:	3


IATA / ICAO

UN no:	1263	Class:	3
Packing group:	II	Packing instructions:	305(P&CA); 307(CAO)
Labelling:	3		

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Harmful.



Risk phrases: R11: Highly flammable.
R20: Harmful by inhalation.
R42/43: May cause sensitisation by inhalation and skin contact.

Safety phrases: S23 Do not breathe vapour/spray
S24: Avoid contact with skin.
S42: During fumigation / spraying wear suitable respiratory equipment.
S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

VbF: All

Water hazard class: 1

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Risk phrases used in s.2: R43: May cause sensitisation by skin contact.
R11: Highly flammable.
R20: Harmful by inhalation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above

Issued: 03/01/2005

SAFETY DATA SHEET

UP2301, UP2302, UP2303, UP2304, UP2305, UP2306 2K SYSTEM 20 FAST HARDENER

Page 5

U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.