

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name X-6+ Xzilon Exterior Sealant
Version # 02
Revision date 07-14-2010
CAS # Mixture
Product use Sealant.
Manufacturer/Supplier Xzilon, Inc.
11022 Vulcan Street
South Gate, CA 90280-0893 US
Telephone: (562) 923-5438
Emergency CHEMTREC: (800) 424-9300
CHEMTREC International: 00 1-703-527-3887

2. Hazards Identification

Physical state Liquid.
Appearance Colorless liquid.
Emergency overview **WARNING!**
Flammable liquid and vapor. Will be easily ignited by heat, spark or flames.

Harmful if inhaled. Irritating to eyes, respiratory system and skin. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness. Prolonged exposure may cause chronic effects.
OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects
Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.
Eyes Irritating to eyes. Contact may irritate or burn eyes.
Skin Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Inhalation Harmful if inhaled. Irritating to respiratory system. Prolonged inhalation may be harmful.
Ingestion Harmful: may cause lung damage if swallowed. Irritating. May cause nausea, stomach pain and vomiting.
Target organs Eyes. Skin. Respiratory system. Central nervous system. Kidneys. Liver. Lungs.
Chronic effects Contains a substance that is classified as an IARC 2B - possibly carcinogenic to humans. May cause damage to the liver and kidneys. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Potential environmental effects Components of this product are hazardous to aquatic life. Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Stoddard solvent	8052-41-3	85 - 90
1,2,4-Trimethylbenzene	95-63-6	3 - 7
Solvent naphtha (petroleum), light aromatic	64742-95-6	3 - 7
1,3,5-Trimethylbenzene	108-67-8	0.5 - 1.5
Siloxanes and silicones, di-Me, ((methylamino)silyl)oxy-terminated	No Data	0.5 - 1.5
Cumene	98-82-8	0.1 - 0.6
Diethylbenzene	25340-17-4	0.1 - 0.6
Xylene	1330-20-7	0.1 - 0.6

Composition comments Components not listed are either non-hazardous or are below reportable limits. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Get medical attention, if needed.

Ingestion Rinse mouth thoroughly. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention immediately.

Notes to physician In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General advice Take off contaminated clothing and shoes immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

5. Fire Fighting Measures

Flammable properties Flammable liquid and vapor. Can be ignited easily and burns vigorously. Heat may cause the containers to explode.

Extinguishing media

Suitable extinguishing media Water. Water spray. Foam. Dry powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from the chemical Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Vapors may be ignited by a spark, a hot surface or an ember.

Protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Containers should be cooled with water to prevent vapor pressure build up. Cool containers exposed to flames with water until well after the fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage.

Special protective equipment for fire-fighters Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Specific methods In the event of fire and/or explosion do not breathe fumes.

Hazardous combustion products Carbon monoxide. Carbon Dioxide. Silicon oxides. Nitrogen Oxides.

6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the MSDS for Personal Protective Equipment.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for containment ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Collect spillage. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Small Spills: Absorb spill with vermiculite or other inert material. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. Should not be released into the environment.

Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Do not allow material to contaminate ground water system.

Other information

Clean up in accordance with all applicable regulations.

7. Handling and Storage**Handling**

Wear personal protective equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. Use only with adequate ventilation. Wash thoroughly after handling. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. When using, do not eat, drink or smoke. Avoid release to the environment. Do not empty into drains.

Storage

Store in cool place. Store in a well-ventilated place. Keep container tightly closed. Keep away from food, drink and animal feedings. Keep out of the reach of children.

8. Exposure Controls / Personal Protection**Occupational exposure limits****ACGIH**

Components	Type	Value
1,2,4-Trimethylbenzene (95-63-6)	TWA	25 ppm
1,3,5-Trimethylbenzene (108-67-8)	TWA	25 ppm
Cumene (98-82-8)	TWA	50 ppm
Ethylbenzene (100-41-4)	STEL	125 ppm
	TWA	100 ppm
Stoddard solvent (8052-41-3)	TWA	100 ppm
Xylene (1330-20-7)	STEL	150 ppm
	TWA	100 ppm

U.S. - OSHA

Components	Type	Value
Cumene (98-82-8)	PEL	50 ppm
		245 mg/m3
Ethylbenzene (100-41-4)	PEL	435 mg/m3
		100 ppm
Stoddard solvent (8052-41-3)	PEL	500 ppm
		2900 mg/m3
Xylene (1330-20-7)	PEL	100 ppm
		435 mg/m3

Canada - Alberta

Components	Type	Value
1,2,4-Trimethylbenzene (95-63-6)	TWA	25 ppm
		123 mg/m3
1,3,5-Trimethylbenzene (108-67-8)	TWA	25 ppm
		123 mg/m3
Cumene (98-82-8)	TWA	246 mg/m3
		50 ppm
Ethylbenzene (100-41-4)	STEL	125 ppm
		543 mg/m3
	TWA	100 ppm
		434 mg/m3
Stoddard solvent (8052-41-3)	TWA	100 ppm
		572 mg/m3

Canada - British Columbia

Components	Type	Value
1,2,4-Trimethylbenzene (95-63-6)	TWA	25 ppm
1,3,5-Trimethylbenzene (108-67-8)	TWA	25 ppm
Cumene (98-82-8)	STEL	75 ppm
	TWA	25 ppm

Components	Type	Value
Ethylbenzene (100-41-4)	STEL	125 ppm
	TWA	100 ppm
Stoddard solvent (8052-41-3)	STEL	580 mg/m3
	TWA	290 mg/m3
Xylene (1330-20-7)	STEL	150 ppm
	TWA	100 ppm
Canada - Ontario		
Components	Type	Value
1,2,4-Trimethylbenzene (95-63-6)	TWA	123 mg/m3
		25 ppm
1,3,5-Trimethylbenzene (108-67-8)	TWA	25 ppm
		123 mg/m3
Cumene (98-82-8)	TWA	245 mg/m3
		50 ppm
Ethylbenzene (100-41-4)	STEL	540 mg/m3
		125 ppm
	TWA	100 ppm
		435 mg/m3
Stoddard solvent (8052-41-3)	TWA	525 mg/m3
Xylene (1330-20-7)	STEL	150 ppm
		650 mg/m3
	TWA	100 ppm
		435 mg/m3
Canada - Quebec		
Components	Type	Value
1,2,4-Trimethylbenzene (95-63-6)	TWA	25 ppm
		123 mg/m3
1,3,5-Trimethylbenzene (108-67-8)	TWA	25 ppm
		123 mg/m3
Cumene (98-82-8)	TWA	246 mg/m3
		50 ppm
Ethylbenzene (100-41-4)	STEL	125 ppm
		543 mg/m3
	TWA	434 mg/m3
		100 ppm
Stoddard solvent (8052-41-3)	TWA	100 ppm
		525 mg/m3
Xylene (1330-20-7)	STEL	150 ppm
		651 mg/m3
	TWA	100 ppm
		434 mg/m3
Mexico		
Components	Type	Value
1,2,4-Trimethylbenzene (95-63-6)	STEL	170 mg/m3
		35 ppm
	TWA	125 mg/m3
		25 ppm
1,3,5-Trimethylbenzene (108-67-8)	STEL	170 mg/m3
		35 ppm
	TWA	25 ppm
		125 mg/m3
Cumene (98-82-8)	STEL	75 ppm
		365 mg/m3
	TWA	245 mg/m3
		50 ppm
Ethylbenzene (100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	100 ppm
		435 mg/m3
Stoddard solvent (8052-41-3)	STEL	1050 mg/m3
		200 ppm

Components	Type	Value
Xylene (1330-20-7)	TWA	523 mg/m3
		100 ppm
	STEL	150 ppm
		655 mg/m3
	TWA	100 ppm
		435 mg/m3
Engineering controls	Use explosion-proof equipment. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.	
Personal protective equipment		
Eye / face protection	Wear approved safety glasses or goggles. Wear face shield if there is risk of splashes.	
Skin protection	Wear suitable protective clothing and gloves.	
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.	
General hygiene considerations	Provide eyewash station and safety shower. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.	

9. Physical & Chemical Properties

Appearance	Colorless liquid.
Color	Colorless.
Odor	Solvent odor.
Odor threshold	Not available.
Physical state	Liquid.
Form	Not available.
pH	Not available.
Melting point	Not available.
Freezing point	Not available.
Boiling point	315 - 390 °F (157.2 - 198.9 °C)
Flash point	100.4 - 140 °F (38 - 60 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	Not available.
Vapor density	4.9
Specific gravity	0.78
Solubility (water)	Slight.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
VOC	774 g/l

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions. Risk of ignition.
Conditions to avoid	Heat, flames and sparks. Electrostatic discharge.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong bases.
Hazardous decomposition products	Carbon monoxide. Carbon Dioxide. Silicon oxides. Nitrogen Oxides.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Components	Test Results
Ethylbenzene (100-41-4)	Acute Dermal LD50 Rabbit: > 5000 mg/kg Acute Oral LD50 Rat: 3500 mg/kg
1,3,5-Trimethylbenzene (108-67-8)	Acute Oral LD50 Rat: 8970 mg/kg
Xylene (1330-20-7)	Acute Oral LD50 Rat: 4300 mg/kg Acute Other LD50 Rat: 3.8 mg/kg
Diethylbenzene (25340-17-4)	Acute Dermal LD50 Rat: > 2000 mg/kg Acute Oral LD50 Rat: 2050 mg/kg
1,2,4-Trimethylbenzene (95-63-6)	Acute Dermal LD50 Rabbit: > 3160 mg/kg Acute Inhalation LC50 Rat: 18000 mg/m3 4 hours
Cumene (98-82-8)	Acute Oral LD50 Rat: 2910 mg/kg
Acute effects	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, it may cause pulmonary hemorrhage, edema and possible death.
Local effects	Irritating to eyes, respiratory system and skin. Vapors may cause drowsiness and dizziness.
Sensitization	Risk of sensitization or allergic reactions among sensitive individuals.
Chronic effects	Prolonged inhalation may be harmful. Prolonged or repeated exposure may cause lung injury. Prolonged or repeated exposure may cause liver, kidney, and central nervous system damage.
Carcinogenicity	Contains ethylbenzene, which is classified as an IARC 2B chemical (Possibly Carcinogenic to Humans).
ACGIH Carcinogens	
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
Mutagenicity	Not available.
Neurological effects	Central and/or peripheral nervous system damage. May cause drowsiness or dizziness.
Reproductive effects	Not available.
Teratogenicity	Not available.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Components	Test Results
Ethylbenzene (100-41-4)	EC50 Water flea (Daphnia magna): 1.37 - 4.4 mg/l 48 hours LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss): 4.2 mg/l 96 hours
1,3,5-Trimethylbenzene (108-67-8)	LC50 Goldfish (Carassius auratus): 9.89 - 15.05 mg/l 96 hours
1,2,4-Trimethylbenzene (95-63-6)	LC50 Fathead minnow (Pimephales promelas): 7.19 - 8.28 mg/l 96 hours
Cumene (98-82-8)	EC50 Brine shrimp (Artemia sp.): 3.55 - 11.29 mg/l 48 hours LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss): 2.7 mg/l 96 hours
Ecotoxicity	Contains a substance which causes risk of hazardous effects to the environment.
Environmental effects	The product may cause risk of hazardous effects to the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Aquatic toxicity	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
Persistence and degradability	Not available.
Bioaccumulation / Accumulation	No data available.

Partition coefficient (n-octanol/water)	Not available.
Mobility in environmental media	No data available.

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 °F
Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1268
Proper shipping name	Petroleum distillates, n.o.s. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	Combustible Liquid
Packing group	III
Labels required	Combustible Liquid

Additional information:

Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
ERG number	128

IATA

Basic shipping requirements:

UN number	1268
Proper shipping name	Petroleum distillates, n.o.s. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	3
Packing group	III

IMDG

Basic shipping requirements:

UN number	1268
Proper shipping name	PETROLEUM DISTILLATES, N.O.S. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	3
Packing group	III
EmS No.	F-E, S-E

TDG

Basic shipping requirements:

Proper shipping name	PETROLEUM DISTILLATES, N.O.S. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	3
UN number	UN1268
Packing group	III
Marine pollutant	.



DOT



IATA



IMDG

Partition coefficient (n-octanol/water)	Not available.
Mobility in environmental media	No data available.

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 °F
Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1268
Proper shipping name	Petroleum distillates, n.o.s. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	Combustible Liquid
Packing group	III
Labels required	Combustible Liquid

Additional information:

Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
ERG number	128

IATA

Basic shipping requirements:

UN number	1268
Proper shipping name	Petroleum distillates, n.o.s. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	3
Packing group	III

IMDG

Basic shipping requirements:

UN number	1268
Proper shipping name	PETROLEUM DISTILLATES, N.O.S. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	3
Packing group	III
EmS No.	F-E, S-E

TDG

Basic shipping requirements:

Proper shipping name	PETROLEUM DISTILLATES, N.O.S. (Stoddard solvent, Solvent naphtha (petroleum), light aromatic)
Hazard class	3
UN number	UN1268
Packing group	III
Marine pollutant	.



DOT



IATA



IMDG



TDG

15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

1,2,4-Trimethylbenzene (CAS 95-63-6)	1.0 %
Cumene (CAS 98-82-8)	1.0 %
Ethylbenzene (CAS 100-41-4)	0.1 %
Xylene (CAS 1330-20-7)	1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

1,2,4-Trimethylbenzene (CAS 95-63-6)	Listed.
Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

CERCLA (Superfund) reportable quantity (lbs)

Cumene 5000
Xylene 1000
Ethylbenzene 1000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance
No

Section 311 hazardous chemical
Yes

Clean Air Act (CAA)
HAPS list

Clean Water Act (CWA)
Hazardous substance

Drug Enforcement Agency (DEA)
Not controlled

Canadian regulations
This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status
Controlled

WHMIS classification
B3 - Flammable/Combustible
D2B - Other Toxic Effects-TOXIC

WHMIS labeling



Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

1,2,4-Trimethylbenzene (CAS 95-63-6)	Listed.
1,3,5-Trimethylbenzene (CAS 108-67-8)	Listed.
Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Ethylbenzene (CAS 100-41-4)	Listed.
Toluene (CAS 108-88-3)	Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004 Carcinogenic.
-----------------------------	-------------------------------------

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)	Listed: January 1, 1991 Developmental toxin.
------------------------	--

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)	Listed: August 7, 2009 Female reproductive toxin.
------------------------	---

US - Massachusetts RTK - Substance: Listed substance

1,2,4-Trimethylbenzene (CAS 95-63-6)	Listed.
1,3,5-Trimethylbenzene (CAS 108-67-8)	Listed.
Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

1,2,4-Trimethylbenzene (CAS 95-63-6)	500 LBS
Cumene (CAS 98-82-8)	500 LBS
Ethylbenzene (CAS 100-41-4)	500 LBS
Xylene (CAS 1330-20-7)	500 LBS

US - New Jersey RTK - Substances: Listed substance

1,2,4-Trimethylbenzene (CAS 95-63-6)	Listed.
1,3,5-Trimethylbenzene (CAS 108-67-8)	Listed.
Cumene (CAS 98-82-8)	Listed.
Diethylbenzene (CAS 25340-17-4)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

1,2,4-Trimethylbenzene (CAS 95-63-6)	Listed.
1,3,5-Trimethylbenzene (CAS 108-67-8)	Listed.
Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

16. Other Information

Recommended use Solvent.

Further information

HMIS® ratings

HMIS® is a registered trade and service mark of the NPCA.

Health: 2*

Flammability: 2

Physical hazard: 0

NFPA ratings

Health: 2

Flammability: 2

Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.

Issue date

07-14-2010