


WHMIS Code

B

Flammable

Material Safety Data Sheet

ResistAll Fabric Sealant



Section 1 - Material Identification and Use

Manufacturer's Name..... **Cal-Tex Protective Coatings, Incorporated**
 Manufacturer's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 Emergency Phone Number..... INFOTRAC 1-800-535-5053 24 Hours Per Day, 7 Days Per Week
 Supplier Name and Identifier..... **Cal-Tex Protective Coatings, Incorporated**
 Supplier's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 MSDS Prepared By Ronnie Meadows (210) 564-3200
 Trade Name..... **ResistAll Fabric Sealant**
 Product Use..... Vehicle interior stain protection.

Section 2 - Hazardous Ingredients of Material

No.	Chemical Identity	Concentration	CAS	PEL	TLV	STEL	IDLH
1	Odorless Mineral Spirits	Trade Secret	64742-48-9	500	100		

NA = Not Applicable ND = No Data Available < = Less Than > = More Than * Ceiling Value ** Chemical Believed to be a Potential Carcinogen (NIOSH)

Section 3 - Hazardous Identification

EYE	☒	This chemical may affect the eye or visual capacity
SKIN	☒	This chemical may affect the dermal layer of the body
LUNGS	☒	This chemical may irritate or damage pulmonary tissue
NERVOUS SYSTEM	☐	This chemical may produce a toxic affect on the nervous system
REPRODUCTIVE	☐	May affect reproductive capabilities including mutations and effects on the fetus.
BLOOD	☐	This chemical may act on the blood or hematopoietic system; decrease hemoglobin function; deprive tissue of oxygen
LIVER	☐	This chemical may produce liver damage - Hepatotoxins
KIDNEYS	☐	This chemical may produce kidney damage - Nephrotoxins

WHMIS Warning:



Flammable


Section 4 - First Aid Measures

INGESTION	☒	DO NOT induce vomiting. Rinse mouth with water and give plenty of milk. Never give liquids to an unconscious victim - Seek Immediate Medical Attention
EYE CONTACT	☒	Flush immediately with plenty of water for at least 15 minutes - Seek Medical Attention
SKIN CONTACT	☒	Wash thoroughly with soap and water - Seek Medical Attention if irritation persists
INHALATION	☒	Remove to fresh air. If breathing is difficult give oxygen - If not breathing give artificial respiration -Get Medical Attention
SPECIAL	☐	None Identified

WHMIS Code

B
Flammable

Material Safety Data Sheet ResistAll Fabric Sealant



Section 5 - Fire-Fighting Measures

Flashpoint F 142
Flashpoint C 61.05

Upper Explosion Limit Not Determined
Lower Explosion Limit Not Determined
Auto-Ignition Temp. Not Determined

Extinguishing Media

Carbon dioxide, dry chemical, water fog, water spray, foam.

☒ DO NOT USE WATER

Special Fire Fighting Procedures Use self contained breathing apparatus when fighting large fires.

Section 6 - Accidental Release Measures

Spill and Leak Requirements

Small leaks-mop up, wipe up, or soak up immediately. Large spills-contain material and ventilate area. Do not dump into sewers, on the ground, or into any body of water.

Section 7 - Handling and Special Storage

Handling and Special Storage

Keep from sources of ignition. Keep containers closed when not in use. Store in a cool place with adequate ventilation. Storage location should be constructed for containment and dilution/neutralization of spills

Additional Storage Requirements

Section 8 - Exposure Controls and Personal Protection

Eye Protection

Wear approved eye protection to safeguard against potential eye contact, irritation or injury. Use chemical goggles if material is to be sprayed.

Skin Protection

Wear chemical resistant gloves, suits, aprons, and boots to safeguard against potential skin contact, irritation or injury.

Comments

None needed with proper engineering controls. Use when concentrations exceed the PEL/TLV. Maintain ventilation to keep vapor concentration below the PEL/TLV.

Section 9 - Physical and Chemical Properties

Physical State

Liquid

Odor and Appearance

Slight sweet smell, clear water white liquid

Specific Gravity

<1

Vapour Pressure

Not Determined

Vapour Density

Not Determined

Evaporation Rate

Not Determined

Boiling Point

Not Determined

Freezing Point

N/A

pH

Not Determined

Density (g/ml)

Not Determined

Section 10 - Stability and Reactivity

Stability

☒ Material is Stable ☐ Material is NOT Stable

Incompatibility

Strong Oxidizing Material

Hazardous Decomposition Products

Thermal decomposition may yield carbon monoxide and/or carbon dioxide

Hazardous Polymerization


☐ May Occur ☒ Will NOT Occur

WHMIS Code

B
Flammable

Material Safety Data Sheet

ResistAll Fabric Sealant



Section 11 - Toxicological Information

Acute Over Exposure Effects	Skin contact may cause redness or slight dermatitis. Eye contact may cause discomfort. Ingestion may cause chemical pneumonia. Aspiration
Chronic Over Exposure Effects	Not Determined
Eye Contact	Slight irritating but does not injure eye tissue.
Skin Contact	Frequent or prolonged contact may irritate and cause dermatitis. Low order of toxicity. Skin contact may aggravate an existing dermatitis condition.
If Inhaled	High vapor/aerosol concentrations are irritating to the eyes and the respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.
If Swallowed	Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. Minimal toxicity.

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Dispose in accordance with local, state, and federal regulations.

Section 14 - Transportation Information

Ship as per DOT requirements in 49 CFR. Ship in accordance with local, state, and federal regulations.

Section 15 - Regulatory Information

No.	Chemical Identity	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
1	Odorless Mineral Spirits																				X		

(1) EHS-RQ (2) CERCLA (3) RQ (4) CAA 122r (5) TPO (6) FIFRA (7) RCRA Code (8) Cal-CARC (9) Priority Pollutant (10) Cal-Well Monitoring (11) SARA 313 (12) SARA 302 (13) MCL (14) Cal-HOT SPOT (15) Cal-Drinking Water (16) Cal-Toxic Air (17) NESHAP (18) Cal-Prop 65 (19) DOT Inhalation (20) Director's List (21) EPA Air (22) Cal-Reg Pest.

An "X" in Column 11 indicates that this product contains a toxic chemical subject to the reporting requirements of Section 313 of EPCRA (40 CFR 372)

MSDS No.	72	Date Reviewed	2/5/2004	Prepared By	Ronnie Meadows
Trade Name	ResistAll Fabric Sealant	Supersedes	4/15/2000	Phone Number	(210) 564-3200

TLV - Threshold Limit Value. An estimate of the average safe airborne concentration of a substance in representative conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. TLVs are published annually by the ACGIH (American Conference of Governmental Industrial Hygienists).

PEL - Permissible Exposure Limit. The OSHA limit of employee exposure to chemicals; found primarily in 29 CFR 1910.1000.

STEL - Short Term Exposure Limit. The maximum concentration for a continuous 15-minute exposure period.

IDLH - Immediately Dangerous to Life and Health. The concentration of a airborne chemical which may cause irreversible health effects or death.

Ceiling - The maximum allowable concentration to which an employee may be exposed.

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using this product, read label. The information contained in this publication is intended for general information purposes only. This publication is not a substitute for review of the applicable government regulations and standards, and should not be construed as legal advice or opinion. Readers with specific questions should refer to the cited references.