



SAFETY DATA SHEET

Issue Date 06-22-2018

Revision Date 06-22-2018

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name: PERFECTION™

Other means of identification

Common Name: 2180
UN/ID No NA1993 (domestic)
Synonyms None
Product Categories Automotive Wax

Recommended use of the chemical and restrictions on use

Sale and Use Restrictions Not applicable
Recommended Use Restricted to professional users.
Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier Address
MOC PRODUCTS CO., INC.
12306 Montague Street
Pacoima, CA 91331

Emergency telephone number

Company Phone Number MOC PRODUCTS CO., INC. (818) 794-3500
Emergency Telephone CHEMTREC 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Germ cell mutagenicity	Sub-category 1B
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

Harmful if inhaled
 May cause genetic defects
 Suspected of causing cancer
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Flammable liquid and vapor



Appearance Viscous

Physical state Cream/ Lotion

Odor Cola

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment (if metal)
 Use explosion-proof electrical/ventilating/lighting equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CONTROL CENTER or doctor/physician

Do not induce vomiting

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

• Toxic to aquatic life with long lasting effects

1.11 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %	Trade Secret
Hydrotreated Light Petroleum Distillates	64742-47-8	15-40	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	0-15	*
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0-15	*
Anhydrous Aluminum Silicate	92704-41-1	4-8	*
Montan Wax, mono and diester of ethylene glycol	73138-45-1	1-5	*
Oleamide DEA	93-83-4	1-5	*
Alkyl Quaternary Ammonium Montmorillinite	68911-87-5	1-2	*
Alkyl Quaternary Ammonium Bentonite	68953-58-2	1-2	*
Titanium dioxide	13463-67-7	0.1-0.5	*
Diethanolamine	111-42-2	0.1-0.5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice	If exposed or concerned: Get medical advice/attention.
Skin contact	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Rinse immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before reuse.
Inhalation	Remove to fresh air. Keep at rest position comfortable for breathing.
Eye contact	Flush immediately with large amount of water for at least 15 minutes. Consult a physician.
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.
Notes to Physician	Aspiration hazard if swallowed - can enter lungs and cause damage. Causes central nervous system depression. Dermatitis may result from prolonged or repeated exposure.

Most important symptoms and effects, both acute and delayed

Symptoms	Drowsiness, Dizziness, Headache, Hearing loss, Nausea, Vomiting, Coughing and/ or wheezing; Weakness, Unconsciousness, Skin irritation, Eye irritation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Self-protection of the first aider	Avoid breathing vapors or mists. Avoid contact with skin.
---	---

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Use dry chemical, CO₂, water spray (fog) or alcohol resistant foam.

Small Fire	Dry chemical or CO ₂ .
Large Fire	Water spray or fog; Alcohol resistant foam.
Explosive properties:	Risk of explosion if heated under confinement. Fire or intense heat may cause violent rupture of packages.

Specific hazards arising from the chemical

FLAMMABLE LIQUID AND VAPOR. Keep product and empty container away from heat and sources of ignition. May be ignited by heat, sparks or flames. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Hazardous combustion products Carbon monoxide, Carbon dioxide (CO₂), Hydrocarbons, Aldehydes, Silicon dioxide, Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

Specific methods:

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes. May be ignited by heat, sparks or flames.

Special firefighting procedures:

Flammable liquid and vapor. No action shall be taken involving any personal risk without suitable training. Evacuate surrounding areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not use a solid water stream as it may scatter and spread fire. Water mist may be used to cool closed containers. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Dike to collect large liquid spills.

Do not allow run-off from fire-fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Personal precautions:** Use personal protective equipment. See Section 8 for information on appropriate personal protective equipment. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Ensure adequate ventilation. Pay attention to flashback. Avoid dust formation.
- For emergency responders** Use personal protection recommended in Section 8. Remove all sources of ignition. Ventilate the area. Pay attention to flashback. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

Environmental precautions

- Environmental precautions:** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Methods and material for containment and cleaning up

- Methods for Containment** Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to state, local, federal regulations.
- Methods for clean-up:** Clean-up methods - small spillage: Soak up with inert absorbent material. Shovel into suitable container for disposal. Clean-up methods - large spillage: Large spills present a vapor explosion and liquid fire hazard; evacuate area and ensure response by personnel trained and equipped to respond to flammable material incident or off-site emergency responders or fire department.
- Prevention of secondary hazards** Avoid dust formation. Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

- Handling:** Avoid breathing (dust, vapor, mist, gas). Do not get in eyes, on skin, or on clothing. Do not store at temperatures above 120°F (50°C). Protect from physical damage. Protect from freezing (<0°C, or 32°F). Keep product and empty container away from heat and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Store in a cool, well ventilated area. Empty containers retain product residue and can be hazardous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose these containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death.

Conditions for safe storage, including any incompatibilities

- Technical measures/precautions:** Mechanical ventilation required if used indoors on a continuous basis. Eye wash and safety shower should be easily accessible.
- Materials to avoid:** Chlorine, Strong oxidizing agents, Strong acids, Alkalies.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA Exposure Limits:	NIOSH IDLH
Hydrotreated Light Petroleum Distillates 64742-47-8	TWA: 200 ppm	TWA: 500 ppm	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	-	Z1 PEL: 500 ppm TWA: 2900 mg/m ³ Z1A TWA: 100 ppm TWA: 525 mg/m ³ (as Stoddard Solvent)	-
Naphtha (petroleum), hydrotreated heavy 64742-48-9	-	Not established	-
Anhydrous Aluminum Silicate 92704-41-1	-	Not established	-
Montan Wax, mono and diester of ethylene glycol 73138-45-1	-	Not established	-
Oleamide DEA 93-83-4	-	Not established	-
Alkyl Quaternary Ammonium Montmorillonite 68911-87-5	-	Not established	-
Alkyl Quaternary Ammonium Bentonite 68953-58-2	-	Not established	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Diethanolamine 111-42-2	S* TWA: 1 mg/m ³ inhalable fraction and vapor	TWA: 3 ppm TWA: 15 mg/m ³	TWA: 3 ppm TWA: 15 mg/m ³

Appropriate engineering controls

Engineering measures: Mechanical ventilation required if used indoors on a continuous basis. Eye wash and safety shower should be easily accessible.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear normal work clothing, Chemical resistant gloves (consult with the specific manufacturer to confirm performance).

Respiratory protection Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Use personal protective equipment. Avoid breathing (dust, vapor, mist, gas). Wash face, hands and any exposed skin thoroughly after handling. Take off contaminated clothing and wash it before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Cream/ Lotion	Odor	Cola
Appearance	Viscous	Odor threshold	No information available
Color	Blue		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	Not applicable
Melting point/freezing point	No information available	
Boiling point / boiling range	> 65 °C / 149 °F	(based on components)
Flash point	59 °C / 138 °F	Pensky-Martens Closed Cup (PMCC)
Evaporation rate		
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
Upper flammability limit	No Data Available	
Lower flammability limit	No Data Available	
Vapor pressure	No Data Available	
Vapor density	Heavier than air	
Specific Gravity	0.97	@25°C
Water solubility	No Data Available	
Solubility in other solvents	No Data Available	
Partition coefficient	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Kinematic viscosity	No information available	
Dynamic viscosity	20,000-25,000 cPs	@ 25 °C
Explosive properties	No Data Available	
Oxidizing properties	No Data Available	

Other information

Softening point	No Data Available
Molecular weight	No Data Available
VOC Content (%)	
VOC Content (%)	10.2
Density	0.97 g/cc
Bulk density	No Data Available

10. STABILITY AND REACTIVITY

Reactivity

Reactivity	Stable
------------	--------

Chemical stability

Possibility of Hazardous Reactions	May react with oxidizing agents.
Hazardous polymerization	Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Materials to avoid: Chlorine, Strong oxidizing agents, Strong acids, Alkalis.

Hazardous Decomposition Products

Hazardous Decomposition Products Carbon monoxide, Carbon dioxide (CO₂), Hydrocarbons, Aldehydes, Silicon dioxide,

Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Harmful if inhaled. May cause genetic defects. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
Inhalation	Harmful if inhaled. Avoid breathing vapors or mists. Do not breathe dust. Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Contact with eyes may cause irritation.
Skin Contact	May cause irritation.
Ingestion	May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrotreated Light Petroleum Distillates 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Naphtha (petroleum), hydrotreated heavy 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
Anhydrous Aluminum Silicate 92704-41-1	> 2000 mg/kg (Rat)	-	-
Montan Wax, mono and diester of ethylene glycol 73138-45-1	> 2000 mg/kg (Rat)	-	-
Oleamide DEA 93-83-4	=12.4 ml/kg (Rat)	-	-
Alkyl Quaternary Ammonium Montmorillonite 68911-87-5	-	-	-
Alkyl Quaternary Ammonium Bentonite 68953-58-2	> 5000 mg/kg (Rat)	-	> 12.6 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Diethanolamine 111-42-2	=710 mg/kg (Rat)	=12200 mg/kg (Rabbit)	-

Information on toxicological effects

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	Skin Sensitization: Not expected. Respiratory Sensitization: Not classified.
Mutagenic effects:	Is classified by the European Union as a mutagen of category 1B. Substances which should be regarded as being mutagenic to man.
Carcinogenicity	This product contains one or more substances which are classified by IARC as probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		
Diethanolamine 111-42-2		Group 2B		

Reproductive toxicity	No information available.
STOT - single exposure	Not classified.
STOT - repeated exposure	Category 1: Causes damage to organs through prolonged or repeated exposure.
Chronic toxicity	Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged exposure may cause central nervous system damage. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Suspected of causing cancer. May cause genetic defects.
Target Organ Effects	Liver, Kidney, Spleen, Respiratory system, Central nervous system, Heart.

Neurological effects

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system.

Other adverse effects

Caused kidney effects in male rats which are not considered relevant to humans. Auditory system: prolonged and repeated exposure to high concentrations have resulted in hearing losses in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss. Stomach irregularities.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information**Unknown Acute Toxicity**

1.11 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	7377 mg/kg
ATEmix (dermal)	5234 mg/kg
ATEmix (inhalation-vapor)	14 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chronic Aquatic Toxicity: Toxic to aquatic life with long lasting effects.

12.13 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hydrotreated Light Petroleum Distillates 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static		100: 48 h Daphnia magna mg/L EC50
Naphtha (petroleum), hydrotreated heavy 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50		
Anhydrous Aluminum Silicate 92704-41-1	100: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Oncorhynchus mykiss mg/L LC50 semi-static		1: 48 h Daphnia magna mg/L EC50
Montan Wax, mono and diester of ethylene glycol 73138-45-1		50 - 100: 96 h Brachydanio rerio mg/L LC50 static		
Diethanolamine 111-42-2	7.8: 72 h Desmodesmus subspicatus mg/L EC50 2.1 - 2.3: 96 h Pseudokirchneriella subcapitata mg/L EC50	4460 - 4980: 96 h Pimephales promelas mg/L LC50 flow-through 1200 - 1580: 96 h Pimephales promelas mg/L LC50 static 600 - 1000: 96 h Lepomis macrochirus mg/L LC50 static		55: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

Bioaccumulative potential.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

Disposal of wastes	Dispose of in accordance with federal, state and local regulations.
Contaminated packaging	Do not reuse container. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Limited quantity (LQ) < 5 Liters

DOT

UN/ID No	NA1993
Proper Shipping Name:	Combustible liquid, n.o.s. (Solvent Naphtha)
Hazard Class	Comb. Liq.
Packing Group:	III
Emergency Response Guide Number	128

IATA

UN/ID No	UN1993
Proper Shipping Name:	Flammable liquids, n.o.s. (Solvent Naphtha)
Hazard Class	3
Packing Group:	III

IMDG

UN/ID No	UN1993
Proper Shipping Name:	Flammable liquids, n.o.s. (Solvent Naphtha)
Hazard Class	3
Packing Group:	III

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

Federal Regulations

SARA 313

No SARA 313 chemicals are present above the reporting threshold:

Chemical Name	CAS Number	Weight %	SARA 313 - Threshold Values %
Diethanolamine 111-42-2	111-42-2	0.1-0.5	1.0 % de minimis concentration

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Diethanolamine 111-42-2	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

State Regulations (RTK)

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm:

Chemical Name	CAS Number	California Proposition 65
Titanium dioxide	13463-67-7	Carcinogen
Diethanolamine	111-42-2	Carcinogen
Methanol	67-56-1	Developmental
Silica, Quartz	14808-60-7	Carcinogen
Ethylbenzene	100-41-4	Carcinogen
Cumene	98-82-8	Carcinogen
1,3-Dichloropropene	542-75-6	Carcinogen
Toluene	108-88-3	Developmental
Methylene chloride	75-09-2	Carcinogen
Naphthalene	91-20-3	Carcinogen
Ethylene oxide	75-21-8	Carcinogen Developmental Female Reproductive Male Reproductive
1,4-Dioxane	123-91-1	Carcinogen
Formaldehyde	50-00-0	Carcinogen

U.S. State Right-to-Know RegulationsU.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATIONNFPA Rating

Health hazards 1

Flammability 2

Instability 0

Physical and Chemical Properties -

HMIS Rating

Health hazards 1*

Flammability 2

Physical hazards 0

Personal protection B

Chronic Hazard Star Legend

* = Chronic Health Hazard

Prepared by

Environmental Health and Safety Department

Issue Date

06-22-2018

Revision Date

06-22-2018

Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet