

MATERIAL SAFETY DATA SHEET

PermaPlate Windshield Treatment

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets before attempting to use the material. You must also provide this information to those people at your company whose responsibility it is to comply with Federal and State "Right to Know" regulations. Also make sure this information is made available and is disseminated to your employees before use of the product. This information should be kept on file and made available to any employee who requests it. It is your obligation to comply with the act.

SECTION 1 - IDENTIFICATION

Manufacturer's Name PermaPlate Company, LLC
 Address (Street, City, State, Zip) 2525 W. Bridger Road, Salt Lake City, UT 84104
 Company Phone Number (800) 453-8470
 Chemical Name (Synonym) Q-17 Glass Treatment
 Trade Name (Synonym) Glass Treatment

 Date November 30, 2007

SECTION II – HAZARDOUS INGREDIENTS

HEALTH		FLAMMABILITY		REACTIVITY	
1		2		0	
<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>PERCENT</u>	
Proprietary Blend of Aliphatics	64742-47-8	300 ppm	300 ppm	< 80	
Dimethyl(oxo)silane	94363-18-5	NONE	NONE	< 20	
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm	< 10	

SECTION III – PHYSICAL DATA (Typical)

Boiling Point 420– 485 Deg F
 Vapor Density 7.1
 Solubility in Water (Neg) .001
 Specific Gravity 0.77
 Percent Volatiles by Volume 62% in 400 min
 Appearance & Odor Clear liquid with slight petroleum odor.
 Vapor Pressure < .5 mm Hg @ 68 F

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash Point 155 Deg F, (Closed Cup)
Flammable Limits Lfl 1.3% Ufl 8.8%
Extinguishing Media Use Foam, dry chemical, carbon dioxide. Water may be ineffective.
Special Fire Fighting Procedures None
Unusual Fire Fighting Hazards Heating above 395 Deg F in a fire situation may cause toxic decomposition.
Explosion Data Material does not have explosive properties.

SECTION V FIRE FIGHTING MEASURES

Flash Point 155 Deg F, (Closed Cup)
Flammable Limits N.D.
Extinguishing Media Use Foam, dry chemical, carbon dioxide. Water may be ineffective.
Special Fire Fighting Procedures None
Unusual Fire Fighting Hazards Heating above 395 Deg F in a fire situation may cause toxic decomposition.
Explosion Data Material does not have explosive properties.

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Water should be used to keep fire-exposed containers cool. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SPECIAL PROTECTIVE EQUIPMENT: As with all fires where smoke is present, fire fighters should use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, water.

SECTION VI ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES: Report spills/releases as required to appropriate authorities. U.S. Coast Guard and EPA regulations require immediate reporting of spills/releases that could reach any waterway including intermittent dry creeks. Report spill/release to Coast Guard National Response Center toll free number **(800) 424-8802**.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: LAND SPILL: Stop source of leak taking normal safety precautions. Take measures to minimize the effects on ground water.

WATER SPILL: Confine with booms. Otherwise disperse in unconfined waters, if permitted by local authorities and environmental agencies. If permitted by regulatory authorities the use of suitable dispersants should be considered where recommended in local oil spill procedures.

ENVIRONMENTAL PRECAUTIONS: Prevent material from entering sewers.

PERSONAL PRECAUTIONS: See Section 8

SECTION VII HANDLING AND STORAGE

HANDLING: Use in well ventilated area. See Section 8 for additional personal protection advice when handling this product.

STORAGE: Store in containers of approved design and properly labeled. Keep out of reach of children. Protect against direct sunlight.

SPECIAL PRECAUTIONS: NONE

EMPTY CONTAINER WARNING: Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION VIII . EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Use in well ventilated area.

RESPIRATORY PROTECTION: Facemask is recommended for those who have sensitivities.

EYE PROTECTION: Protective glasses should be worn.

SKIN PROTECTION: Gloves should be worn. Good personal hygiene practices should always be followed.

SECTION IX PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Liquid

COLOR: Clear,Colorless

ODOR: Mild Hydrocarbon

ODOR THRESHOLD-ppm: NE

pH: NA

SECTION X STABILITY AND REACTIVITY

STABILITY (THERMAL, LIGHT, ETC.): Stable.

CONDITIONS TO AVOID: Direct sunlight.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Product does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI TOXICOLOGICAL DATA

ORAL TOXICITY (RATS): Not established

INHALATION TOXICITY (RATS): Not established

EYE IRRITATION (RABBITS): Not established

SKIN IRRITATION (RABBITS): Not established

CHRONIC TOXICOLOGY (SUMMARY)-Prolonged repeated skin contact may cause skin irritation and/or dermatitis.

SECTION XII ECOLOGICAL INFORMATION

ECOTOXICITY: Not established.

MOBILITY: Not established.

PERSISTENCE AND DEGRADABILITY: Not established.

BIOACCUMULATIVE POTENTIAL: Not established.

SECTION XIII DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Product is suitable for burning for fuel value in compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity. The unused product is not formulated with substances covered by the Toxicity Characteristic Leaching Procedure (TCLP).

SECTION XIV TRANSPORT INFORMATION

USA DOT SHIPPING NAME: Petroleum Oil
HAZARD CLASS & DIV: COMBUSTIBLE LIQUID
PACKING GROUP: PG III
DANGEROUS WHEN WET: No POISON: No
PLACARD(s): Combustible
PRODUCT RQ: NA

SUPPLEMENTAL STATE COMPLIANCE INFORMATION

California

Warning: this product contains the following chemical(s) listed by the State of California under *The Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)* as being known to cause cancer, birth defects or other reproductive harm.

None Known