

Material Safety Data Sheet

ALUMA KLEEN 1000

WESMAR CO. INC.5720 204TH ST SW
LYNNWOOD, WA. 98036
(206) 783-5344

DATE PREPARED: MAR 1, 2006

REVISED DATE: MAR 1, 2008

24 HOUR EMERGENCY PHONE NUMBER:

CHEMTREC: 800-424-9300

SECTION I - IDENTIFICATIONPRODUCT NAME: ALUMA KLEEN 1000
CHEMICAL FAMILY: HIGHLY ACIDIC MATERIAL
FORMULA: N/A
CAS NUMBER: N/A**SECTION II - HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW:**

EYES: Vapors, liquid and mists are extremely corrosive to the eyes. Brief contact of the liquids or mists will severely damage the eyes and may cause permanent eye injury which may be followed by permanent impairment of vision or blindness.

SKIN (DERMAL): Vapors, mists, and liquid are extremely corrosive to the skin. A short single exposure will severely burn the skin. Prolonged contact with liquid will burn or destroy surrounding tissue.

INGESTION: Vapors, mists and liquid are extremely corrosive to the mouth and throat. Swallowing the liquid burns the tissue and causes severe abdominal pain, nausea, vomiting, kidney damage and collapse. Swallowing large amounts can cause death.

INHALATION: Vapors, mists and liquid are extremely corrosive to the respiratory system. Irritation, coughing, chest pain and breathing difficulty may occur with short exposure. Prolonged exposure may result in more severe irritation and tissue damage.

MEDICAL CONDITION AGGRAVATED**BY EXPOSURE:** Existing skin and/or respiratory disorders may be aggravated by exposure.**CHRONIC OVEREXPOSURE:**... May cause bronchial irritation, coughing and pneumonia. Persons with pre-existing skin disorders, eye, cardio pulmonary and lung disease may be more susceptible to the effects of this products. Chronic exposure may cause mottling of teeth and bone damage (osteosclerosis) and fluorosis. Symptoms of fluorosis include brittle bones, weight loss, anemia, calcified ligaments, general ill health and joint stiffness.**OSHA REGULATORY STATUS:** Since this product is a mixture, there is no defined PELs (Personal Exposure Limits) established by OSHA. ACGIH TLVs (Threshold Limit Values) for hazardous components are listed in the Hazardous Ingredients Section of this data sheet.**CHRONIC OVEREXPOSURE:**... May cause bronchial irritation, coughing and pneumonia. Persons with pre-existing skin disorders, eye, cardio pulmonary and lung disease may be more susceptible to the effects of this products. Chronic exposure may cause mottling of teeth and bone damage (osteosclerosis) and fluorosis. Symptoms of fluorosis include brittle bones, weight loss, anemia, calcified ligaments, general ill health and joint stiffness.

Material Safety Data Sheet

ALUMA KLEEN 1000

SECTION III – COMPOSITION INFORMATION ON INGREDIENTS

THRESHOLD LIMIT VALUE:... The TLV in section II is the ACGIH/TLV-TWA and OSHA/PEL, (the time weighted average concentration for an eight hour work day.) The STEL is the (short term exposure limit.) (Ceil) is the ceiling limit.

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER	ACGIH/TWA	TLV/STEL
Sulfuric acid	10-20	7664-93-9	0.2 mg/M ³ *	NOT EST.
Phosphoric acid	10-20	7664-38-2	1 mg/M ³	3mg/M ³
Ammonium hydrogen difluoride	10-20	1341-49-7	2.5 mg/M ³ (as Fluoride)	NOT EST.

(Also contains biodegradable surfactant.)

SECTION IV – FIRST AID DATA

EYES: Water is the only accepted method of removal of this product from the eyes or skin. You may have 10 seconds or less to avoid serious permanent injury. Therefore, **IMMEDIATE** first aid must be given after any exposure. Moving the victim from water access for transport to medical aid should be done only on the advice of qualified medical personnel. While transporting victim to a medical facility, continue washing if possible. In case of contact, immediately flush eyes with lots of running water for at least 15 minutes. Call for medical assistance. In case of contact, immediately flush eyes with lots of running water for at least 15 minutes. Call for medical assistance.

SKIN (DERMAL): In case of skin contact, wash thoroughly with soap and water.

INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. (If available, give several glasses of milk.) If vomiting occurs spontaneously, keep airway clear and give more water. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: If exposure by inhalation is suspected, immediately move exposed individual to fresh air. If individual experiences nausea, headache, dizziness, has difficulty in breathing or is cyanotic, seek a health care professional immediately. Never give anything by mouth to an unconscious person.

SECTION V – FIRE FIGHTING MEASURES

FLASHPOINT: Non flammable, non combustible.

LOWER EXPLOSIVE LIMIT:... N/A

UPPER EXPLOSIVE LIMIT:... N/A

EXTINGUISHING MEDIA: Use extinguishing media appropriate to primary cause of fire.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid contact with fire fighting personnel as burns may result from contact with skin. When fighting a fire near or involving this product, wear a self-contained breathing apparatus (SCBA).

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

Material Safety Data Sheet

ALUMA KLEEN 1000

SECTION VI – ACCIDENTAL RELEASE MEASURES

SPILL: Always use appropriate protective equipment during clean-up. Stop leaks if possible. Review "Fire, reactivity hazards, and precautions" before proceeding with clean-up. Soak up small spills with dry sand, clay, or diatomaceous earth. Dike large spills. Cautiously dilute with water, neutralize with lime or soda ash and transfer to waste water treatment system. Prevent liquid from entering sewers and waterways. If this product is spilled and not recovered, or is recovered as a waste for treatment or disposal, the **REPORTABLE QUANTITY** is 1000 lbs. (based on the sulfuric or nitric acid content of the solution) or 5000 lbs. (based on the phosphoric or hydrochloric acid content). Comply with federal, state and local regulations on reporting releases.

SECTION – VII HANDLING AND STORAGE

HANDLING INFORMATION:... Do not get in eyes, on skin or on clothing. Avoid breathing dust, mists, or spray. Do not take internally. Wash thoroughly after handling or contact. Exposure can cause burns that are not immediately painful or visible. Do not add water to contents while in container because of possible violent reaction. Keep out of sun and away from heat, sparks and flames. Keep container tightly closed when not in use to prevent leakage. Do not use pressure to empty container. Do not wash out container or use it for other purposes. Replace closure after each withdrawal and return it with empty container. Empty containers retain product residue and must be handled as if they were full. **KEEP OUT OF REACH OF CHILDREN.**

STORAGE REQUIREMENTS:... Keep containers tightly closed when not in use. Empty container completely and dispose of in accordance with applicable regulations.

SECTION VIII – EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE PROTECTION: Chemical safety splash goggles and full face shield (8" min.) to protect against splashing in compliance with OSHA regulations are advised. OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist) Contact lenses should not be worn when working with any chemicals.

RESPIRATORY PROTECTION: Respiratory protection should be worn if levels exceed defined PEL(s) for this product or any hazardous component listed in the Hazardous Ingredient Section of this DATA SHEET.

PROTECTIVE CLOTHING: Impervious protective clothing and chemical resistant safety shoes should be worn to minimize contact. Emergency shower and eyewash facility should be in close proximity. (ANSI Z358.1)

VENTILATION: Local exhaust sufficient to maintain TLV below permissible exposure limits.

ADDITIONAL MEASURES: **SULFURIC ACID:** PEL (OSHA)= 1 mg/M³ / 8 hr/TWA; TLV (ACGIH) = 0.2 mg/M³ / 8 hr/TWA; *(A2 (Sulfuric acid contained in strong inorganic acid mists))

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear pink liquid with sharp odor

BOILING POINT: Appx. 212° F.

VAPOR PRESSURE: NOT EST.

VAPOR DENSITY (AIR=1): NOT EST.

SPECIFIC GRAVITY: 1.26

Material Safety Data Sheet

ALUMA KLEEN 1000

pH: 2.0 (1% SOLUTION), APPX. 1.0 AS IS

SOLUBILITY IN WATER: Completely soluble in water.

SECTION X – STABILITY AND REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Chlorinated products such as bleach, alkaline materials, metals, metal powder, carbides, chlorates, fumigates, nitrates, picrates, strong oxidizing, reducing, or combustible organic material. Hazardous gases are evolved on contact with chemicals such as chlorine bleach, cyanides, sulfides and carbides.

HAZARDOUS

DECOMPOSITION: Carbon monoxide, carbon dioxide. Oxides of sulfur, nitrogen and/or phosphorous may be released at extremely high temperatures. Reactions with chlorinated products produce deadly chlorine gas.

HAZARDOUS

POLYMERIZATION: Will not occur.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICITY EFFECTS: The highly acidic product can be acutely toxic in aquatic life through reduction in aqueous pH to toxic levels. Typically most aquatic species are intolerant of pH levels lower than 5.5 for any extended length of time. Reduction in aqueous pH levels may also cause the liberation of metals such as aluminum which will also contribute to exhibited toxicity. The highly acidic product will dissociate in water and undergo neutralization with carbonate and other naturally occurring buffering agents. Terrestrial organisms would be subject to severe burns if exposed to the acidic product during accidental release. A large, highly acidic product release, could lead to a persistent reduction in pH in a poorly buffered system lacking in carbonates or other naturally occurring acid neutralizers. Care should be taken to avoid accidental releases to aquatic or terrestrial ecosystems. **SULFURIC ACID:** Eye: This material is corrosive to the eyes. Skin: This material is corrosive to the skin. Ingestion: LD50, rat 2,140 mg/kg. Inhalation: LC50, (8 hr), guinea pigs: 30 mg/M³. **CARCINOGENIC, DEVELOPMENTAL, REPRODUCTIVE, MUTAGENIC EFFECTS:** No adequate animal data are available to define the characteristic potential of this material. **PHOSPHORIC ACID:** Acute oral toxicity (LD50): 1530 mg/kg (Rat). Acute dermal toxicity: (LD50): 2740 mg/kg (Rabbit). **CHRONIC EFFECTS ON HUMANS:** May cause damage to the following organs: blood, liver, skin, eyes, bone marrow.

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: **SULFURIC ACID:** Aquatic Toxicity: Slightly to moderately toxic. LC50 (96 hr) Bluegill sunfish: 10, 5 ppm. (48 hr) TLM - Flounder: 100-300 ppm. **PHOSPHORIC ACID:** Ecotoxicity: Not available. BODS and COD: Not available. Products of Biodegradation: Possibly short term degradation products are not likely. However, long term degradation products may arise.

Material Safety Data Sheet

ALUMA KLEEN 1000

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:..... Consult all LOCAL, STATE, and FEDERAL regulations with regard to proper and suitable disposal methods.

SECTION XIV – TRANSPORTATION INFORMATION

HAZARD CLASS AND LABEL: 8 (CORROSIVE)

PROPER SHIPPING NAME: CORROSIVE LIQUID, TOXIC, N.O.S. (SULFURIC ACID, AMMONIUM HYDROGEN DIFLUORIDE) 8, 6.1 UN-2922 PG-II

UN NUMBER: UN-2922

PACKAGING GROUP:..... PG – II

REPORTABLE QUANTITY: 1000 lbs. (based on sulfuric or nitric acid content of the solution) or 5000 lbs. (based on phosphoric or hydrochloric acid content).

SECTION XV – REGULATORY INFORMATION

LISTED CARCINOGEN:..... See Section XI for additional Toxicological and Carcinogenic information.

TSCA STATUS:..... **SULFURIC ACID:** TSCA Inventory Status: Reported/Included, TITLE III HAZARD CLASSIFICATION SECTIONS 311, 312: Acute: YES, Chronic: YES, Fire: NO, Reactivity: YES **HAZARDOUS CHEMICAL**
LISTS: SARA Extremely Hazardous Substance: YES; CERCLA Hazardous substance: YES; SARA Toxic Chemical: NO

SARA SECTION 313: **SULFURIC ACID:** Is subject to reporting requirements of Section 313, Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA), 40 CFR Part 372.

NFPA HEALTH: 3

NFPA FLAMMABILITY: 0

NFPA REACTIVITY: 1

SECTION XVI – OTHER INFORMATION

REFERENCES: The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. WESMAR CO. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

FOOT NOTES: ACGIH = American Conference of Governmental Industrial Hygienists
CAS = Chemical Abstracts Service Registry Number
CEILING = Ceiling Limit instantaneous/minimum time sufficient for detection
CEL = Corporate Exposure Limit
OSHA = Occupational Safety and Health Administration
PEL = Permissible Exposure Limits (OSHA)
STEL = Short Term Exposure Limit (15 minutes)
TDG = Transportation Of Dangerous Goods (Canada)
TLV = Threshold Limit Value (ACGIH)

Material Safety Data Sheet

ALUMA KLEEN 1000

TWA = Time Weighted Average (8 hours)

NOT EST. = Not established, N/A = Not applicable: (Ceil) = TLV Ceiling