

HMIS CODES: H F R P

2* 4 0 J

PRODUCT CODE : AR 3750
 PRODUCT NAME : WESMAR GUIDE COAT BLACK
 TYPE OF PRODUCT : Aerosol
 DOT CLASS : CONSUMER COMMODITY,ORM-D

===== SECTION I - MANUFACTURER'S IDENTIFICATION =====

MANUFACTURED BY :
 ADDRESS :
 INFORMATION PHONE :
 24-HOUR EMERGENCY : CALL CHEMTREC 1-800-424-9300 (SPILL, LEAK, FIRE, ACCIDENT)
 NAME OF PREPARER :
 DATE PREPARED/REVISED: 07/16/2002 DATE PRINTED: 07/16/02
 REASON REVISED : Format Update

===== SECTION IIA - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION =====

CAS NUMBER	HAZARDOUS COMPONENTS	WT. %	---OCCUPATION EXPOSURE LIMITS---			VAPOR PRESSURE	
			OSHA PEL**	ACGIH TLV	OTHER	mm HG @ deg-F	
00067-64-1	ACETONE	27.82	750 ppm	750 ppm	1780 mg/m3	181	68
00074-98-6	PROPANE	10.13	Simple	Asphyxiant	1000 ppm	3619	70
00075-28-5	ISOBUTANE	3.53	Not Est.	800 ppm	(estimate)		
00106-97-8	N-BUTANE	6.93	Not Est.	800 ppm	1900 mg/m3	>999	64
00108-88-3	TOLUENE	36.07	100 ppm	50 ppm	188 mg/m3	22	68
01333-86-4	CARBON BLACK	.49	3.5 mg/m3	3.5 mg/m3		N/A	
14807-96-6	TALC (NON-FIBROUS)	2.42					
14808-60-7	SILICA, CRYSTALLINE-QUARTZ	Trace	0.1 mg/m3	0.1 mg/m3	(Resp Dust)		
64742-89-8	PETROLEUM NAPHTHA, ALKANES & NAPHTHENES	3.23	Not Est.	300 ppm		80	70

**=PELS represent lowered 1989 limits and may not be enforceable by Federal OSHA.

===== SECTION IIB - OTHER REGULATORY INFORMATION =====

CAS NUMBER	DESCRIPTION	CARCINOGEN		SARA TITLE III		CALIFORNIA	
		NTP	IARC OSHA	302	313	P65	I II
00067-64-1	ACETONE						
00074-98-6	PROPANE						
00075-28-5	ISOBUTANE						
00106-97-8	N-BUTANE						
00108-88-3	TOLUENE				X	X	X
01333-86-4	CARBON BLACK	X	X				
14807-96-6	TALC (NON-FIBROUS)						
14808-60-7	SILICA, CRYSTALLINE-QUARTZ	X				X	
64742-89-8	PETROLEUM NAPHTHA, ALKANES & NAPHTHENES						

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE : -13 to 313 deg F. WT/GAL: 7.40 (W/ PROP: 6.53)
 VAPOR DENSITY : HEAVIER THAN AIR SOLIDS BY % WEIGHT: 11.13 w/o prop
 EVAPORATION RATE : MEDIUM compared to n-butyl acetate VOC BY % WEIGHT : 60.87% MIR : 0.03
 SOLUBILITY IN WATER: Non-Soluble

HAPS BY % WEIGHT : 46.93 w/o prop
 APPEARANCE AND ODOR: BLACK LIQUID, AROMATIC ODOR

WESMAR PRODUCTS, INC.
 1440 N.W. 45th STREET
 SEATTLE, WA 98107
 (206) 782-8186

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASS : Class IB Flammable
BULK PRODUCT FLASH POINT : -4 deg F. METHOD USED: P-WARTEN
BULK PROPELLANT FLASH POINT : -134 deg F.
PACKAGED PRODUCT FLAME EXTENSION: **0 inches
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.0% UPPER: 13.8%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all unnecessary personnel. Use full protective equipment, including self-contained breathing apparatus. Use water spray, preferably fog, to cool closed containers to prevent pressure build-up and possible explosion. Direct water stream is not recommended for oil base fires. Product may float and reignite on surface of water. Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams or waterways.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Explosive air-vapor mixtures may form which are dangerous when exposed to heat or flame. Vapors are heavier than air and may travel along the ground, or be moved by ventilation, and ignited by pilot lights, stoves, heaters, electric motors, sparks, flame, smoking, static discharge or other ignition sources even at locations distant from material handling site. Contents under pressure. Exposure to heat or prolonged exposure to sun may cause bursting.

=====SECTION V - REACTIVITY DATA =====

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide, Hydrocarbons, Nitrogen Oxides, Ammonia Fumes.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong Oxidizing agents, Acids, Lithium, Neodymium, Titanium, Ozone.

STABILITY: Stable. HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: High temperature and humidity, ignition source, vapor build-up.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, skin contact.

ACUTE EFFECTS FROM SHORT TERM EXPOSURE:

INHALATION: Vapors and mists cause severe irritation to nose, throat and lungs (burning, stinging, coughing). May cause headache, dizziness, nausea, weakness, shortness of breath and loss of coordination. Exposure to extremely high vapor concentrations may cause unconsciousness and asphyxiation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EYES: Contact with liquid or vapors causes severe irritation (redness, watering, itching, stinging, blurred vision).

SKIN: Contact causes severe irritation (dryness, itching, cracking, rash and swelling). Direct contact with propellant may cause frostbite.

SKIN ABSORPTION: May be absorbed through the skin in harmful amounts, especially with prolonged or repeated exposure. Symptoms may include headache, dizziness, nausea, weakness, loss of coordination.

SWALLOWING: Causes nausea, vomiting and diarrhea. Aspiration into the lungs may occur during ingestion or vomiting, resulting in lung injury.

CHRONIC EFFECTS FROM LONG TERM/REPEATED EXPOSURE: Long-term or repeated overexposure, without proper ventilation or personal protection, may cause damage to: kidneys, liver, eyes, brain and nervous system, dermatitis or other skin disorders, lungs, fetal damage (birth defects), spleen, heart.

OTHER: This product contains a form of Crystalline Silica. Long-term exposure to high levels of Crystalline Silica dusts may result in silicosis, a disabling lung disease. Always wear appropriate respiratory protection when exposed to sanding or grinding dusts.

CARCINOGEN DATA: Crystalline Silicas are classified by IARC as potential human carcinogens. Inhalation of Crystalline Silica dusts may cause lung tumors. Risk of cancer depends on level and duration of exposure.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Respiratory tract irritation, nausea, eye disorders, skin disorders, sensitization to chemical substances.

The following statement is required by California Proposition 65. Warning! This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

===== SECTION VII - EMERGENCY AND FIRST AID PROCEDURES =====

SWALLOWING: In case of accidental ingestion call Poison Center, Emergency Room or Physician immediately.

INHALATION: Remove from exposure to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get medical attention immediately.

EYE: Immediately flush with plenty of water for 15 minutes, while lifting upper and lower eyelids. Get medical attention.

SKIN: Immediately remove by wiping, followed by waterless hand cleaner and plenty of soap and water. Remove contaminated clothing and shoes. Wash or clean thoroughly before reuse. Get medical attention if irritation persists.

OTHER: Have Material Safety Data Sheet available if possible when calling Poison Center, Emergency Room or Physician.

===== SECTION VIII - PERSONAL PROTECTION =====

RESPIRATORY PROTECTION: OUTDOOR OR OPEN AREAS: If necessary because of wind, etc. use mechanical filter respirator or particle mask to avoid breathing spray mists. ENCLOSED OR RESTRICTED VENTILATION AREAS: Use NIOSH approved cartridge respirator to keep vapor/mist levels of hazardous ingredients (listed in section IIA) below the occupational exposure limits (PEL and TLV). If exposure levels are unknown, or limits exceeded, a full facepiece air-purifying cartridge respirator is recommended. Use filters to avoid breathing spray particles and sanding dusts. Follow respirators manufacturer's instructions for use.

VENTILATION: INDOOR OR ENCLOSED AREAS: Provide general mechanical ventilation or local exhaust to keep vapor concentrations below the PEL's and TLV's in section II and Lower Flammable Limits in section IV.

HAND PROTECTION: When necessary, wear impermeable gloves to prevent skin contact. Consult safety equipment supplier for specific recommendation of construction material.

EYE PROTECTION: Wear safety glasses, with side shields, designed to protect eyes against liquid splash and mists. Note: Contact lenses may contribute to the severity of an eye injury and should not be worn when working with chemicals.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing to avoid skin contact with liquid or mists.

WORK/HYGIENIC PRACTICES: Eye washes and safety showers are recommended in the workplace. Wash hands after using and before eating, drinking or using tobacco products. Thoroughly clean contaminated clothing and shoes before reuse. Periodically monitor exposure levels to hazardous ingredients listed in section II and review permissible limits.

===== SECTION IX - SPILL OR LEAK PROCEDURES =====

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Eliminate ignition sources and ventilate area. Evacuate all unnecessary personnel. Wear full protective equipment. Dike drains to prevent entering storm or sanitary sewers, rivers, streams or waterways. Contain spill and cover with inert absorbent material. Take up using non-sparking tools (aluminum, brass or copper) and place mixture into containers for disposal. Note: Some spills or releases may require special reporting to local, state or federal agencies.

WASTE DISPOSAL: Waste material and empty containers must be disposed of in accordance with all local, state and federal environmental control regulations. Use only approved waste management facilities.

DOT/CERCLA:

The DOT/CERCLA reportable quantity (RQ) for this product is 297 gallons based on TOLUENE RQ 1000 pounds.

===== SECTION X - SPECIAL PRECAUTIONS =====

HANDLING PRECAUTIONS: Keep liquid spray and vapors away from heat, sparks and flame. Turn off or remove all sources of ignition. Use proper methods of ventilation to prevent vapor build-up. Avoid spraying hot surfaces. Avoid breathing vapors, spray mists and sanding or grinding dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate methods of ventilation, respiratory and personal protective equipment. Do not heat, puncture or incinerate containers. Contents are under pressure and may contain explosive vapors, even when empty. Do not remove or deface label.

SHIPPING AND STORAGE PRECAUTIONS: Contents under pressure. Do not store above 120°F or permit prolonged exposure to sunlight. Protect containers from damage. Store in buildings or areas designed and protected for storage of aerosols. Keep out of reach of children. Do not store where contact with incompatible material could occur, even during an accidental spill or release.

===== SECTION XI - DISCLAIMER =====

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.