

AR 9280

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

SECTION I * PRODUCT IDENTIFICATION

PRODUCT NAME: METAL KLEEN

Chemical Family: N/A

PRODUCT NUMBER: 140

Formula: Proprietary

PRODUCT TYPE: AEROSOL

Date Prepared: 11/24/97

SUPPLIERS NAME: Wesmar Products, Inc.
1440 NW 45th St
Seattle, Wa 98107

Emergency Phone: (800) 255-3924

SUPPLIERS ADDRESS: (206) 782-8186

Information Phone: (206) 783-5344

D.O.T. HAZARD CONSUMER COMMODITY: ORM-D

HMS RATING: (BASED ON AEROSOL CONCENTRATE)

0-MINIMAL: 1-SLIGHT;
2-MODERATE
3-SERIOUS; 4-EXTREME

HEALTH 1
FLAMMABILITY 2

SECTION II * INGREDIENTS

CHEMICAL NAME	CAS #	% WT	313 CHEM	PEL	SKIN	TWA-TLV	CARCINOGEN
Isoparaffinic hydrocarbon	64742-48-9	10-20	NO	400 PPM	NO	400 PPM	NO
Isoparaffinic hydrocarbon	64742-46-7	10-20	NO	400 PPM	NO	400 PPM	NO
Food grade mineral oil	8042-47-5	1-5	NO	200 PPM	NO	200 PPM	NO
PROPELLANT – Carbon dioxide	124-38-9	1-5	No	1000 PPM	NO	1000 PPM	NO

SECTION III * PHYSICAL DATA

DATA BELOW BASED ON AEROSOL CONCENTRATE ONLY

Boiling Point – Approximately 300°F

Vapor Density (Air = 1): N/D

Solubility in Water of concentrate: Negligible

pH: N/A

Specific Gravity: (H2O=1@70°F): 0.862

DATA BELOW BASED ON TOTAL CONTENTS

Vapor Pressure of Can (psig @ 72°F): 80

Appearance/Odor: Cloudy liquid, mint odor.

Total VOC %: 89%

Flammable limits: lower – N/A ; Upper – N/A

SECTION IV * FIRE AND EXPLOSION HAZARDS

Flash Point (OF CONCENTRATE ONLY): 110°F (T.O.C.)

Flammability as per USA Flame Projection Test:

Flammable Spray

Extinguishing Media: Foam, Carbon dioxide, Dry Media

% Volatile by volume in can: Approximately 14%

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Exposure to temperature above 120°F may cause bursting.

SECTION V * REACTIVITY DATA

Stability: Material Stable

Hazardous Polymerization: Will not occur.

Incompatibility: strong alkalis, oxidizers, aluminum and other reactive metals.

Hazardous Decomposition Products: hydrogen chloride,
Phosgene (small amount).

SECTION VI * STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN

For Industrial & Institutional Use Only.

Store in a cool, dry area away from heat or open flame.

Do not Store at temperatures above 120°F.

NFPA Code 30b Rating: Level 3 Aerosol.

MATERIAL SAFETY DATA SHEET
COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

SECTION VII * HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonia.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists, get medical attention immediately.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII * SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.

VENTILATION: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

PROTECTIVE GLOVES: None needed for proper use in accordance with label directions! Use chemical resistant gloves if hand contact will be made.

EYE PROTECTION: None needed unless it is anticipated that a splash or sprayback will occur, then wear safety glasses.

SECTION IX * SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Allow propellant to evaporate.

Maintain local exhaust and adequate ventilation.

No smoking. Keep sparks, heat sources and open flame far away from spill or leaks. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD:

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT ACCEPTABLE N/E= NOT ESTABLISHED N/D= NOT DETERMINED <= LESS THAN >= MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulation, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.