

BS 0342



13400 SATICOY STREET
NORTH HOLLYWOOD, CALIFORNIA 91605

MATERIAL HEALTH AND SAFETY BULLETIN



MANUFACTURER'S NAME

Wesmar Products, Inc
1440 NW 45th St

STREET ADDRESS

Seattle, Wa 98107
(206)782-8186

CITY, STATE, AND ZIP CODE

EMERGENCY TELEPHONE NO.

PRODUCT: #342 RUBBER DRESSING

GENERIC NAME: VOLATILE SOLVENT

CHEMICAL FAMILY: HYDROCARBON MIXTURE

DOT PROPER SHIPPING NAME:

WARNING STATEMENT:

DANGER EXTREMELY FLAMMABLE.
DO NOT induce vomiting if swallowed.
For industrial use only.

Section I —INGREDIENTS

PETROLEUM NAPHTHA

CAS #64742-89-8

PEL

50
100
300

TLV*

400

TLV*

HMIS HAZARD INDEX

4 - Severe
3 - Serious
2 - Moderate
1 - Slight
0 - Minimal

HMIS RATINGS

Health.....1
Flammability..3
Reactivity....0

Carcinogens: None Known

*Threshold Limit Value

A. OSHA ☒B. ACGIH ☐C. See Section III ☐D. Other ☐

Section II — EMERGENCY AND FIRST AID PROCEDURES

EMERGENCY: Have a physician call LOS ANGELES POISON CONTROL CENTER (24 hrs.) 213/664-2121

Eye Contact	If this product comes in contact with the eyes, flush with large quantities of water for at least 15 minutes and seek immediate medical attention.
Skin Contact	If this product comes in contact with the skin, wash with soap and large quantities of water. Seek medical attention if irritation from contact persists.
Inhalation	If breathing stops, begin artificial respiration and seek immediate medical attention.
Ingestion	If this product is swallowed, DO NOT induce vomiting. Seek immediate medical advice and/or attention.

Section III — PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

Eye Effects	This product may be an eye irritant.
Skin Effects	This product may cause skin irritation upon prolonged or repeated contact.
Systemic Effects	Various studies have shown a possible association with exposure to this product and the following: Respiratory tract irritation Central nervous system depression in high concentrations

Section IV — SPECIAL PROTECTION INFORMATION

Respiratory Protection Specify Type	The use of respiratory protection depends on vapor concentration above the time-weighted TLV; use a NIOSH approved cartridge respirator or gas mask.		
Ventilation	General mechanical ventilation may be sufficient to keep product vapor concentrations within specified time-weighted TLV ranges. If general ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required. Other special precautions such as respiratory masks or environmental containment devices may be required in extreme cases.		
Protective Gloves	The use of impermeable gloves is advised to prevent skin irritation in sensitive individuals.	Eye protection	Safety glasses, chemical goggles and/or face shields are recommended to safeguard against potential eye contact, irritation, or injury.
Other Protective Equipment	Impermeable aprons are advised when working with this product. The availability of eye washes and safety showers in work areas is recommended.		

Section V — REACTIVITY DATA

Stability	Unstable		Conditions to Avoid:
	Stable	X	
Incompatibility (Materials to Avoid)	This product is incompatible with: strong oxidizing agents strong acids or bases selected amines		
Hazardous Decomposition Products	Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.		
Hazardous Polymerization	May Occur		Conditions to Avoid:
	Will Not Occur	X	

Section IV — SPILL OR LEAK PROCEDURES

HIGHWAY OR RAILWAY SPILLS—CALL CHEMTREC 800/424-9300

Precautions In Case Of Release or Spill	Keep sources of ignition and hot metal surfaces isolated from the spill. Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts of spilled material may be absorbed into an appropriate absorbant.
Reportable Quantity	Notify Coast Guard National Response Center; Phone No. 800-424-8802, If Spill Is Greater Than <u>1000</u> lbs. (Kilograms)
Waste Disposal Method	Dispose of used product in accordance with applicable local, county, state and federal regulations.

Section VII — STORAGE AND SPECIAL PRECAUTIONS

Handling and Storing Precautions	Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. (See Section IV.)
Other Precautions	Personnel should avoid inhalation of vapors. (See Sections I, II, III, V, VI) Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected areas with water. (See Sections II, IV, VI).

Section VIII — FIRE AND EXPLOSION HAZARD DATA

DOT Flammability Classification	FLAMMABLE LIQUID	Flash Point Range: ☒ Below 20° F, ☐ 20° F - 100° F ☐ 100° F - 200° F, ☐ Over 200° F ☐ None to boiling
Extinguishing Media	Use foam, CO ₂ or dry chemical fire fighting apparatus.	
Unusual Fire and Explosion Hazards	Keep work areas free of hot metal surfaces and other sources of ignition.	
Fire Fighting Procedures	The use of self-contained breathing apparatus is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes.	

Section IX — PHYSICAL DATA

Approximate Boiling Range, ° F	114° - 285°F	Vapor Density: ☒ Heavier Than Air ☐ Lighter
Evaporation Rate: ☐ Faster Than Ether ☒ Slower	Percent Volatile: 100%	Solubility in Water: Negligible
Specific Gravity: ☒ Lighter Than Water ☐ Heavier	Weight per Gallon: 5.83	
Appearance and Odor:	This product is clear, has little if any color and has a characteristic odor.	

Section X — DOCUMENTARY INFORMATION

Product Code No. #342

Issue Date 06/01/04

Prepared By D. KLINGERMANN

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.