

CA 1213

Wesmar Products
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Material Safety Data Sheet

HMIS Ratings
Health 1
Flammability 4
Reactivity 0
Protection X

1 Chemical Product and Company Identification

Manufacturer Information Wesmar Products
1440 NW 45th ST
Seattle, WA 98107

Phone (206) 782-8186

Emergency Phone CHEMTREC
1-800-424-9300
FOR INTERNATIONAL
CALLS
703-527-3887

Date Prepared 2002-Apr-18

Product Identity ENGINE PAINTS (IMPORT MAGNESIUM)

Product Code Number G003-1816 **CA 1213**

Product Use Automotive Reconditioning Product

Version # 1.0

CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits	
				TLV-ACGIH	Carcinogen
2-PROPANONE	67-64-1	25 - 30	750 ppm TWA; 1800 mg/m3 TWA	500 ppm TWA	No
SOLVENT NAPHTHA, PETROLEUM, LIGHT ALIPH.	64742-89-8	20 - 25			No
BENZENE, DIMETHYL-	1330-20-7	0 - 5	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA	No
PETROLEUM GASES, LIQUEFIED, SWEETENED	68476-86-8	30			No
Non-hazardous and other ingredients below reportable levels	Proprietary	15	N/AP	N/AP	N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.

Inhalation Excessive inhalation of this product may cause headache, dizziness, blurred vision, nausea and vomiting.

Ingestion Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazard Statements

EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE.

4 First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.
Notes to Physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5 Fire Fighting Measures

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Alcohol foam. Carbon dioxide. Dry chemical.

General Fire Hazards

Pressurized Container: May explode when exposed to heat or flame.

Fire Fighting Equipment/Instructions

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Flash Point	< 1 F (<-17 C) lowest flashing component	TCC
--------------------	--	-----

Flammability Limits in Air, Lower, % by Volume	%
---	---

Flammability Limits in Air, Upper, % by Volume	15.0 %
---	--------

6 Accidental Release Measures

Clean-Up Procedures

Ventilate the contaminated area. Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Do not puncture the container. Avoid getting this material into contact with your skin and eyes.

Storage Procedures

Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Recommended gloves include rubber, neoprene, nitrile or viton. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material. Eye wash fountain and emergency showers are recommended.

9 Physical & Chemical Properties

Boiling Point	N/AV
Specific Gravity	< 1
Vapor Pressure	< 20 mm/Hg
Evaporation Rate	Slower than ether
Vapor Density	> 1
Freezing Point	N/AV

10 Chemical Stability & Reactivity Information

Chemical Stability

Stable under normal conditions.

Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

US DOT HMR Information

Proper Shipping Name	Consumer commodity
Identification Number	None
Hazard Class	ORM-D
Labels Required	None

15 Regulatory Information

US Federal Regulations

CERCLA/SARA - Section 313 - Emission Reporting

2-PROPANOL
BENZENE, DIMETHYL-
ETHANOL, 2-BUTOXY-

16 Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By	Technical Department
Issue Date	18-Apr-2002