

CA 1316  
**ASHLAND**  
**SAFETY DATA SHEET**

Page: 1  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Wesmar Products, Inc  
1440 NW 45th ST  
Seattle, WA 98107  
(206) 782-8186

Emergency telephone number

1-800-ASHLAND  
(1-800-274-5263)

Product name

CAR BRITE® XTRA DTY PLUS AERO CLEANER

Product code

CBOOE006B18

Product Use Description

No data

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: aerosol

WARNING! Corrosive to skin, Severe eye irritant.

**Potential Health Effects**

**Routes of Exposure**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye Contact**

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

**Skin Contact**

May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

**Inhalation**

Breathing aerosol and/or mist is possible when material is sprayed. Aerosol and mist may present a greater risk of injury because more material may be present in the air than from vapor alone. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

# ASHLAND

## SAFETY DATA SHEET

Page: 2  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions)

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), loss of coordination

### Target Organs

Diethylene glycol monobutyl ether has been found to cause breakage of red blood cells following ingestion in rats. Injury to other organs including liver and kidneys was considered secondary to the effect on the blood.

### Carcinogenicity

There is no information available. The chance of this material causing cancer is unknown. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

### Reproductive Hazard

Diethylene glycol monobutyl ether did not cause harm to the fetus when given orally or when applied to the skin in laboratory animal studies.

### Other Information

No data

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components                           | CAS-No.  | Concentration |
|--------------------------------------|----------|---------------|
| BUTANE NORMAL                        | 106-97-8 | >=5-<10%      |
| DIETHYLENE GLYCOL MONOBUTYL<br>ETHER | 112-34-5 | >=5-<10%      |

## 4. FIRST AID MEASURES

# ASHLAND

## SAFETY DATA SHEET

Page: 3  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

### Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

### Notes to Physician

**Hazards:** Diglycol ethers may cause acidosis.

**Treatment:** No information available.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Water mist, carbon dioxide (CO<sub>2</sub>), dry chemical

### Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

### Precautions for Fire-Fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

# ASHLAND

## SAFETY DATA SHEET

Page: 4  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

### Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

### Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

### Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

| BUTANE NORMAL |                                   | 106-97-8    |
|---------------|-----------------------------------|-------------|
| NIOSH         | Recommended exposure limit (REL): | 800 ppm     |
| NIOSH         | Recommended exposure limit (REL): | 1,900 mg/m3 |
| OSHA Z1A      | time weighted average             | 800 ppm     |
| OSHA Z1A      | time weighted average             | 1,900 mg/m3 |

# ASHLAND

## SAFETY DATA SHEET

Page: 5  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

|           |                                   |             |
|-----------|-----------------------------------|-------------|
| US CA OEL | Time Weighted Average (TWA)       | 800 ppm     |
|           | Permissible Exposure Limit (PEL): |             |
| US CA OEL | Time Weighted Average (TWA)       | 1,900 mg/m3 |
|           | Permissible Exposure Limit (PEL): |             |

### General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

### Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

### Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). Other protective equipment: eyewash station, emergency shower.

### Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                     |          |
|---------------------|----------|
| Physical state      | aerosol  |
| Form                | aerosol, |
| Colour              | No data  |
| Odour               | No data  |
| Boiling point/range | No data  |
| pH                  | 10.5     |
| Flash point         | No data  |
| Evaporation rate    | No data  |

# ASHLAND

## SAFETY DATA SHEET

Page: 6  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Explosion limits                        | 1.9 %(V) 9.5 %(V)                  |
| Vapour pressure                         | 60.0000 mmHg @ 70.00 °F / 21.11 °C |
| Vapour density                          | No data                            |
| Density                                 | 0.95 g/cm3 @ 60.00 °F / 15.56 °C   |
| Solubility                              | No data                            |
| Partition coefficient (n-octanol/water) | No data                            |
| Autoignition temperature                | No data                            |

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to Avoid

Avoid contact with:

#### Incompatible Products

Avoid contact with: alkalis, strong oxidizing agents

#### Hazardous Decomposition Products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

#### Hazardous Reactions

Product will not undergo hazardous polymerization.

#### Thermal Decomposition

No data

### 11. TOXICOLOGICAL INFORMATION

#### Acute Oral Toxicity

BUTANE NORMAL

LD 50 Rat: 5 g/kg

DIETHYLENE GLYCOL  
MONOBUTYL ETHER

LD 50 Rat: 6,560 mg/kg

#### Acute Inhalation Toxicity

# ASHLAND

## SAFETY DATA SHEET

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

Page: 7  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

BUTANE NORMAL

LC 50 Rat: 658 mg/l,

### Acute Dermal Toxicity

BUTANE NORMAL

LD 50 Rabbit: 3.16 g/kg

DIETHYLENE GLYCOL  
MONOBUTYL ETHER

LD 50 Rabbit: 2,700 mg/kg

## 12. ECOLOGICAL INFORMATION

### Aquatic Toxicity

#### Acute and Prolonged Toxicity to Fish

No data

#### Acute Toxicity to Aquatic Invertebrates

No data

### Environmental Fate and Pathways

No data

## 13. DISPOSAL CONSIDERATIONS

### Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

## 14. TRANSPORT INFORMATION

IMDG:

# ASHLAND

## SAFETY DATA SHEET

Page: 8  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

UN1950, AEROSOLS 2.1,  
**IATA\_P:**  
UN1950, Aerosols, flammable 2.1,  
**IATA\_C:**  
UN1950, Aerosols, flammable 2.1,  
**CFR\_ROAD:**  
UN1950, Aerosols 2.1,  
**CFR\_RAIL:**  
UN1950, Aerosols 2.1,  
**CFR\_INWTR:**  
UN1950, Aerosols 2.1,  
**IMDG\_INWTR:**  
UN1950, AEROSOLS 2.1,  
**IMDG\_ROAD:**  
UN1950, AEROSOLS 2.1,  
**IMDG\_RAIL:**  
UN1950, AEROSOLS 2.1,

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

### 15. REGULATORY INFORMATION

#### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

**SARA Hazard Classification** Acute Health Hazard

#### SARA 313 Component(s)

**OSHA Hazards** Corrosive to skin  
Severe eye irritant

|      | Health | Flammability | Reactivity | Other |
|------|--------|--------------|------------|-------|
| HMIS | 2      | 2            | 0          |       |
| NFPA | 2      | 2            | 0          |       |

**ASHLAND**  
**SAFETY DATA SHEET**

CAR BRITE® XTRA DTY PLUS  
AERO CLEANER CBOOE006B18

Page: 9  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0410643  
Version: 1.

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).