

CA 2001

ASHLAND
SAFETY DATA SHEET

Page: 1

Revision Date: 04/04/2007

Print Date: 4/24/2007

MSDS Number: R0411195

Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® CB C/V DYE BEIGE DYES
Product code	CBOOG014-0001
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: aerosol

DANGER! Toxic by inhalation, Moderate skin irritant, Severe eye irritant, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin Contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Passage of this material into the body through the skin is possible, and may add to toxic effects from breathing or swallowing.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidney, central nervous system, male reproductive system, auditory system. Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), tight feeling in the chest, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle weakness, respiratory depression (slowing of the breathing rate), blurred vision, shortness of breath, loss of coordination, confusion, irregular heartbeat, high blood sugar, narcosis (dazed or sluggish feeling), coma, and death.

Target Organs

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Based on animal studies, exposure to methyl ethyl ketone (MEK) increases the onset of peripheral neuropathy caused by exposure to methyl butyl ketone (MBK), and/or n-hexane, and/or ethyl butylketone. MEK alone has not been shown to cause peripheral neuropathy. Prolonged intentional toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: cardiac sensitization, anemia, respiratory tract damage (nose, throat, and airways), testis damage, kidney damage, liver damage, lung damage, effects on hearing, central nervous system damage. Overexposure to this material (or its components) has been suggested as a cause

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

of the following effects in humans:; central nervous system effects, cardiac sensitization, anemia, effects on hearing, kidney damage

Carcinogenicity

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. The International Agency for Research on Cancer (IARC) has classified ethylbenzene as a possible human carcinogen.

Reproductive Hazard

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ACETONE	67-64-1	>=20-<30%
TOLUENE	108-88-3	>=15-<20%
METHYL ETHYL KETONE	78-93-3	>=10-<15%
BUTANOL NORMAL	71-36-3	>=5-<10%
TALC	14807-96-6	>=5-<10%
CALCIUM CARBONATE	1317-65-3	>=5-<10%
XYLENE	1330-20-7	>=1.5-<5%
ETHYL BENZENE	100-41-4	>=1-<1.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water mist, carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001**Environmental Precautions**

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines**

ACETONE		67-64-1
ACGIH	time weighted average	500 ppm
ACGIH	Short term exposure limit	750 ppm
NIOSH	Recommended exposure limit	250 ppm
	(REL):	
NIOSH	Recommended exposure limit	590 mg/m3
	(REL):	
OSHA Z1	Permissible exposure limit	1,000 ppm
OSHA Z1	Permissible exposure limit	2,400 mg/m3

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

TOLUENE		108-88-3	
ACGIH NIC	time weighted average	20 ppm	
ACGIH	time weighted average	50 ppm	
NIOSH	Recommended exposure limit (REL):	100 ppm	
NIOSH	Recommended exposure limit (REL):	375 mg/m3	
NIOSH	Short term exposure limit	150 ppm	
NIOSH	Short term exposure limit	560 mg/m3	
OSHA Z2	time weighted average	200 ppm	
OSHA Z2	Ceiling Limit Value:	300 ppm	
OSHA Z2	Maximum concentration:	500 ppm	
METHYL ETHYL KETONE		78-93-3	
ACGIH	time weighted average	200 ppm	
ACGIH	Short term exposure limit	300 ppm	
NIOSH	Recommended exposure limit (REL):	200 ppm	
NIOSH	Recommended exposure limit (REL):	590 mg/m3	
NIOSH	Short term exposure limit	300 ppm	
NIOSH	Short term exposure limit	885 mg/m3	
OSHA Z1	Permissible exposure limit	200 ppm	
OSHA Z1	Permissible exposure limit	590 mg/m3	
BUTANOL NORMAL		71-36-3	
ACGIH	time weighted average	20 ppm	
NIOSH	Ceiling Limit Value and Time Period (if specified):	50 ppm	
NIOSH	Ceiling Limit Value and Time Period (if specified):	150 mg/m3	
OSHA Z1	Permissible exposure limit	100 ppm	
OSHA Z1	Permissible exposure limit	300 mg/m3	
OSHA Z1A	Ceiling Limit Value:	50 ppm	
OSHA Z1A	Ceiling Limit Value:	150 mg/m3	
US CA OEL	Ceiling Limit Value:	50 ppm	
US CA OEL	Ceiling Limit Value:	150 mg/m3	
TALC		14807-96-6	
ACGIH	time weighted average	2 mg/m3	Respirable fraction.
NIOSH	Recommended exposure limit (REL):	2 mg/m3	Respirable.
OSHA Z1A	time weighted average	2 mg/m3	Respirable dust.
Z3	time weighted average	0.1 mg/m3	Respirable.
Z3	time weighted average	0.3 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA)	2 mg/m3	Respirable dust.
	Permissible Exposure Limit (PEL):		
CALCIUM CARBONATE		1317-65-3	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Respirable.
NIOSH	Recommended exposure limit (REL):	10 mg/m3	Total

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE DYES CBOOG014-0001

NIOSH	Recommended exposure limit (REL):	5 mg/m3	Respirable.
NIOSH	Recommended exposure limit (REL):	10 mg/m3	Total
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Respirable.
NIOSH	Recommended exposure limit (REL):	10 mg/m3	Total
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		

XYLENE

1330-20-7

ACGIH	time weighted average	100 ppm
ACGIH	Short term exposure limit	150 ppm
OSHA Z1	Permissible exposure limit	100 ppm
OSHA Z1	Permissible exposure limit	435 mg/m3
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	655 mg/m3
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	655 mg/m3
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	150 ppm

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

Page: 8
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

NIOSH	Short term exposure limit	655 mg/m3
ETHYL BENZENE	100-41-4	
ACGIH	time weighted average	100 ppm
ACGIH	Short term exposure limit	125 ppm
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	435 mg/m3
NIOSH	Short term exposure limit	125 ppm
NIOSH	Short term exposure limit	545 mg/m3
OSHA Z1	Permissible exposure limit	100 ppm
OSHA Z1	Permissible exposure limit	435 mg/m3

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Other protective equipment: eyewash station, emergency shower.

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Physical state	aerosol
----------------	---------

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

Form	aerosol,
Colour	No data
Odour	No data
Boiling point/range	No data
pH	No data
Flash point	No data
Evaporation rate	No data
Explosion limits	1.0 %(V) 12.8 %(V)
Vapour pressure	85.0000 mmHg @ 60.00 °F / 15.56 °C
Vapour density	No data
Density	< 1 g/cm3 @ 59.9 °F / 15.5 °C
	No data
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Avoid contact with:

Incompatible Products

Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

ACETONE	LD 50 Rat: 5,800 mg/kg
TOLUENE	LD 50 Rat: 5,000 mg/kg
METHYL ETHYL KETONE	LD 50 Mouse: 670 mg/kgLD 50 Rat: 2,300 - 3,500 mg/kg
BUTANOL NORMAL	LD 50 Rat: 790 mg/kg
XYLENE	LD 50 Rat: 4,300 mg/kg
ETHYL BENZENE	LD 50 Rat: 3,500 mg/kg

Acute Inhalation Toxicity

ACETONE	LC 50 Rat: 16000 ppm, 4 h
TOLUENE	LC 50 Rat: 8000 ppm, 4 h
METHYL ETHYL KETONE	LC 50 Rat: 11,700 mg/l, 4 h
ETHYL BENZENE	LC Lo Rat: 4000 ppm, 4 h

Acute Dermal Toxicity

ACETONE	LD 50 Rabbit: 20,000 mg/kg
TOLUENE	LD 50 Rabbit: 12,124 mg/kg
METHYL ETHYL KETONE	LD 50 Rabbit: 5 g/kg
BUTANOL NORMAL	LD 50 Rabbit: 3,400 mg/kg
XYLENE	LD 50 Rabbit: 2,000 mg/kg
ETHYL BENZENE	LD 50 Rabbit: 15,433 mg/kg

ASHLAND

SAFETY DATA SHEET

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

Page: 11
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1950, AEROSOLS 2.1,

IATA_P:

UN1950, Aerosols, flammable 2.1,

IATA_C:

UN1950, Aerosols, flammable 2.1,

CFR_ROAD:

UN1950, Aerosols 2.1,

CFR_RAIL:

UN1950, Aerosols 2.1,

CFR_INWTR:

ASHLAND

SAFETY DATA SHEET

Page: 12
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

UN1950, Aerosols 2.1,
IMDG_INWTR:
UN1950, AEROSOLS 2.1,
IMDG_ROAD:
UN1950, AEROSOLS 2.1,
IMDG_RAIL:
UN1950, AEROSOLS 2.1,

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

Additional Regulations

US. Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

SARA Hazard Classification Acute Health Hazard
 Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards Toxic by inhalation
 Moderate skin irritant
 Severe eye irritant
 Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	2	4	0	
NFPA	2	4	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

ASHLAND
SAFETY DATA SHEET

CAR BRITE® CB C/V DYE BEIGE
DYES CBOOG014-0001

Page: 13
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0411195
Version: 1.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department
(1-800-325-3751).