

CG 1112 - CG 1112A

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: WIRE WHEEL CLEANER 4/1 GAL

SAP Material No: CBOOE011-03

Wesmar Products Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
PHOSPHORIC ACID	7664-38-2	10.0- 20.0
HYDROFLUORIC ACID	7664-39-3	6.0- 6.0
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	1.0- 7.0
NONIONIC SURFACTANT	68439-46-3	1.0- 7.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Material is corrosive to eyes. May cause burns.

Skin

Both the liquid and vapor can cause severe burns which may not be immediately painful or visible. Pain may become gradually more severe, possibly taking 1-24 hours to become noticable. These burns can be very deep, possibly causing bone damage, and are very slow to heal. Even solutions containing 2% or less hydrogen fluoride or other inorganic fluoride compounds can cause burns and tissue damage. Passage of this material through the skin may be harmful or fatal.

Swallowing

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation, burns and tissue damage. Shock may occur. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing this material may be harmful or fatal. May cause severe irritation and burns to the nose, throat, and respiratory tract. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, sneezing, headache, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficult breathing, irregular heartbeat, blood in the urine, blood abnormalities (breakage of red blood cells), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, coma, and death.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

Target Organ Effects

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Repeated, prolonged overexposure to inorganic fluoride compounds may result in gastrointestinal disturbances, loss of weight, anemia (reduced number of red blood cells), diseases of the teeth, and skeletal fluorosis. Skeletal fluorosis is characterized by bone and joint pain, limited motion in the joints or spine, increased bone density which can cause the bones to become brittle, and hardening of ligaments. Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: nervous system effects, blood abnormalities, liver abnormalities, kidney damage.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Other Health Effects

Hydrofluoric acid has been shown to cause permanent changes in the DNA of insect germ cells. Changes in these cells can be passed to the next generation. The relevance of this finding to human health is uncertain.

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush contaminated skin with large quantities of cool running water for 5 minutes. Remove contaminated clothing while flushing contaminated skin. Immediately after washing, apply 2.5% calcium gluconate gel to all affected skin areas. (Note: If gel is not prepared within 5 minutes, continue flushing until gel is prepared.) The gel should be massaged into the affected skin by personnel wearing gloves to prevent skin contamination during first aid. Gel should be applied every 15 minutes and massaged continuously. Instead of calcium gluconate treatment, the affected areas may be soaked in iced 0.13% benzalkonium chloride solution (Zephiran chloride). Use ice cubes rather than shaved ice to prevent frostbite. If it is not practical to immerse affected area, towels should be soaked with iced 0.13% benzalkonium chloride solution and used as compresses for the burned area. Compresses should be changed every

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

2-3 minutes and continued until pain is relieved or victim is seen by a physician. If neither calcium gluconate nor benzalkonium chloride is available, use an iced saturated water solution of magnesium sulfate (Epsom salts), or if that is not available, iced 70% alcohol or ice water. Local anesthetics should be avoided since relief of pain indicates success of the treatment.

GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

NOTE - Calcium gluconate gel can be prepared by mixing a 10 milliliter ampule of calcium gluconate with a 2-ounce tube of K-Y jelly (Johnson & Johnson). After a jar of this mixture has been opened and used, it should be discarded to prevent bacterial or chemical contamination.

Swallowing

Seek immediate medical attention. Do not induce vomiting. If individual is conscious and alert, immediately rinse mouth with water and give milk to drink (one-half to one glassful), chewable calcium carbonate tablets, or milk of magnesia. The calcium in milk and the magnesium in milk of magnesia will act as an antidote in cases of hydrofluoric acid ingestion. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. This product contains hydrofluoric acid (HF). Acute local effects from HF exposure are concentration-dependent. If untreated or exposure is prolonged, even dilute solutions of HF can cause delayed toxicity following penetration to subcutaneous tissue. Acute systemic toxicity is largely dependent upon the total amount of fluoride ion absorbed. Thus ingestion, skin contact or significant inhalation can cause severe systemic effects including electrolyte (calcium, magnesium, potassium) and acid-base abnormalities with resulting cardiovascular effects. Exposure of >5% of the body surface area with any concentration of HF may predispose the patient to development of hypocalcemia. Chronic exposure to less than acutely toxic amounts of HF is a low toxicity hazard. Repeated exposure and absorption of 10-80 mg of fluoride per day may produce systemic fluorosis. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidneys, nervous system, blood-forming system, bone. Exposure to this material may aggravate any pre-existing condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with pre-existing heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: acid vapors, carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

During a fire, irritating or toxic decomposition products may be generated.

Extinguishing Media

alcohol foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Not determined

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Cover the contaminated surface with sodium bicarbonate or a soda ash/flaked lime mixture (50-50). Mix and add water if necessary to form a slurry. Scoop up slurry and wash site with soda ash solution. Proper mixing procedures are essential. Trained personnel should conduct this procedure. Untrained personnel should be removed from the spill area. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Persons not wearing protective equipment should be excluded from area of spill until clean-up is completed. Stop spill at source. Dike to prevent spreading. Pump to salvage tank. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

Storage

Under oxidation conditions, peroxides may be formed. If they become concentrated, these peroxides may present an explosion hazard. Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

PHOSPHORIC ACID (7664-38-2)
OSHA VPEL 1.000 mg/m3 - TWA
OSHA VPEL 3.000 mg/m3 - STEL
ACGIH TLV 1.000 mg/m3 - TWA
ACGIH TLV 3.000 mg/m3 - STEL

HYDROFLUORIC ACID (7664-39-3)
OSHA VPEL 3.000 ppm - TWA as F
OSHA VPEL 6.000 ppm - STEL as F
ACGIH TLV 2.600 mg/m3 - Ceiling
ACGIH TLV 3.000 ppm - Ceiling as F

ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2)
OSHA VPEL 25.000 ppm - TWA ((Skin))
ACGIH TLV 20.000 ppm - TWA

NONIONIC SURFACTANT (68439-46-3)
No exposure limits established

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 10/07/05
Date Printed: 08/24/06
MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
No data

Vapor Pressure
(for component) 775.000 mmHg

Specific Vapor Density
No data

Specific Gravity
1.078 @ 60.00 F

Liquid Density
9.000 lbs/gal @ 60.00 F
9.000 lbs/gal @ 60.00 F

Percent Volatiles (Including Water)
No data

Evaporation Rate
No data

Appearance
No data

State
LIQUID

Physical Form
No data

Color
COLORLESS

Odor
PUNGENT

pH
< 1.0

10. STABILITY AND REACTIVITY

Hazardous Polymerization
Product will not undergo hazardous polymerization.

Hazardous Decomposition
May form: acid vapors, carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability
Stable.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

Incompatibility

Avoid contact with: organic materials, strong alkalies, strong oxidizing agents, strong reducing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

CORROSIVE LIQUIDS, TOXIC, N.O.S., 8, UN2922, II

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

HYDROFLUORIC ACID
PHOSPHORIC ACID

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

1740	HYDROGEN FLUORIDE
34171	PHOSPHORIC ACID

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component

Component

PHOSPHORIC ACID
HYDROGEN FLUORIDE

5000
100

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008

Date Prepared: 10/07/05

Date Printed: 08/24/06

MSDS No: 525.0405960-001.002

WIRE WHEEL CLEANER 4/1 GAL

SARA 302 Components - 40 CFR 355 Appendix A

Section 302 Component(s)	TPQ (lbs)	RQ (lbs)
HYDROGEN FLUORIDE	100	100

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire() Reactive() Sudden Release of Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number
HYDROGEN FLUORIDE	7664-39-3
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

PHOSPHORIC ACID	7664-38-2
HYDROGEN FLUORIDE	7664-39-3
2-BUTOXY ETHANOL	111-76-2

Pennsylvania RTK Label Information

PHOSPHORIC ACID	7664-38-2
HYDROFLUORIC ACID	7664-39-3
ETHANOL, 2-BUTOXY-	111-76-2

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.