

CG 1115, 1116, 1116A
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 06/08/2007
Print Date: 6/14/2007
MSDS Number: R0406088
Version: 1.2

CAR BRITE® MAG WHEEL NA Non-Acid Wheel Cleaner CBOOEL02-09

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® MAG WHEEL NA Non-Acid Wheel Cleaner
Product code	CBOOEL02-09
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid,, dark green

WARNING! MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS. MAY CAUSE ALLERGIC SKIN REACTION.

Potential Health Effects

Routes of Exposure

Inhalation, Skin Absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin Contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Additional symptoms of skin contact may include: allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects) Passage of this material into the body through the skin is possible, and skin contact may be harmful.

CAR BRITE® MAG WHEEL NA Non-
Acid Wheel Cleaner CBOOEL02-09

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing this material may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, blood-forming system

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficult breathing, blood in the urine, blood abnormalities (breakage of red blood cells), kidney damage, liver damage, lung damage, coma, and death

Target Organs

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, blood abnormalities, kidney damage

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. d-Limonene caused kidney cancer in male rats, but not in female rats or in mice of either sex, when given to the animals through a feeding tube. The relevance of this finding to humans is uncertain.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 06/08/2007
Print Date: 6/14/2007
MSDS Number: R0406088
Version: 1.2

CAR BRITE® MAG WHEEL NA Non-Acid Wheel Cleaner CBOOEL02-09

Reproductive Hazard

This material (or a component) has been shown to cause birth defects in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ETHYLENE GLYCOL MONOBUTYL ETHER SURFACTANT	111-76-2	$\geq 1.5 - < 5\%$
	NJTS# 254504001-5149	$\geq 1.5 - < 5\%$
ORANGE OIL, COLD PRESSED	8008-57-9	$\geq 1 - < 1.5\%$

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and discard contaminated shoes.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

CAR BRITE® MAG WHEEL NA Non-
Acid Wheel Cleaner CBOOEL02-09

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

CAR BRITE® MAG WHEEL NA Non-
Acid Wheel Cleaner CBOOEL02-09**7. HANDLING AND STORAGE****Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines****ETHYLENE GLYCOL MONOBUTYL 111-76-2
ETHER**

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	5 ppm
NIOSH	Recommended exposure limit (REL):	24 mg/m3
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	240 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical

CAR BRITE® MAG WHEEL NA Non-
Acid Wheel Cleaner CBOOEL02-09

concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	dark green
Odour	fruity
Boiling point/range	212 °F / 100 °C @ 1,013.333333 hPa
pH	13
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	23.3333333 hPa @ 68 °F / 20 °C
Vapour density	No data
Density	1.03 g/cm3 8.6 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-	No data

CAR BRITE® MAG WHEEL NA Non-
Acid Wheel Cleaner CBOOEL02-09

octanol/water)

Autoignition temperature

No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with: strong oxidizing agents, strong reducing agents, This product should not be used in conjunction with trimethylol propane or trimethylol propane-derived products. There is a possibility that bicyclic phosphates or phosphites can be produced as a result of the thermal decomposition of this product in combination with trimethylol propane, trimethylol propane-derived products or their corresponding trimethylol propane alkane homologs. Bicyclic phosphates and phosphites are a class of materials with acute neurotoxic properties which produce characteristic convulsive seizures in test animals.

Hazardous Decomposition Products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

ETHYLENE GLYCOL MONOBUTYL ETHER LD 50 Guinea pig: 1,200 mg/kg

SURFACTANT LD 50 Rat: 1.4 g/kg

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 06/08/2007
Print Date: 6/14/2007
MSDS Number: R0406088
Version: 1.2

CAR BRITE® MAG WHEEL NA Non-Acid Wheel Cleaner CBOOEL02-09

Acute Inhalation Toxicity

ETHYLENE GLYCOL MONOBUTYL ETHER LC 50 Guinea pig: 633 ppm, 1 h

Acute Dermal Toxicity

ETHYLENE GLYCOL MONOBUTYL ETHER LD 50 Guinea pig: 2,000 mg/kg

SURFACTANT LD 50 Rabbit: 5 g/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE,) 8, III

IATA_P:

UN1719, Caustic alkali liquid, n.o.s. (POTASSIUM HYDROXIDE,) 8, III

IATA_C:

UN1719, Caustic alkali liquid, n.o.s. (POTASSIUM HYDROXIDE,) 8, III

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 06/08/2007
Print Date: 6/14/2007
MSDS Number: R0406088
Version: 1.2

CAR BRITE® MAG WHEEL NA Non-Acid Wheel Cleaner CBOOEL02-09

CFR_ROAD:

UN1719, Caustic alkali liquids, n.o.s. (POTASSIUM HYDROXIDE,) 8, III

CFR_RAIL:

UN1719, Caustic alkali liquids, n.o.s. (POTASSIUM HYDROXIDE,) 8, III

CFR_INWTR:

UN1719, Caustic alkali liquids, n.o.s. (POTASSIUM HYDROXIDE,) 8, III

IMDG_INWTR:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. 8, III

IMDG_ROAD:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. 8, III

IMDG_RAIL:

UN1719, CAUSTIC ALKALI LIQUID, N.O.S. 8, III

Dangerous goods descriptions (if indicated above) may not reflect package size, quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ARSENIC

SARA Hazard Classification Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

ETHYLENE GLYCOL	111-76-2	4.2075%
MONOBUTYL ETHER		

OSHA Hazards Moderate skin irritant
Severe eye irritant
Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	3	0	0	

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 06/08/2007
Print Date: 6/14/2007
MSDS Number: R0406088
Version: 1.2

CAR BRITE® MAG WHEEL NA Non-
Acid Wheel Cleaner CBOOEL02-09

NFPA 2 0 0

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).