

CG 1119/A1B

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 06/10/05

Date Printed: 11/23/05

MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: HD WHEEL CLEANER 55 GAL

SAP Material No: CROOE013F09

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206)782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
SODIUM HYDROXIDE	1310-73-2	2.8- 13.0
SODIUM GLUCOHEPTONATE	31138-65-5	0.0- 10.0
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	1.0- 6.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Material is corrosive to eyes. May cause burns.

Skin

Can cause skin burns and other permanent skin damage. The feeling of irritation or pain may not occur until several hours after the exposure. Additional symptoms of skin contact may include: hair loss, Passage of this material through the skin may be harmful.

Swallowing

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation, burns and tissue damage. Shock may occur.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful or fatal. May cause severe irritation and burns to the nose, throat, and respiratory tract. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficult breathing, blood in the urine, blood abnormalities (breakage of red blood cells), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, damage to the mouth, throat and/or airways, shock, coma, and death.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 06/10/05
Date Printed: 11/23/05
MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

Target Organ Effects

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention. Do not remove the victim from water access for transport to a medical facility unless instructed to do so by qualified medical personnel. If possible, continue flushing the eye gently with water while transporting the victim.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes.

Swallowing

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003
Date Prepared: 06/10/05
Date Printed: 11/23/05
MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

Note to Physicians

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidneys, blood-forming system.

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

No special fire hazards are known to be associated with this product.

Extinguishing Media

alcohol foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Not determined

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks).

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 06/10/05

Date Printed: 11/23/05

MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Under oxidation conditions, peroxides may be formed. If they become concentrated, these peroxides may present an explosion hazard. Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

SODIUM HYDROXIDE (1310-73-2)
OSHA VPEL 2.000 mg/m³ - Ceiling
ACGIH TLV 2.000 mg/m³ - Ceiling

SODIUM GLUCOHEPTONATE (31138-65-5)
No exposure limits established

ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2)
OSHA VPEL 25.000 ppm - TWA ((Skin))
ACGIH TLV 20.000 ppm - TWA

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 06/10/05
Date Printed: 11/23/05
MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for product) /A .0 (-17.7 C)

Vapor Pressure

(for product) .000

Specific Vapor Density

No data

Specific Gravity

1.100 @ 60.00 F

Liquid Density

9.180 lbs/gal @ 60.00 F
9.180 lbs/gal @ 60.00 F

Percent Volatiles (Including Water)

No data

Evaporation Rate

No data

Appearance

No data

State

LIQUID

Physical Form

No data

Color

BROWN

Odor

CHEMICAL/AMMONIA

pH

> 13.0

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 06/10/05
Date Printed: 11/23/05
MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

Incompatibility

Avoid contact with: aluminum, strong oxidizing agents, strong reducing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

CAUSTIC ALKALI LIQUIDS, NOS,8,UN1719,III

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

SODIUM HYDROXIDE

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

12821

SODIUM HYDROXIDE

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component

Component

SODIUM HYDROXIDE

1000

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007
Date Prepared: 06/10/05
Date Printed: 11/23/05
MSDS No: 525.0406011-001.001

HD WHEEL CLEANER 55 GAL

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate(X) Delayed(X) Fire() Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65
Section 313 Component(s) CAS Number

ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2

International Regulations
Inventory Status
Not determined

State and Local Regulations
California Proposition 65
None

New Jersey RTK Label Information
SODIUM HYDROXIDE 1310-73-2
2-BUTOXY ETHANOL 111-76-2

Pennsylvania RTK Label Information
SODIUM HYDROXIDE (NA(OH)) 1310-73-2
ETHANOL, 2-BUTOXY- 111-76-2

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.