

CG 1650-1655

ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Product name	CAR BRITE® REFLECT Satin Gloss Dressing
Product code	CBOOC033W05-S5
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid
WARNING! Flammable Liquid, Moderate skin irritant, Moderate eye irritant.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin Contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

Target Organs

No data

Carcinogenicity

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other Information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin. Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

ASHLAND

SAFETY DATA SHEET

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	>=70-<80%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO2), dry chemical

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Handling equipment must be properly grounded.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

ASHLAND

SAFETY DATA SHEET

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	No data
Odour	No data
Boiling point/range	No data

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

pH	No data
Flash point	72.0 °F / 22.2 °C
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	No data
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to Avoid

Incompatible Products
Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products
May form:, carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Hazardous Reactions
Product will not undergo hazardous polymerization.

Thermal Decomposition
No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

SOLVENT NAPHTHA (PETROLEUM), LD 50 Rat: 8,000 mg/kg
LIGHT ALIPHATIC

ASHLAND

SAFETY DATA SHEET

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

Acute Inhalation Toxicity

SOLVENT NAPHTHA (PETROLEUM), LC 50 Rat: 3400 ppm, 4 h
LIGHT ALIPHATIC

Acute Dermal Toxicity

SOLVENT NAPHTHA (PETROLEUM), LD 50 Rat: 4,000 mg/kg
LIGHT ALIPHATIC

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish
No data

Acute Toxicity to Aquatic Invertebrates
No data

Environmental Fate and Pathways
No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

14. TRANSPORT INFORMATION

IMDG:
UN1993, FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM
NAPHTHA,) 3, II
IATA_P:

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405742
Version: 1.

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA,) 3,
II

IATA_C:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA,) 3,
II

CFR_ROAD:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA,)
3, II

CFR_RAIL:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA,)
3, II

CFR_INWTR:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA,)
3, II

IMDG_INWTR:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, II

IMDG_ROAD:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, II

IMDG_RAIL:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, II

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

SARA Hazard Classification Fire Hazard
Acute Health Hazard

SARA 313 Component(s)

OSHA Hazards Flammable Liquid
Moderate skin irritant
Moderate eye irritant

ASHLAND

SAFETY DATA SHEET

Page: 9

Revision Date: 04/03/2007

Print Date: 4/24/2007

MSDS Number: R0405742

Version: 1.

CAR BRITE® REFLECT Satin Gloss
Dressing CBOOC033W05-S5

	Health	Flammability	Reactivity	Other
HMIS	1	3	0	
NFPA				No data

16. OTHER INFORMATION

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).