



Material Safety Data Sheet

HMIS Ratings
Health 2
Flammability 3
Reactivity 0
Protection X

1 Chemical Product and Company Identification

Manufacturer Information Car Brite, Inc.
1910 South State Avenue
Indianapolis, IN 46203

Phone (317) 788-9925

Emergency Phone CHEMTREC
1-800-424-9300
FOR INTERNATIONAL
CALLS
703-527-3887

Date Prepared 2001-Sep-27

Supersedes 2001-Sep-27

Product Identity WATER WAX

Product Code Number A002W

Product Use Automotive Reconditioning Product

Version # 1.0

CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT KAOLIN	64742-49-0	30 - 60		300 ppm		No
	66402-68-4	3 - 7				No
Non-hazardous and other ingredients below reportable levels	Proprietary	50	N/AP	N/AP		N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may cause irritation to the eyes. Symptoms include itching, burning, redness and tearing.

Inhalation This product may cause irritation to the respiratory system.

Ingestion Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements

FLAMMABLE

4 First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to non-contaminated air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice. Do not induce vomiting unless directed to do so by medical personnel.
Notes to Physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Alcohol foam. Carbon dioxide. Use methods for the surrounding fire.

General Fire Hazards

DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point 50 F

6 Accidental Release Measures

Containment Procedures

Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps.

Clean-Up Procedures

Eliminate ignition sources including sources of electrical, static or frictional sparks. Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Avoid prolonged or repeated skin contact with this material. Keep this product from heat, sparks, or open flame.

Storage Procedures

Keep the container tightly closed and in a cool, well-ventilated place. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good hygiene practices when handling this material, including changing and laundering work clothes after use. Discard contaminated shoes and leather goods. Eye wash fountain and emergency showers are recommended.

9 Physical & Chemical Properties

Boiling Point	> 212 F
Specific Gravity	0.84
Vapor Pressure	4
Evaporation Rate	Faster than water
Vapor Density	4
Solubility (H₂O)	Insoluble

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

US DOT HMR Information

Proper Shipping Name	Flammable liquids, n.o.s., (Petroleum Distillates)		
Identification Number	UN1993	Packaging Group	II
Hazard Class	3		

15 Regulatory Information

US Federal Regulations**CERCLA/SARA - Section 313 - Emission Reporting**

KAOLIN

16 Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By Technical Department**Issue Date** 27-Sep-2001