

CG 3054

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001
Date Prepared: 02/15/06
Date Printed: 06/02/06
MSDS No: 510.0362533-002.001

MAXGLOSS 5 GAL SQ

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: MAXGLOSS 5 GAL SQ

SAP Material No: CBOOC045G05-S5

General or Generic ID: PREMIUM AUTOMOTIVE DETAIL PRODUCT

Wesmar Products, Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
SILICONE EMULSIONS	63148-62-9	17.0- 27.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation.

Skin

Unlikely to cause skin irritation or injury.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects.

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea).

Target Organ Effects

No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 02/15/06
Date Printed: 06/02/06
MSDS No: 510.0362533-002.001

MAXGLOSS 5 GAL SQ

Other Health Effects

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

Primary Route(s) of Entry

Inhalation, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

No data

5. FIRE FIGHTING MEASURES

Flash Point

> 200.0 F (93.3 C) ESTIMATED

Explosive Limit

No data

Autoignition Temperature

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003
Date Prepared: 02/15/06
Date Printed: 06/02/06
MSDS No: 510.0362533-002.001

MAXGLOSS 5 GAL SQ

Hazardous Products of Combustion

May form: acrolein, carbon dioxide and carbon monoxide, formaldehyde, hydrogen silicates, silicon oxides, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. No special fire hazards are known to be associated with this product.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 0, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004
Date Prepared: 02/15/06
Date Printed: 06/02/06
MSDS No: 510.0362533-002.001

MAXGLOSS 5 GAL SQ

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

SILICONE EMULSIONS (63148-62-9)
No exposure limits established

Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) 340.0 F (171.1 C)

Vapor Pressure

(for component) 3.000 mmHg

Specific Vapor Density

No data

Specific Gravity

.980

Liquid Density

No data

Percent Volatiles (Including Water)

No data

Evaporation Rate

No data

Appearance

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 02/15/06
Date Printed: 06/02/06
MSDS No: 510.0362533-002.001

MAXGLOSS 5 GAL SQ

State

Physical Form

Color

Odor

pH 8.5 - 8.7

Viscosity 1825.0 - 1900.0 cps

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: acrolein, carbon dioxide and carbon monoxide, formaldehyde, hydrogen silicates, silicon oxides, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 02/15/06
Date Printed: 06/02/06
MSDS No: 510.0362533-002.001

MAXGLOSS 5 GAL SQ

Container/Mode:
CASES/SURFACE - NO EXCEPTIONS

NOS Component:
None

RQ (Reportable Quantity) - 49 CFR 172.101
Not applicable

15. REGULATORY INFORMATION

US Federal Regulations
CERCLA RQ - 40 CFR 302.4
None

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate(X) Delayed(X) Fire() Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65
None

International Regulations
Inventory Status
Not determined

State and Local Regulations
California Proposition 65
None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.