

CG 3072

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 07/21/05

Date Printed: 08/29/06

MSDS No: 525.0406015-001.001

## LOTION HAND CLNR 4/1 GAL

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

## Material Identity

Product Name: LOTION HAND CLNR 4/1 GAL

SAP Material No: CBOOE015-03

Wesmar Products Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

## Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient(s)           | CAS Number | % (by weight) |
|-------------------------|------------|---------------|
| DIETHANOLAMIDE          |            | 1.0- 11.0     |
| TRIETHANOLAMINE         | 102-71-6   | 1.0- 10.0     |
| SHINER                  |            | 1.0- 9.0      |
| SODIUM TRIPOLYPHOSPHATE | 7758-29-4  | 1.0- 7.0      |

## 3. HAZARDS IDENTIFICATION

## Potential Health Effects

## Eye

Can cause severe eye irritation and injure eye tissue.

## Skin

Can cause skin irritation. Prolonged or repeated contact may dry and crack the skin. Additional symptoms of skin contact may include: allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects), Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

## Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. Exposure causes severe irritation of the gastrointestinal tract.

## Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

## Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), low blood pressure, pain in the abdomen, effects on heart rate, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), coma.

Continued on next page

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002  
Date Prepared: 07/21/05  
Date Printed: 08/29/06  
MSDS No: 525.0406015-001.001

### LOTION HAND CLNR 4/1 GAL

---

#### Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: kidney damage, liver damage.

#### Developmental Information

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

#### Cancer Information

There was an increase in kidney tumors in male, but not female rats given triethanolamine by skin application for two years. When given in the drinking water, triethanolamine caused an increase in tumors in female mice in one study, but not in another. It had no effect on tumor incidence when given in the drinking water of rats. The relevance of these findings to humans is uncertain. Triethanolamine is not listed as carcinogenic by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

#### Other Health Effects

This product contains amines which may react with nitrites or other nitrosating agents to form nitrosamines. Certain nitrosamines have been shown to cause cancer in laboratory animals.

#### Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

---

### 4. FIRST AID MEASURES

#### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

#### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

#### Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

#### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

#### Note to Physicians

Excessive levels of phosphorus can cause low blood calcium, with tetany and convulsions. Preexisting disorders of the following organs ( or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions), liver, kidneys. Exposure to this material may aggravate any pre-existing condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

Continued on next page

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 07/21/05

Date Printed: 08/29/06

MSDS No: 525.0406015-001.001

LOTION HAND CLNR 4/1 GAL

---

### 5. FIRE FIGHTING MEASURES

#### Flash Point

Not applicable

#### Explosive Limit

No data

#### Autoignition Temperature

No data

#### Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, phosphorous oxides, sodium oxide various hydrocarbons.

#### Fire and Explosion Hazards

No special fire hazards are known to be associated with this product.

#### Extinguishing Media

alcohol foam, water fog, carbon dioxide, dry chemical.

#### Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

#### NFPA Rating

Not determined

---

### 6. ACCIDENTAL RELEASE MEASURES

#### Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

#### Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

---

### 7. HANDLING AND STORAGE

#### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer-causing nitrosamines could be formed. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact,

Continued on next page

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004  
Date Prepared: 07/21/05  
Date Printed: 08/29/06  
MSDS No: 525.0406015-001.001

### LOTION HAND CLNR 4/1 GAL

especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

#### Storage

Store in closed containers in a dry, well-ventilated area.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

#### Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Other protective equipment: eyewash station, emergency shower.

#### Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

#### Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

#### Exposure Guidelines

##### Component

-----

##### DIETHANOLAMIDE

No exposure limits established

##### TRIETHANOLAMINE (102-71-6)

ACGIH TLV 5.000 mg/m<sup>3</sup> - TWA

##### SHINER

No exposure limits established

##### SODIUM TRIPOLYPHOSPHATE (7758-29-4)

No exposure limits established

Continued on next page

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 07/21/05

Date Printed: 08/29/06

MSDS No: 525.0406015-001.001

LOTION HAND CLNR 4/1 GAL

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point**

(for product) A .0 (-17.7 C)

**Vapor Pressure**

(for product) .000

**Specific Vapor Density**

No data

**Specific Gravity**

1.091 @ 60.00 F

**Liquid Density**

9.100 lbs/gal @ 60.00 F

9.100 lbs/gal @ 60.00 F

**Percent Volatiles (Including Water)**

No data

**Evaporation Rate**

No data

**Appearance**

No data

**State**

LIQUID

**Physical Form**

No data

**Color**

PINK

**Odor**

SWEET PEA

**pH**

No data

---

### 10. STABILITY AND REACTIVITY

**Hazardous Polymerization**

Product will not undergo hazardous polymerization.

**Hazardous Decomposition**

May form: carbon dioxide and carbon monoxide, phosphorous oxides, sodium oxide various hydrocarbons.

**Chemical Stability**

Stable.

Continued on next page

# MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 07/21/05

Date Printed: 08/29/06

MSDS No: 525.0406015-001.001

LOTION HAND CLNR 4/1 GAL

## Incompatibility

Avoid contact with: acids, aldehydes, halogenated hydrocarbons, reactive metals such as aluminum and magnesium, strong alkalis, strong oxidizing agents strong reducing agents.

## 11. TOXICOLOGICAL INFORMATION

No data

## 12. ECOLOGICAL INFORMATION

No data

## 13. DISPOSAL CONSIDERATION

### Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

## 14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

## 15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component

Component

PENTASODIUM TRIPHOSPHATE

5000

Continued on next page

# MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 07/21/05

Date Printed: 08/29/06

MSDS No: 525.0406015-001.001

LOTION HAND CLNR 4/1 GAL

---

**SARA 302 Components - 40 CFR 355 Appendix A**

None

**Section 311/312 Hazard Class - 40 CFR 370.2**

Immediate(X) Delayed(X) Fire( ) Reactive( ) Sudden Release of Pressure( )

**SARA 313 Components - 40 CFR 372.65**

None

**International Regulations**

**Inventory Status**

Not determined

**State and Local Regulations**

**California Proposition 65**

None

**New Jersey RTK Label Information**

SODIUM PHOSPHATE, TRIBASIC

7758-29-4

**Pennsylvania RTK Label Information**

ETHANOL, 2,2',2''-NITRILOTRIS-  
TRIPHOSPHORIC ACID, PENTASODIUM SALT

102-71-6

7758-29-4

---

## 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.