

CG 4010

ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number 1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® CAROLINA HIGH GLOSS High Gloss Dressing
Product code	CBOOC004T05-S5
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, fruity, white

WARNING! Moderate skin irritant, Severe eye irritant.

Potential Health Effects

Routes of Exposure

No data

Eye Contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin Contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

ASHLAND

SAFETY DATA SHEET

Page: 2

Revision Date: 04/03/2007

Print Date: 6/15/2007

MSDS Number: R0405711

Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, difficult breathing, lung damage

Target Organs

Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects

Carcinogenicity

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other Information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
GLYCERINE	56-81-5	>=1.5-<5%
SURFACTANT	NJTS# 254504001- 5216	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Precautions for Fire-Fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental Precautions

No data

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Flush area with water. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Ethylene oxide may accumulate in the headspace of shipping and storage containers and in enclosed areas where the product is

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

being handled or used. Ethylene oxide is listed as carcinogenic by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

No data

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

GLYCERINE		56-81-5	
ACGIH	time weighted average	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). This product may contain small amounts of ethylene oxide which could potentially accumulate in the headspace of shipping and storage containers and in enclosed areas where the product is being handled or used. Provide adequate ventilation to control exposures to within the OSHA permissible exposure limits of 1 ppm (TWA) and 5 ppm (STEL).

Eye Protection

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	white
Odour	fruity
Boiling point/range	No data
pH	No data
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	1.01 g/cm ³ 8.41 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with: strong oxidizing agents

Hazardous Decomposition Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

GLYCERINE	LD 50 Rat: 12,600 mg/kg
SURFACTANT	LD 50 Rat: 3,000 mg/kg

Acute Inhalation Toxicity

GLYCERINE	LC 50 Rat: 570 mg/m3, 1 h
-----------	---------------------------

Acute Dermal Toxicity

GLYCERINE	LD 50 Rabbit: 10 g/kg
SURFACTANT	LD 50 Rabbit: 2,830 mg/kg

12. ECOLOGICAL INFORMATION

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

FORMALDEHYDE

1,4-DIOXANE

ETHYLENE OXIDE

ACETALDEHYDE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

ETHYLENE OXIDE

SARA Hazard Classification Acute Health Hazard

ASHLAND
SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 6/15/2007
MSDS Number: R0405711
Version: 1.

CAR BRITE® CAROLINA HIGH
GLOSS High Gloss Dressing
CBOOC004T05-S5

SARA 313 Component(s)

OSHA Hazards

Moderate skin irritant
Severe eye irritant

	Health	Flammability	Reactivity	Other
HMIS	2	0	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).