

CQ 1103



Material Safety Data Sheet

HMIS Ratings
Health 1
Flammability 3
Reactivity 0
Protection X

1 Chemical Product and Company Identification

Manufacturer Information

Wesmar Products, Inc.
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Phone

Emergency Phone

1-800-424-9300
FOR INTERNATIONAL
CALLS
703-527-3887

Date Prepared

2003-Jun-13

Product Identity

TURBO

Product Code Number

A093

Product Use

Automotive Reconditioning Products

Version

1.0

CAS

Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	10 - 30		300 ppm		No
NAPHTHA, PETROLEUM, LIGHT ALKYLATE	64741-66-8	10 - 30				No
POLYSILOXANE COMPOUND	Mixture	1 - 5				No
Non-hazardous and other ingredients below reportable levels	Proprietary	57	N/AP	N/AP		N/AP

3 Hazards Identification

Potential Health Effects

Skin

Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes

This product may cause irritation to the eyes.

Inhalation

This product may cause irritation to the respiratory system.

Ingestion

Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements

FLAMMABLE

4 First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. Immediately take off all contaminated clothing. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.
Notes to Physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Carbon dioxide. Alcohol foam.

General Fire Hazards

Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point	40 - 45 F TCC
Flammability Limits in Air, Lower, % by Volume	N/AV
Flammability Limits in Air, Upper, % by Volume	N/AV

6 Accidental Release Measures

Containment Procedures

Eliminate sources of ignition. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Keep this product from heat, sparks, or open flame. Avoid prolonged or repeated skin contact with this material.

Storage Procedures

Keep the container tightly closed. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit (48°C). Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Eye wash fountain and emergency showers are recommended. Use good industrial hygiene practices in handling this material.

9 Physical & Chemical Properties

Boiling Point	> 212 F
Specific Gravity	0.907
Vapor Pressure	< 20 mm/Hg
Evaporation Rate	Faster than water
Vapor Density	> 1
Solubility (H2O)	Insoluble
Freezing Point	32 F

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

General

This product is not regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

US DOT HMR Information

Proper Shipping Name	Flammable liquids, n.o.s. (Petroleum Distillates)		
Identification Number	UN1993	Packaging Group	II
Hazard Class	3		

15 Regulatory Information

16 Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By	Technical Department
Issue Date	13-Jun-2003