

CQ 4004 Black Pearl #4

ASHLAND
SAFETY DATA SHEET

Page: 1

Revision Date: 04/03/2007

Print Date: 4/24/2007

MSDS Number: R0405379

Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® BLACK PEARL PREMIUM POLISH VOC Compliant Body Shop-Safe
Product code	CBOOBP04-02
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, fruity, light grey

WARNING! Combustible Liquid, Highly toxic by inhalation, Moderate skin irritant, Severe eye irritant.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin Contact

Can cause severe skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: skin blistering. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, loss of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), convulsions, coma, and death

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

Reproductive Hazard

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

Other Information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin. Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ALIPHATIC HYDROCARBON	NJTS# 254504001- 5164	>=10-<15%
MINERAL SPIRITS REGULAR (BASE DATA)	8052-41-3	>=5-<10%
ALUMINUM OXIDE (AL ₂ O ₃)	1344-28-1	>=1.5-<5%
ALUMINUM SILICATE CALCINED	66402-68-4	>=1.5-<5%
QUATERNARY AMMONIUM MONTMORILLONITE	68953-58-2	>=1.5-<5%
TALL OIL FATTY ACIDS	68155-20-4	>=1.5-<5%
DIETHANOLAMIDES ISOPROPANOL	67-63-0	>=1-<1.5%

4. FIRST AID MEASURES

Eyes

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Precautions for Fire-Fighting

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Flammability Class for Flammable Liquids Combustible Liquid Class II

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

MINERAL SPIRITS REGULAR (BASE 8052-41-3

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

DATA)

ACGIH	time weighted average	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	2,900 mg/m3
OSHA Z1A	time weighted average	100 ppm
OSHA Z1A	time weighted average	525 mg/m3
US CA OEL	Time Weighted Average (TWA)	100 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	525 mg/m3
	Permissible Exposure Limit (PEL):	

ALUMINUM OXIDE (AL2O3)

1344-28-1

ACGIH	time weighted average	10 mg/m3	
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	10 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		

ISOPROPANOL

67-63-0

ACGIH	time weighted average	200 ppm
ACGIH	Short term exposure limit	400 ppm
NIOSH	Recommended exposure limit (REL):	400 ppm
NIOSH	Recommended exposure limit (REL):	980 mg/m3
NIOSH	Short term exposure limit	500 ppm
NIOSH	Short term exposure limit	1,225 mg/m3
OSHA Z1	Permissible exposure limit	400 ppm
OSHA Z1	Permissible exposure limit	980 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	light grey
Odour	fruity
Boiling point/range	No data
pH	8
Flash point	104 °F / 40 °C
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	1.00 g/cm ³ 8.33 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

Autoignition temperature

No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

ALIPHATIC HYDROCARBON	LD 50 Rat: 8,000 mg/kg
MINERAL SPIRITS REGULAR (BASE DATA)	LD 50 Rat: 5 g/kg
QUATERNARY AMMONIUM MONTMORILLONITE	LD 50 Rat: 8 g/kg
ISOPROPANOL	LD 50 Rat: 5,045 mg/kg

Acute Inhalation Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

ALIPHATIC HYDROCARBON LD 50 Rat: 2500 ppm, 4 h

ISOPROPANOL LC 50 Rat: 16000 ppm, 4 h

Acute Dermal Toxicity

ALIPHATIC HYDROCARBON LD 50 Rabbit: 4,000 mg/kg

MINERAL SPIRITS REGULAR (BASE DATA) LD 50 Rabbit: 3 g/kg

ISOPROPANOL LD 50 Rabbit: 5,030 - 7,900 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_P:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_C:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_ROAD:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_RAIL:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_INWTR:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IMDG_INWTR:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_ROAD:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_RAIL:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ETHYL BENZENE
QUARTZ / SAND

ASHLAND

SAFETY DATA SHEET

Page: 11
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405379
Version: 1.

CAR BRITE® BLACK PEARL
PREMIUM POLISH VOC Compliant
Body Shop-Safe CBOOBP04-02

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

TOLUENE

BENZENE

SARA Hazard Classification Fire Hazard
Acute Health Hazard

SARA 313 Component(s)

OSHA Hazards Combustible Liquid
Highly toxic by inhalation
Moderate skin irritant
Severe eye irritant

	Health	Flammability	Reactivity	Other
HMIS	2	3	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).