

CW 3011-3031-3041-3051
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® KWIET KOTE #81520 321 H7-K5-10 Undercoating
Product code	CBOOK035-31
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid
WARNING! Combustible Liquid, Highly toxic by inhalation, Moderate skin irritant, Moderate eye irritant, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin Contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include: abnormal coloring of the skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing aerosol and/or mist is possible when material is sprayed. Aerosol and mist may present a greater risk of injury because more material may be present in the air than from vapor alone. Breathing of dust, vapor, and/or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, loss of appetite

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: respiratory tract damage (nose, throat, and airways)

Carcinogenicity

Asphalt is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Extracts from certain types of asphalt and some undiluted asphalts have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. The relevance of this to humans with exposure to hot asphalt fume is uncertain.

Reproductive Hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ASPHALT	8052-42-4	>=30-<40%
ATTAPULGITE	12174-11-7	>=30-<40%
MINERAL SPIRITS REGULAR (BASE DATA)	8052-41-3	>=30-<40%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Flammability Class for Flammable Liquids

Combustible Liquid Class II

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Scoop or scrape up. Put in container for recovery or disposal.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

ASPHALT		8052-42-4	
ACGIH	time weighted average	0.5 mg/m3	Inhalable fraction.
NIOSH	Ceiling Limit Value and Time	5 mg/m3	Fume.
	Period (if specified):		
MINERAL SPIRITS REGULAR (BASE DATA)		8052-41-3	
ACGIH	time weighted average	100 ppm	
NIOSH	Recommended exposure limit	350 mg/m3	
	(REL):		
NIOSH	Ceiling Limit Value and Time	1,800 mg/m3	
	Period (if specified):		
OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,900 mg/m3	
OSHA Z1A	time weighted average	100 ppm	
OSHA Z1A	time weighted average	525 mg/m3	
US CA OEL	Time Weighted Average (TWA)	100 ppm	
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	525 mg/m3	
	Permissible Exposure Limit (PEL):		

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	No data
Odour	No data
Boiling point/range	315.00 °F / 157.22 °C
pH	No data
Flash point	104.9 °F / 40.5 °C
Evaporation rate	No data
Explosion limits	1 %(V) 6 %(V)
Vapour pressure	35 hPa @ 77 °F / 25 °C
Vapour density	No data
Density	1.3768 g/cm3 @ 68 °F / 20 °C
	No data
Solubility	insoluble in water
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, strong oxidizing agents, strong reducing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

MINERAL SPIRITS REGULAR (BASE DATA) LD 50 Rat: 5 g/kg

Acute Inhalation Toxicity

Acute Dermal Toxicity

MINERAL SPIRITS REGULAR (BASE DATA) LD 50 Rabbit: 3 g/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_P:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_C:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_ROAD:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_RAIL:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_INWTR:

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,
) 3, III

IMDG_INWTR:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_ROAD:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_RAIL:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ASPHALT
ATTAPULGITE

SARA Hazard Classification Fire Hazard
 Acute Health Hazard
 Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards Combustible Liquid
 Highly toxic by inhalation
 Moderate skin irritant
 Moderate eye irritant
 Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	1	2		
NFPA	1	2	0	

16. OTHER INFORMATION

ASHLAND
SAFETY DATA SHEET

Page: 10
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0407700
Version: 1.

CAR BRITE® KWIET KOTE #81520
321 H7-K5-10 Undercoating
CBOOK035-31

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).