

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® FABRIC GUARD Fabric Protectant
Product code	CBOOK015-03
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, white

Moderate eye irritant.

Potential Health Effects

Routes of Exposure

Inhalation, Skin contact, Eye Contact, Ingestion

Eye Contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin Contact

Unlikely to cause skin irritation or injury.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. This product may give off a fine particulate fume when heated above 300 degrees C. Smoking cigarettes or tobacco contaminated with polymer dust may give off this fume. Inhalation of polymer fumes may cause "polymer fume fever", a

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406261
Version: 1.

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

flu-like illness with fever, chills, nausea, shortness of breath, chest tightness, muscle or joint ache, and sometimes cough. The symptoms may not occur until several hours after exposure and are generally temporary, lasting 24-48 hours, even without treatment.

Aggravated Medical Condition

No data

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

There is no information available. The chance of this material causing cancer is unknown. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	88917-22-0	>=5-<10%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406261
Version: 1.

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

Give individual two glasses of milk or water to drink. If symptoms develop, seek medical attention.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: No information available.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use an extinguishing media appropriate for surrounding fire.

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, carbonyl fluoride, hydrogen fluoride, various hydrocarbons

Precautions for Fire-Fighting

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Spills of this material are very slippery.

Environmental Precautions

No data

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Flush area with water. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. This material is slippery when wet. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. **Warning.** Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area. Keep from freezing. Store at temperatures between 40 degrees F (5 degrees C) and 90 degrees F (30 degrees C) to maintain stability of the product.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below level of overexposure (from known, suspected or apparent adverse effects).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product.

Respiratory Protection

If needed, use a NIOSH-approved respirator suitable for the potential exposure level.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	white
Odour	No data
Boiling point/range	212 °F / 100 °C @ 1,013.333333 hPa
pH	5
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	23.3333333 hPa @ 68 °F / 20 °C
Vapour density	No data
Density	1.01 g/cm ³ 8.41 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

ASHLAND

SAFETY DATA SHEET

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406261
Version: 1.

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, alkalis, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, carbonyl fluoride, hydrogen fluoride, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

DIPROPYLENE GLYCOL
MONOMETHYL ETHER ACETATE

LD 50 Rat: 5,000 mg/kg

Acute Inhalation Toxicity

Acute Dermal Toxicity

DIPROPYLENE GLYCOL
MONOMETHYL ETHER ACETATE

LD 50 Rabbit: 5,000 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406261
Version: 1.

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0406261
Version: 1.

CAR BRITE® FABRIC GUARD
Fabric Protectant CBOOK015-03

OSHA Hazards

Moderate eye irritant

	Health	Flammability	Reactivity	Other
HMIS	1	0	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).