

1 Identification of the substance/preparation and of the company/undertaking

- Product details
- Trade name: **2K-Löser**
- Application of the substance / the preparation Thinner, Diluent
- Manufacturer/Supplier:
Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

DE 0515.5000

2 Composition/information on ingredients

- Chemical characterization
- Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 108-94-1 EINECS: 203-631-1	cyclohexanone	 Xn; R 10-20	25-50%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate	 Xi; R 10-36	25-50%
CAS: 112-07-2 EINECS: 203-933-3	2-butoxyethyl acetate	 Xn; R 20/21	2.5-10%
CAS: 67-64-1 EINECS: 200-662-2	acetone	 Xi,  F; R 11-36-66-67	2.5-10%

- Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

Hazard description:



Xn Harmful

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 20/21 Harmful by inhalation and in contact with skin.

R 36 Irritating to eyes.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 29.11.2005

(Contd. of page 1)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

108-94-1 cyclohexanone (25-50%)

WEL	Short-term value: 20 ppm
	Long-term value: 10 ppm

108-65-6 2-methoxy-1-methylethyl acetate (25-50%)

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm

112-07-2 2-butoxyethyl acetate (2.5-10%)

WEL	Short-term value: 50 ppm
	Long-term value: 20 ppm

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

(Contd. of page 2)

67-64-1 acetone (2.5-10%)

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
 - Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55°C

· **Flash point:** 59°C

· **Ignition temperature:** 280.0°C

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

(Contd. of page 3)

· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20°C:	233.0 hPa
· Density at 20°C:	0.935 g/cm³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Kinematic at 20°C:	15 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	100.00 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

108-94-1 cyclohexanone

Oral	LD50	1535 mg/kg (rat)
Dermal	LD50	948 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Irritant

12 Ecological information

- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

GB

(Contd. on page 5)

Material Safety Data Sheet
According to 91/155 EEC

(Contd. of page 4)

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**


14 06 03 other solvents and solvent mixtures

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 3 (F1) Flammable liquids.

· **Danger code (Kemler):** 30


· **UN-Number:** 1263

· **Packaging group:** III

· **Hazard label:** 3

· **Description of goods:** 1263 PAINT RELATED MATERIAL, special provision 640E

· **Maritime transport IMDG:**



· **IMDG Class:** 3

· **UN Number:** 1263

· **Label** 3


· **Packaging group:** III

· **EMS Number:** F-E,S-E

· **Marine pollutant:** No

· **Proper shipping name:** PAINT RELATED MATERIAL

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3

· **UN/ID Number:** 1263

· **Label** 3

· **Packaging group:** III

· **Proper shipping name:** PAINT RELATED MATERIAL

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 6)

Material Safety Data Sheet
According to 91/155 EEC

(Contd. of page 5)

· **Code letter and hazard designation of product:**

Xn Harmful

· **Hazard-determining components of labelling:**

cyclohexanone

· **Risk phrases:**

20/21 Harmful by inhalation and in contact with skin.

36 Irritating to eyes.

· **Safety phrases:**

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

13 Keep away from food, drink and animal feedingstuffs.

16 Keep away from sources of ignition - No smoking.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

· **National regulations:**

· **Information about limitation of use:**

108-94-1 cyclohexanone

3

Class	Share in %
NK	100.0

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.

11 Highly flammable.

20 Harmful by inhalation.

20/21 Harmful by inhalation and in contact with skin.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** MIPA AG, Abteilung Umweltschutz

· **Contact:** Dr. Philip Betten

GB