

**5170 Seam Sealer**

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

Name, full adress and tel. of Company:

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2. HAZARDS IDENTIFICATION OF THE PREPERATION.

• Hazard description:

Xn Harmful
F Highly flammable
N Dangerous for the environment

• Information concerning particular hazards for human and environment:

R 11 Highly flammable.
R 18 In use, may form flammable/explosive vapour-air mixture.
R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R 65 Harmful: may cause lung damage if swallowed.
R 67 Vapours may cause drowsiness and dizziness.

• Classification system:

The classification is according to the latest editions of the EU-lists,
and extended by company and literature data.

4. FIRST AID MEASURES.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist,
consult a doctor.

• After swallowing:

Do not induce vomiting; call for medical help immediately.

• Information for doctor:

• The following symptoms may occur:

Headache
Dizziness
Dizziness

Material Safety Data Sheet

According to 91/155 EEC

Date: 08.06.04

Revision Date: 01.06.04

5. FIRE-FIGHTING MEASURES.

- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - For safety reasons unsuitable extinguishing agents:
Water with full jet
 - Special hazards caused by the substance, its products of combustion or resulting gases:
Can form explosive gas-air mixtures.
 - Protective equipment:
Mount respiratory protective device.
 - Additional information Cool endangered receptacles with water spray.
-

6. ACCIDENTAL RELEASE MEASURES.

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
 - Measures for environmental protection:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
 - Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
-

7. HANDLING AND STORAGE.

- Information for safe handling:
Use only in well ventilated areas.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
 - Storage:
Requirements to be met by storerooms and receptacles: Store in a cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
 - Class according to regulation on flammable liquids: A I
-

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Additional information about design of technical facilities: No further data; see item Ingredients with limit values that require monitoring at the workplace: 1330-20-7 xylene (mix) OES Short-term value: 440 mg/m³, 100 ppm
Long-term value: 441 mg/m³, 100 ppm Sk
- Additional information: The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:
- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Material Safety Data Sheet

According to 91/155 EEC

Date: 08.06.04

Revision Date: 01.06.04

• Product:

• Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• European waste catalogue

08 00 00

08 01 11

15 01 10

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
waste paint and varnish containing organic solvents or other dangerous substances
packaging containing residues of or contaminated by dangerous substances

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations .

Land transport ADR/RID (cross-border)

Material Safety Data Sheet
According to 91/155 EEC

Date: 08.06.04

Revision Date: 01.06.04

14. PHYSIKAL AND CHEMICAL

(Contd. of page 5) · Hazard label

· Description of goods: 4.1

1133 COATING SOLUTION · Maritime transport IMDG: · IMDG Class: 3

· UN Number: 1133

· Label

· Packaging group: II

· EMS Number: F-A, S-1

· Marine pollutant: 4.1

No · Proper shipping name: COATING SOLUTION ·

Air transport ICAO-TI and IATA - DGR: ·

ICAO/IATA Class: 3 · UN/ID Number: 1133

· Label

· Packaging group: II

II · Proper shipping name: COATING SOLUTION 15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

· Risk phrases:

11 Highly flammable.

18 In use, may form flammable/explosive vapour-air mixture.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking. 23 Do not breathe fumes.

24/25 Avoid contact with skin and eyes.

15. REGULATORY INFORMATION.

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

· Risk phrases:

11 Highly flammable.

18 In use, may form flammable/explosive vapour-air mixture.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking. 23 Do not breathe fumes.

24/25 Avoid contact with skin and eyes.

16. GLOBAL INFORMATION.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R -phrases

10 Flammable.

11 Highly flammable.

20 Harmful by inhalation.

20/21 Harmful by inhalation and in contact with skin.

36 Irritating to eyes. 38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.