



5400 Stone Chip Protection Spray - grey 500ml

1 Identification of the substance/preparation and of the company/undertaking

- Product details
- Trade name: 5400
- Article number: 6.5400.0501
- Application of the substance / the preparation Surface protection
- Manufacturer/Supplier:
Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2 Composition/information on ingredients

- Chemical characterization
- Description: Active substance with propellant

Dangerous components:

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light	Xn, F, N; R 11-38-51/53-65-67	25-50%
CAS: 74-98-6 EINECS: 200-827-9	propane	F+; R 12	10-25%
CAS: 78-93-3 EINECS: 201-159-0	butanone	Xi, F; R 11-36-66-67	10-25%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol	R 10	2.5-10%
CAS: 108-88-3 EINECS: 203-625-9	toluene	Xn, F; R 11-20	1.0-2.5%

- Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

Hazard description:



Xi Irritant
F+ Extremely flammable
N Dangerous for the environment

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Material Safety Data Sheet

According to 91/155 EEC

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
 - Water haze
 - Fire-extinguishing powder
 - Carbon dioxide
 - Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:** Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Do not seal receptacle gas tight.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.

GB

Material Safety Data Sheet

According to 91/155 EEC

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

74-98-6 propane

OES Long-term value: 1800 mg/m³, 1000 ppm
Asphyxiant

78-93-3 butanone

OES Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
IOELV, Sk, Bmgv

107-98-2 1-methoxy-2-propanol

OES Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
New, IOELV, Sk

108-88-3 toluene

OES Short-term value: 574 mg/m³, 150 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

GB

Material Safety Data Sheet

According to 91/155 EEC

· **Body protection:** Use protective suit.

9 Physical and chemical properties

· General Information

Form: Aerosol
Colour: According to product specification
Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44°C

· **Flash point:** -97°C

· **Ignition temperature:** 200.0°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.8 Vol %
Upper: 11.5 Vol %

· **Vapour pressure at 20°C:** 4 Bar

· **Density at 20°C:** 0.805 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Solvent content:

Organic solvents: 73.0 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

78-93-3 butanone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rbt)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rab)
Inhalative	LC50/4 h	5320 mg/l (mus)

· Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

Material Safety Data Sheet

According to 91/155 EEC

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

Ecotoxicological effects:

• **Remark:** Toxic for fish

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

Product:

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 02 99 wastes not otherwise specified

Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

Land transport ADR/RID (cross-border)

• **ADR/RID class:** 2 5F Gases.

• **Danger code (Kemler):** 23

• **UN-Number:** 1950

• **Packaging group:** -

• **Hazard label** 2.1

• **Description of goods:** 1950 AEROSOLS

Maritime transport IMDG:

• **IMDG Class:** 2.1

• **UN Number:** 1950

• **Label** 2.1

• **Packaging group:** -

• **EMS Number:** F-D,S-U

• **Marine pollutant:** No

• **Proper shipping name:** AEROSOLS

Air transport ICAO-TI and IATA-DGR:

• **ICAO/IATA Class:** 2.1

• **UN/ID Number:** 1950

• **Label** 2.1

• **Packaging group:** -

• **Proper shipping name:** AEROSOLS, flammable, n.o.s

Material Safety Data Sheet

According to 91/155 EEC

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant
F+ Extremely flammable
N Dangerous for the environment

· **Risk phrases:**

- 12 Extremely flammable.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 2 Keep out of the reach of children.
- 23 Do not breathe aerosol.
- 24 Avoid contact with skin.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	50-100

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **VOC-CH** 73.00 %

· **VOC-EU** 587.7 g/l

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20 Harmful by inhalation.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development