

**7416 Aluminium Spray**

Date: 28.07.04

Revision Date: 24.03.04

page/1/6

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

DE 7416.0400

Name, full adress and tel. of Company:

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC.

EINECS-Nr CAS-No.	Names R-phrases	Symb.	Conc. %
215-535-7 1330-20-7	xylene, mixture of isomers 10-20/21-38	Xn	10 - 12.5
200-662-2 67-64-1	acetone 11-36-66-67	Xi, F	25 - 50
204-658-1 123-86-4	n-butyl acetate 10-66-67		1 - 2.5
203-603-9 108-65-6	2-methox 1-methylethyl acetate 10-36	Xi	2.5 - 10
200-827-9 74-98-6	propane 12	F+	12.5 - 20
211_-948-7 112'-37-8	butane 12	F+	12.5 - 20
265-150-3 64742-48-9	Naphtha (pet.roleum),hydrotreated heavy; low boiling point. 10-65-66	Xn	1 - 2.5
265-199-0 64742-95-6	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha unspecified 10-37-51/53-65-66-67	Xn, N	1 - 2.5

Extra notices:

(See full text of R phrases under chapter 16)

3. HAZARDS IDENTIFICATION OF THE PREPERATION.

	Xi	irritant
	F+	extremely flammable
12		Extremely flammable.
36		Irritating to eyes.
66		Repeated exposure may cause skin dryness or cracking.
67		Vapours may cause drowsiness and dizziness.

4 FIRST AID MEASURES.

General.

In all causes of doubt, or when symptoms persist, seek medical attention.

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/2/6

Inhalation

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES.

Extinguishing media : recommended : alcohol resistant foam, CO₂, powders, waterspray not to be used : waterjet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.
Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE hEA:"UEES.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE.

Handling.

Vapours are heavier than air and may spread along floors. Vapours may form Explosive mixtures with air.

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8.

Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/3/6

Storage.

Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act. Observe label precaution. Storage: protected against frost on a dry, well ventilated place away from sources of heat and direct sunlight.

Keep away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

Engineering Measures.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and

Occupational exposure limit for

EINECS-No	Names	STL mg/m3	LTL mg/m3
215-535-7	xylene mixture of isomers	150	100 ppm
200-662-2	acetone	1500	750 ppm
204-658-1	n-butyl acetate	200	150 ppm
203-603-9	2-methoxy-1-methylethyl acetate	100	50 ppm
200-827-9	propane	MAK	1000 ppm
203-448-7	butane	750	600 ppm
265-199-0	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha unspecified	MAK	50 ppm

Personal Protection:

Respiratory protection.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection.

For prolonged or repeated contact, use

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection.

Use safety eyewear designed to protect against splash of liquids.

Skin protection.

Personel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9 PHYSICAL AND CHEMICAL PROPERTIES.

Physical form	aerosol	Methode
color	see trade name	
odor	charakteristisch	
flash point	n. a.	°C
viscosity density	at 20	°C
solvent content	89	%
vapour pressure	> 4.2 bar	mbar
ignition temperature	200	°C
boiling point	42	°C
solid weight	11.50	%
solid volume	11.50	1/100 kg
lower explosion limit:	2.3	Vol.%

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/4/6

upper explosion limit: 13.0 Vol. %
solubility in water : partly miscible

10. STABILITY AND REACTIVITY.

Stabile under recommended storage and handling conditions. (See section 7) When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION.

There are no data available on the preparation itself.

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Remark: The product has not been tested as such, but is categorised by means of conventional method. (EC-Guidelines 1999/45/EC)

12. ECOLOGICAL INFORMATION.

The product should not be allowed to enter drains or water courses.

The preparation itself is labelled in accordance with the conventional dangerous preparations directive (1999/45/EG) as not dangerous for the environment.

13. DISPOSAL CONSIDERATIONS.

080111 waste paint and varnish containing organic solvents or other dangerous substances Do not allow into drains or water courses.

Empty containers are to be deposited according to the official rules.

14. TRANSPORT INFORMATION.

Road/rail-transportation

ADR/RID 2

UN-Nr.: 1950

Transport document: Aerosols, flammable
(Dampfdruck bei 50 °C höchstens 100 kPa)

contains:

Packaging group: n.a.

Sea transport

IMDG/Class: 2.1

EMS-Nr.: 3-07

UN-Nr.: 1950

Proper shipping name: AEROSOLS

contains: /

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/5/6

ICAO/IATA Class: 2.1 UN Nr.: 1950

Proper shipping name: Aerosols, flammable

Packaging group : n.a.

15. REGULARY INFORMATION.

The requirements of the Classification Packaging and Labelling of Dangerous Substances Regulations. (EC Guidelines 1999/45/EC)

The product is labelled as follows

Xi	irritant
F+	extremely flammable

Danger classification

n.a.

contains:

R phrases:

12	Extremely flammable.
36	Irritating to eyes.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

S phrases:

16	Keep away from sources of ignition - No smoking.
9	Keep container in a well-ventilated place.
25	Avoid contact with eyes.
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
29/56	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
33	Take precautionary measures against static discharges.
43	In case of fire, use...
46	If swallowed, seek medical advice immediately and show this container or label.
51	Use only in well-ventilated areas.

P phrases:

n.a.

Water hazard class: 2

VOC (g/l) DIN ISO 11890: 623.359

16. OTHER INFORMATION.

Full text of R phrases with no appearing in section 2

10	Flammable.
20/21	Harmful by inhalation and in contact with skin.
38	Irritating to skin.
11	Highly flammable.
36	Irritating to eyes.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.
12	Extremely flammable.
65	Harmful: may cause lung damage if swallowed.
37	Irritating to respiratory system.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/6/6

The information of this MSDS is based on the present state of our knowledge and on current EEC and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.