



Date: 28.07.04

Revision Date: 24.03.04

page/1/6

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

Name, full address and tel. of Company:

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

DE 7425.0401,0402

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous
Substances Directive 67/548/EC.

EINECS-Nr	Names	Symb.	Conc. %
CAS-No.	R-phrases		
215-535-7	xylene, mixture of isomers		
1330-20-7	10-20/21-38	Xn	20 - 25
200-751-6	butan-1-ol		
71-36-3	10-22-37/38-41-67	Xn	1 - 2.5
200-662-2	acetone		
67-64-1	11-36-66-67	Xi,F	25 - 50
200-827-9	propane		
74-98-6 12		F+	2.5 - 10
213-448-7	butane		
107-8	12	F+	12.5 - 20
265-150-3	Naphtha (petroleum), hydrotreated heavy; low boiling point		
64742-48-9	10-65-66	Xn	1 - 2.5

Extra notices:

(See full text of R phrases under chapter 16)

3. HAZARDS IDENTIFICATION OF THE PREPERATION.

Xn	harmful
	extremely flammable
12	extremely flammable
20/21	Harmful by inhalation and in contact with skin.
36/38	Irritating to eyes and skin.

4. FIRST AID MEASURES.

General.

In all causes of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person. Inhalation

Remove or fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice. Eye

contact:

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/2/6

Skin contact .

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES.

Extinguishing media : recommended : alcohol resistant foam, CO₂, powders, waterspray not to be used : waterlet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.
Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents.

If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE.

Handling.

Vapours are heavier than air and may spread along floors. Vapours may form Explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8.

Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/3/6

Storage.

Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act.

Observe label precaution. Storage: protected against frost on a dry, well sources of heat and direct sunlight

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

Engineering Measures.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Exposure Limits.

Occupational exposure limit for:

EINECS-No.	Names	STL mg/m3	LTL mg/m3
215-535-7	xylene, mixture of isomers	150	100 ppm
200-751-6	butan-1-ol	50	0 ppm
200-662-2	acetone	1500	750 ppm
200-827-9	propane	MAK	1000 ppm
203-448-7	butane	750	600 ppm

Personal Protection:

Respiratory protection.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection.

For prolonged or repeated contact, use:

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Eye protection.

Use safety eyewear designed to protect against splash of liquids. Skin protection.

Personel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9. PHYSICAL AND CHEMICAL PROPERTIES.

Physical form	: aerosol	Methode
color	: see trade name	
odor	: typical	
flash point	: NB	°C
viscosity:	at 20 oC	NB
density :	0.77	g/cm3
solvent content :	90	%
vapour pressure :>	3-4 bar	mbar
ignition temperature :	n.a.	°C
boiling point :		°C
solid weight :	9.70	%
solid volume :	5.98	1/100kg
lower explosion limit:	1.5	Vol. %
upper explosion limit:	13.0	Vol. %
solubility in water	partly miscible	

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/4/6

10. STABILITY AND REACTIVITY.

Stabile under recommended storage and handling conditions. (See section 7) When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen. Keep away from oxidizing agent, iron-lyr alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION.

There are no data available on the preparation itself.

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage. Remark: The product has not been tested as such, but is categorised by means of conventional method. (EC-Guidelines 1999/45/EC)

12. ECOLOGICAL INFORMATION.

The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS.

080111 waste paint and varnish containing organic solvents or other dangerous substances Do not allow into drains or water courses.

Empty containers are to be deposited according to the official rules.

14. TRANSPORT INFORMATION.

Road/rail-transportation

ADR/RID	2
UN-Nr.:	1950
Transport document:	Aerosols, flammable
contains:	
Packaging group:	n.a.
Sea transport	
IMDG/Class:	2
EMS-Nr.:	2-13
UN-Nr.:	1950
Proper shipping name:	AEROSOLS
contains:	/
Packaging group:	n.a.
Marine pollutant:	n.a.

ICAO/IATA Class	: 2.1
UN-Nr.:	1950
Proper shipping name:	Aerosols, flammable
Packaging group :	n.a.

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/5/6

15. REGULARY INFORMATION.

The requirements of the Classification Packaging and Labelling of Dangerous Substances Regulations. (EC Guidelines 1999/45/EC)

The product is labelled as follows

Xn harmful
F+ extremely flammable

Danger classification

xylene, mixture of isomers

contains:

R phrases:

12 Extremely flammable.
20/21 Harmful by inhalation and in contact with skin.
36/38 Irritating to eyes and skin.

S phrases:

16 Keep away from sources of ignition - No smoking.
24 Avoid contact with skin.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
36/37 Wear suitable protective clothing and gloves.
51 Use only in well-ventilated areas.
23 Do not breathe spray. P phrases:

n.a.

Pressurized container. Keep away from sunlight and do not expose to temperatures exceeding 50° C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Water hazard class: 2

VOC (g/l) DIN ISO 11890: 694.495

16. OTHER INFORMATION.

Full text of R phrases with no appearing in section 2

10 Flammable.
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.
22 Harmful if swallowed.
37/38 Irritating to respiratory system and skin.
41 Risk of serious damage to eyes.
67 Vapours may cause drowsiness and dizziness.
11 Highly flammable.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking. 12 Extremely flammable.
65 Harmful: may cause lung damage swallowed.

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/6/6

The information of this MSDS is based on the present state of our knowledge and on current EEC and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction.

It is always the responsibility of the user to take all

necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.