

Date: 28.07.04

Revision Date: 24.03.04

page/1/6

DE 7450.0400

4CR Deutschland GmbH

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous

Substances Directive 67/548/EC

EINECS-Nr CAS-No.	R-phrases Names	Symb.	Conc.%
200-827-9 74-98-6 12	propane	F+	12.5 - 20
200-661-7 67-63-0	propan-2-ol; isopropyl alcohol 11-36-67	Xi,F	12.5 - 20
203-448-7 106-97-8	butane 12	F+	12.5 - 20
203-692-4 109-66-0	pentane 12-51/53-65-66-67	Xn,F+,N	25 - 50
265-150-3 64742-48-9	Naphtha (petroleum), hydrotreated heavy; low boiling point 10-65-66	Xn	2.5 - 10
265-151-9 64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha 11-38-51/53-65-67	Xn,F,N	2.5 - 10

Extra notices:

(See full text of R phrases under chapter 16)

3	HAZARDS	IDENTIFICATION OF THE PREPERATION.
	F+	Extremely flammable
	N	Dangerous for the environment

- 12 extremely flammable.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse
- 66 effects in the aquatic environment.
Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES.

General .

In all causes of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Inhalation

Remove or fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/2/6

Eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do

NOT use solvents or thinners. Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES.

Extinguishing media : recommended : alcohol resistant foam, CO₂,

powders, waterspray

not to be used : waterjet.

Recommendations : Fire will produce dense black smoke. Exposure

to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents.

If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7 HANDLING AND STORAGE.

Handling.

Vapours are heavier than air and may spread along floors. Vapours may form Explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preperation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in application area. For personal protection se Section 8.

Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/3/6

Storage.

Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act.

Observe label precaution. Storage: protected against frost on a dry, well ventilated place away from sources of heat and direct sunlight.

Keep away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

Engineering Measures.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn. Exposure Limits.

Occupational exposure limit for

EINECS-No.	Names	STL mg/m ³	LTL mg/m ³
200-827-9	propane	MAK	1000 ppm
200-661-7	propan-2-ol; isopropyl alcohol	500	400 ppm
203-448-7	butane	750	600 ppm
203-692-4	pentane	MAK	1000 ppm

Personal Protection:

Respiratory protection.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection.

For prolonged or repeated contact, use

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eve protection.

Use safety eyewear designed to protect against splash of liquids. Skin protection.

Personel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9 PHYSICAL AND CHEMICAL PROPERTIES.

Physical form	: aerosol	Methode
color	see trade name	DIN 53213
odor	typical	
flash point	NB	°C
viscosity:	at 20 °C	DIN 53211
density	0.70	g/cm ³
solvent content	74	%
vapour pressure :	4.5 bar	
ignition temperature :	200	°C
boiling point	42	°C
solid weight	26.00	%
solid volume	37.14	1/100 kg
lower explosion limit:	0.7	Vol. %
upper explosion limit:	12.0	Vol. %
solubility in water :	insoluble	

Material Safety Data Sheet according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/4/6

10. STABILITY AND REACTIVITY.

Stabile under recommended storage and handling conditions. (See section 7) When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION.

There are no data available on the preparation itself.

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Remark: The product has not been tested as such, but is categorised by means of conventional method. (EC-Guidelines 1999/45/EC)

12. ECOLOGICAL INFORMATION.

The product should not be allowed to enter drains or water courses.

The preparation itself is labelled in accordance with the conventional dangerous preparations directive (1999/45/EG) taking into consideration its ecological-toxicological properties. For details see section 2 and 15.

13. DISPOSAL CONSIDERATIONS.

080111 waste paint and varnish containing organic solvents or other dangerous substances

Do not allow into drains or water courses.

Empty containers are to be deposited according to the official rules.

14. TRANSPORT INFORMATION.

Road/rail-transportation

ADR/RID 2

UN-Nr.: 1950

Transport document: Aerosols, flammable
(Dampfdruck bei 50 °C höchstens 110 kPa)

contains:

Packaging group: n.a.

Sea transport IMDG/Class: 2

EMS-Nr.: 2-13

UN-Nr.: 1950

Proper shipping name: AEROSOLS contains:
/

Packaging group: n.a.

Marine pollutant: n.a.

Material Safety Data Sheet

according 91/155/EWG

Date: 28.07.04

Revision Date: 24.03.04

page/5/6

ICAO/IATA Class: 2.1
Proper shipping name: Aerosols, flammable

UN Nr.: 1950

Packaging group : n.a.

15. REGULARY INFORMATION.

The requirements of the Classification Packaging and Labelling of Dangerous Substances Regulations. (EC Guidelines 1999/45/EC) The product is labelled as follows

F+ extremely flammable
N Dangerous for the environment

Danger classification

n.a.

contains:

R phrases:

12 Extremely flammable.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

S phrases:

2 Keep out of the reach of children.

23 Do not breathe vapour.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in

Water hazard class: 1

VOC (g/l) DIN ISO 11890: 426.045

16. OTHER INFORMATION.

Full text of R phrases with no appearing in section 2

12 Extremely flammable.

11 Highly flammable.

36 Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking. 10 Flammable.

38 Irritating to skin.

Date: 28.07.04

Revision Date: 24.03.04

page/1/6

4CR Deutschland GmbH
 Dieselstraße 10 - 12
 D-25813 Husum
 Phone: (+49) 4841 / 99010
 e-mail: msds@4CR.com

Fax: (+49) 4841 / 99010

www.4CR.com

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Dangerous

Substances Directive 67/548/EC

EINECS-Nr CAS-No.	R-phrases Names	Symb.	Conc.%
200-827-9 74-98-6 12	propane	F+	12.5 - 20
200-661-7 67-63-0	propan-2-ol; isopropyl alcohol 11-36-67	Xi,F	12.5 - 20
203-448-7 106-97-8	butane 12	F+	12.5 - 20
203-692-4 109-66-0	pentane 12-51/53-65-66-67	Xn,F+,N	25 - 50
265-150-3 64742-48-9	Naphtha (petroleum), hydrotreated heavy; low boiling point 10-65-66	Xn	2.5 - 10
265-151-9 64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha 11-38-51/53-65-67	Xn,F,N	2.5 - 10

Extra notices:

(See full text of R phrases under chapter 16)

3	HAZARDS	IDENTIFICATION OF THE PREPERATION.
	F+	Extremely flammable
	N	Dangerous for the environment

12 extremely flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse

66 effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES.

General .

In all causes of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Inhalation

Remove or fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.