

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: WESMAR

INFORMATION PHONE: (206) 782-8186

EMERGENCY PHONE: (800) 424-9300 - CHEMTREC

PRODUCT NAME: WESMAR SWEEP AWAY

PRODUCT NUMBER: PA 8124 - PA 8126

PREPARED BY: Patricia Rodabaugh

DATE PREPARED: 06/06/2001

SYNONYMS:

WESMAR PRODUCTS, INC.
1440 N.W. 45th STREET
SEATTLE, WA 98107
(206) 782-8186

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	OSHA PEL	ACGIH TLV	Weight %
Raffinates (Petroleum), Sorption Process (Solvent naphtha)	64741-85-1	100 ppm	100 ppm	41-43
Light naphthenic distillate	64742-53-6	5 mg/m3 (mists)	5 mg/m3 (mists)	41-43
Ethoxylated nonyl phenol	9016-45-9	Not established	10 ppm	15-17

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW:

COMBUSTIBLE. Harmful if swallowed - can enter lungs and cause damage. May cause eye and skin irritation or injury.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Liquid is expected to be nonirritating to practically nonirritating to eyes. May be experienced as temporary discomfort.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. High vapor concentrations may cause central nervous system (CNS) depression.

INGESTION: Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

SKIN CONTACT: Liquid is expected to be slightly to moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SIGNS AND SYMPTOMS OF EXPOSURE:

Itching, burning or redness of the skin or eyes.

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation occurs, get medical attention.

INHALATION: Remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention.

INGESTION: Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

SKIN CONTACT: Remove contaminated clothing/shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

AGGRAVATED MEDICAL CONDITIONS:

Preexisting skin and eye conditions may be aggravated by exposure to this product.

SUPPLEMENTAL HEALTH INFORMATION:

Ingestion: Acute Oral LD50 (rat): >5 g/kg. Inhalation: No toxicity observed in rats exposed for four hours to approximately 1.6 mg/l.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 214F

FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION:

FLAMMABLE LIMITS: LEL: 0.60% **UEL:** 4.70%

EXTINGUISHING MEDIA:

Use water fog, "alcohol" foam, dry chemical, or CO2.

SPECIAL FIRE-FIGHTING PROCEDURES:

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece in positive pressure mode. Move containers from fire area if it can be done without risk. Use water to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Water run off from fire fighting may be slippery. When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

COMBUSTION PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED

Remove all sources of ignition and provide ventilation. Wear protective equipment as given in Section 8. Dike around large spills to prevent spreading. Absorb small spills with inert material (clay, sand). Prevent contamination of surface waters.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION (Specify Type):

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respir. of an air-purifying respir. for organic vapors.

VENTILATION:

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PROTECTIVE GLOVES:

Test data indicate the best protection is provided by neoprene, nitrile, and natural rubber gloves.

EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear gloves and protective clothing which are impervious to this product for the duration of anticipated exposure, if there is potential for skin contact.

WORK/HYGIENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

ENGINEERING CONTROLS:

Use this material only in well ventilated areas.

EXPOSURE GUIDELINES

May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

water white to very pale amber, oily liquid. Hydrocarbon odor.

SOLUBILITY IN WATER:

Solubility negligible in water

BOILING POINT: 400 F

PERCENT VOLATILE: N/A

VAPOR PRESSURE: N/A

PH: N/A

SPECIFIC GRAVITY: 0.867 - 0.873

MOLECULAR WEIGHT: N/A

MELTING POINT: NDA

POUNDS PER GALLON: 7.27

FREEZING POINT: NDA

OTHER PROPERTIES: Evaporation rate: 0.03

EVAPORATION RATE: Slower than ether

VAPOR DENSITY: Heavier than air

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID:

Avoid heat, sparks, flame and contact with strong oxidizing agents.

INCOMPATIBILITY:

Strong oxidizers.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS

Carbon monoxide, carbon dioxide, unidentified organic compounds, irritating aldehydes and ketones may be formed during combustion. Heating in air may produce irritating aldehydes, acids, and ketones.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID:

Avoid heat, flame, and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

12. ECOLOGICAL INFORMATION

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

14. TRANSPORT INFORMATION

DOT CLASS: Combustible liquid
HAZARD CLASS: Combustible
UN NUMBER: UN 1268
PACKING GROUP: III
GUIDE NUMBER: 128
PROPER SHIPPING NAME: Petroleum Distillates, n.o.s. (naphtha)

15. REGULATORY INFORMATION

SARA Title III Categories: 1. Immediate (Acute) Health Affects: YES 2. Delayed (Chronic) Health Effects: YES
3. Fire Hazard: YES 4. Sudden Release of Pressure Haz.: NO 5. Reactivity Hazard: NO

16. OTHER INFORMATION

HMIS INFORMATION: HEALTH: 2 FLAMMABILITY: 2 REACTIVE: 0 PROTECTION: G

SARA TITLE III DATA

For SARA Title III, Sec. 311 reporting, this material is classified as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

SARA 313 Toxic Chemical: Glycol ethers (fraction of product matching EPA definition in ethoxylated nonly phenol is 35.0 - 49.99%)

SARA Title III: Section 302/304 Extremely Hazardous Substances: Residual ethylene oxide (typical) (CAS 75-21-8), range in %: 0.001, TPQ = 1000, RQ = 10

Supplemental Health Info.

This product may contain residual (less than 16ppm) concentrations of ethylene oxide. Ethylene oxide causes tumors in laboratory animals.

Other Information:

Ethoxylated products may contain residual amounts of ethylene oxide (EO) which can accumulate in the container headspace and be released into the ambient environment. This process is enhanced when the product is agitated, as during tank car loading and unloading, and blending operations. Ethylene oxide causes tumors in laboratory animals. The Occupation Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1 ppm for an eight-hour time weighted average exposure. The standard regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with OSHA ethylene oxide standard (29 CFR 1910.1047)

OTHER ADDITIONAL INFORMATION:

NA = Not applicable. NDA = Not data available.

Californai Prop. 65

The following detectable componenets of this product are substances, or belong to classes of substances, known to the State of California to cause cancer and/or reproductive toxicity.

Chemical Name	CAS Number
Residual ethylene oxide (typical)	75-21-8

The information contained herein is based on the data available to us and is believed to be accurate. However, WESMAR makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. WESMAR assumes no responsibility for injuries from the use of the product described herein.