

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206)782-8186

PW 2000 / PW 2005
Clear Engine Paint

MATERIAL SAFETY DATA SHEET
FOR COATINGS AND RELATED MATERIALS
PREP: FEB. 1991 UPDATE: DEC. 1998

SECTION I PRODUCT IDENTIFICATION

PRODUCT NUMBER: X-6420

PRODUCT NAME: WESMAR CLEAR COAT

PRODUCT CLASS: CLEAR ALKYD SEALER

24 HOUR EMERGENCY ASSISTANCE

EMERGENCY (CHEMTREC) (800) 424-9300
INFORMATION (FARWEST) (206) 244-8844

HAZARD RATING

0 LOWEST

1

2

3

4 EXTREME

THIS PRODUCT

HEALTH 2

FLAMMABILITY 3

REACTIVITY 1

PERSONAL

PROTECTION G

SECTION II HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	PERCENT (BY WEIGHT)	OCCUPATIONAL EXPOSURE TLV (ACGIH)	PEL (OSHA)
------------	------------	------------------------	--------------------------------------	------------

ALIPHATIC HYDROCARBON	8052-41-3	32-38%	100ppm	500ppm
-----------------------	-----------	--------	--------	--------

ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	40-45%	300ppm	500ppm
---------------------------------	------------	--------	--------	--------

"PURSUANT TO TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR PART 372, THIS PRODUCT CONTAINS OR MAY CONTAIN A TOXIC CHEMICAL IN A QUANTITY SUBJECT TO THE REPORTING REQUIREMENTS UNDER SECTION 313"

SECTION III PHYSICAL DATA

BOILING RANGE: 244-287 F. WEIGHT/GALLON: 6.79 lbs. VAPOR PRESSURE: 2.0mmHg@68F
VAPOR DENSITY: HEAVIER THAN AIR: XX LIGHTER THAN AIR: _____
EVAPORATION RATE: FASTER THAN ETHER: _____ SLOWER THAN ETHER: XX
PERCENT VOLATILE BY VOLUME: 87% SOLUBILITY IN WATER: NIL
VOC: 676 GRAMS/LITER (LESS WATER) REACTIVITY IN WATER: NIL
APPEARANCE & ODOR: Clear, water white liquid with mild, sweet aromatic odor.

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA: FLAMMABLE FLASH POINT: 80 F. TCC
CLASS: 3 LEL: 1.5%-2.0%
DOT: FLAMMABLE UN NUMBER: 1263

EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical, or Water Fog.

UNUSUAL FIRE & EXPLOSION HAZARDS: Never use near or around welders or cutting torches because drum (even empty) or product (even just residue) can ignite explosively.

SPECIAL FIREFIGHTING PROCEDURES: Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

X-6420 (solvent)