

MATERIAL SAFETY DATA SHEETProduct: **UNIFILLER**Page 1 of 5
Revised : 07/20/01
MSDS - 309/CAN&USA**1. PRODUCT AND COMPANY IDENTIFICATION****WESMAR PRODUCTS, INC.**
1440 N.W. 45th STREET
SEATTLE, WA 98107
(206) 782-8186**1.1 Product specifications**

Name: UNIFILLER 5003 UNIFILLER 5004
Color: Beige Gray
Use: Main component for two component urethane primer.

1.2 Manufacturer's details

ROBERLO S.A.
Ctra. N-11 Km. 706,5
17457 Riudellots de la Selva (Girona)
Tel: +34-972 478 060
Fax: +34-972 477 394

1.3 Emergency telephone number CAN: CANUTEC 613-996-6666
USA: CHEMTREC 888-424-9300

2. INFORMATION/COMPOSITION - PRODUCT COMPONENTS

These substances represent a risk for health according to the European Union Directives for Dangerous Substances - 98/98/CEE or are listed in the "Toxic Substances Control Act Inventory" (TSCA).

INGREDIENTS	CAS Nr	INTERVAL OF CONC. %	SYMBOL	VAPOR PRESSURE (20°C(MMHg)	SARA 313 REPORT	EXPOSURE LIMITS			
						OSHA/ NIOSH	ACGIH	STEL	CEILING
1. N-Butyl acetate	123-86-4	2.5<c<10		8.4	No	150 ppm	150 ppm	200 ppm	--
2. Xylene (mixed isomers)	1330-20-7	10<c<25	Xn	6.7	Yes	100 ppm	100 ppm	150 ppm	200 ppm
3. 1-methoxy-2-Propanol acetate	108-65-6	2.5<c<10		3.8	No	N/E	N/E	--	--
4. Ethyl Benzene	100-41-4	2.5<c<10	Xn	7.1	Yes	100 ppm	100 ppm	125 ppm	--
5. Methyl isobutyl ketone	108-10-1	2.5<c<10		16	Yes	50 ppm	50 ppm	75 ppm	50 ppm

N/E = no evaluation results available at the time this MSDS was printed.

3. PRODUCT RISKS IDENTIFICATION

Flammable. Harmful if inhaled.
Irritating, avoid skin or eye contact.

4. FIRST AID**4.1 General**

In case of inhalation, ingestion, or contact with skin or eyes, follow the instructions below. If symptoms persist seek medical advice. If victim is unconscious do not attempt to administer anything orally.

4.2 Inhalation

Place the person somewhere with fresh air, keep them warm and relaxed, if breathing is irregular or stops, give artificial respiration. Do not attempt to administer anything orally. If the person is still unconscious place the person in a resting position and seek medical attention.

4.3 Eye contact

Wash eyes with plenty of water for approximately 10 minutes, seek medical attention immediately.

4.4 Skin contact

Remove contaminated clothing. Wash skin vigorously with soap and water or a proper skin wash. Never use solvents or thinners.

4.5 Ingestion

In case of ingestion, seek medical attention immediately. Keep the patient relaxed. Do not induce vomiting.

5. FIRE PROCEDURE

5.1 Extinguishing

Recommended: Foam resistant to alcohol, CO₂, dry powder or pulverized water.
Do not use: Water jets.

5.2 Recommendations

Combustion produces very dense, black and toxic fumes and smoke. Exposure to fumes could be dangerous for health. Use adequate respiratory protection. Cool with water all products that have been exposed to or in a fire. Keep extinguishing materials and product out of storm or sewer systems.

6. ACCIDENT PREVENTION MEASURES

Eliminate possible ignition sources and ventilate the zone. Avoid breathing vapours. Use safety measures mentioned in sections 7 and 8. Contain spills with non-combustible absorbents and dispose of in accordance to the requirements of local legislation (see section 13). Keep product spills, absorbent and decontaminant out of storm or sewer systems. Clean with detergent. Do not use solvents. If the product contaminates lakes, rivers, storm or sewer systems, report to the proper authorities according to local legislation.

7. HANDLING AND STORAGE

People with breathing problems or illnesses should not work in any kind of processes in which this substances are used.

7.1 Handling

Vapours are heavier than air and can extend to the soil. Could form dangerous mixtures in contact with air. Avoid creating vapour concentrations with air, flammables or explosives, avoid vapour concentrations above limits of exposure during work.

Do not store or use product near ignition sources and open flames. Electric equipment should be wired according to local code.

Keep containers closed, far from heat, fire. Do not use any type of tools that could provoke sparks. Exposure to atmospheric humidity and water could cause a build-up of pressure from CO₂ formation. Keep out of eye and skin contact. Avoid vapour inhalation and dust produced during spray application. For personal safety/protection, please refer to section 8. Do not eat, drink or smoke in application zones. Follow regulations on hygiene and safety at work. Keep this product in original containers or those made of same material.

7.2 Storage

See label instructions. Store according to local regulations and in a well ventilated area away from heat and direct sunlight. Avoid temperatures above 86°F. Keep away from ignition sources. Keep away from oxidants and very acidic or alkaline materials. Do not smoke. Firmly replace lid after each usage and store in an upright position.

8. EXPOSITION/PERSONAL PROTECTION MEASURES

People with breathing problems or illnesses should not work in any of processes in which this substances are used.

8.1 Technical measures

Provide proper ventilation, which can be obtained through good local extraction and good general extraction systems. Wear NIOSH approved respiratory equipment when handling open containers, pouring and mixing, as well as when applying and sanding.

8.2 Exposure limits

For exposure limits during work see section 2.

8.3 Personal protection

Respiratory protection

Wear NIOSH approved respiratory equipment when handling open containers, pouring and mixing, as well as when applying and sanding. This will most likely be a fresh air supply or an active carbon particulate filter.

Hand protection

For prolonged or repeated contact use polyvinyl alcohol gloves or nitril rubber gloves. Barrier creams could aid in protecting skin areas that may become exposed (e.g. wrist area). NEVER use barrier creams once exposure has already occurred.

Eye protection

Wear protection designed to protect eyes against spray and splashes.

Skin protection

Cover all parts of the body, including neck and head. Exposed parts should be washed after product application.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical estate: Viscous liquid
Flash point: +73.4°F
Viscosity: 45.10³ cps at 68°F BROOKFIELD
Density: 11.83 lbs./gallon at 68°F
Vapour pressure: 11 mbar (N-Butyl acetate at 68°F).
8.39 mbar (Xylene at 68°F)
Flammable limits: min: 1.0% vol. - max: 8% vol. (Xylene)
min: 1.2% vol. - max: 7.5% vol. (N-Butyl acetate)
Water solubility: Partially miscible.
Wt % Solids: 69.5
Vol. % Solids: 65.6
OSHA Storage: 1C
Coating VOC: 1.99 lbs./gallon
Mixture VOC: 2.09 lbs./gallon
Solvent Density: 7.286 lbs./gallon

10. STABILITY AND REACTIVITY

Product is stable under recommended handling and storage conditions (see section 7). Combustion could generate substances like carbon monoxide and carbon dioxide as well as fumes.

11. TOXICOLOGICAL INFORMATION

There is no data available on this on this product from tested samples. In case of repeated and/or prolonged contact with eyes it could produce an irritation and some reversible damage. Based on the isocyanates properties and considering technical data available about similar products, we conclude that the substances used could provoke an irritation and or extreme sensibilization of the breathing system, causing Asthma, breathing difficulties and pressure in the thorax. If exposed to concentrations below level of exposure breathing problems could occur. Continuous exposure could produce breathing illnesses. In case of repeated contact with skin it could produce a moderated irritation and/or skin peeling provoking a non allergic contact dermatitis. Inhalation of vapour concentrations above the limit of exposure causes respiratory irritation. There are no known negative or harmful effects if handled correctly.

12. ECOLOGICAL INFORMATION

There is no data available on this product from tested samples.
Penetration into waterways, storm and sewer systems should be avoided.

13. ELIMINATION CONSIDERATIONS

Do not dispose of material or any by-products thereof into waterways, storm and sewer systems.
Empty containers or residual materials should be treated according to local regulations.

14. TRANSPORT INFORMATION

Transport should be done according to appropriate regulations. Known classifications are listed below and in section 15.

Transport mode	Detail	
Road and rail ADR/TPC - RID/TPF	Partial Exemption. Note Sub E. Marginal 2301.	
Sea IMDG	Class 3.3 UN No.: 1263 Maritime contaminating: NO Packing group: III	Packing name: Bill of Lading Label: Flammable
Air plane IATA/ICAO	Class: 3 UN No.: 1263 Packing group: III	Packing name: Airway bill Label: Flammable

15. TRANSPORTATION:

See section 2 for further information.

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
