

SC 9101 - Promo
Pack**MATERIAL SAFETY DATA SHEET****Wynn's No. Five Spray****WYNN OIL COMPANY**
1151 West Fifth Street
Azusa, California 91702**EMERGENCY TELEPHONE NUMBER:**
Chemtrec (800) 424-9300**INFORMATION TELEPHONE NUMBER:**
Wynn Oil Company (626) 334-0231**PRODUCT IDENTIFICATION**

PRODUCT NAME	EFFECTIVE DATE	PRODUCT CODE
Wynn's No. Five Spray	1-11-00	31001, 31002, 31003
CHEMICAL NAME	CAS NUMBER	
N/A	N/A	

HAZARDOUS INGREDIENTS

COMMON NAME	CHEMICAL NAME	CAS NO.	%	OSHA PEL	ACGIH TLV-TWA
Petroleum Hydrocarbon	Petroleum Oil	64742-52-5	1-10	5 mg/m ³ as mist	5 mg/m ³ as mist
Aliphatic Petroleum Distillates	Aliphatic Petroleum Distillates	64742-88-7	70-80	None Established	None Established
Petroleum Hydrocarbon	Propane	74-98-6	1-10	1000	2500 ppm

Contains no other ingredients now known to be hazardous as defined by OSHA 29CFR 1910.1000(z) and 29CFR 1910.1200.

PHYSICAL DATA

These data are approximate or typical values and should not be used as precise specifications. Unless otherwise noted values are at 20°C (68°F) and 760 mmHg (1 atm).

Boiling Point/Range	-45 to 355°F (-43 to 194°C)	Freeze Point	N/D
Specific Gravity (H ₂ O=1) @ 15.6°C	0.8-0.9	Vapor Pressure (psig)	55-65
Vapor Density (Air =1)	>1	Solubility in Water (%)	Nil
% Volatiles by Volume	N/D	Evaporation Rate (Butyl Acetate = 1)	>1
pH (as is)	N/A	pH (dilute) @ %	N/A
Appearance	Light Amber Clear Liquid	Odor	Solvent

N/D - Not Determined

N/A - Not Applicable

< = Less Than

> = Greater Than

FIRE AND EXPLOSION HAZARD DATA

Flash Point -156°F(-104°C) Method Tag Closed Cup

Flammable or Explosive Limits (Approximate percent by volume in air)

Lower (LEL) 2.2 Upper (UEL) 9.5

Hazard Class Identification

	Flammability		Hazard Code
	4		0 - Least
			(insignificant)
Health		Reactivity	1 - Slight
1		0	2 - Moderate
	Other		3 - High
	--		4 - Extreme

Extinguishing Media

Dry chemicals, carbon dioxide, water fog.

Special Fire Fighting Procedures

Use water to cool fire exposed containers. Fire fighters wear a self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Exposure to heat may cause bursting.

REACTIVITY DATA

Stability

Stable.

Conditions to Avoid

Heat, open flame.

Materials to Avoid

Strong oxidizing agents.

Hazardous Decomposition or Combustion Products

Thermal decomposition may produce oxides of carbon, phosphorus and sulfur compounds.

Hazardous Polymerization (conditions)

Will not occur.

HEALTH HAZARDS/ROUTES OF ENTRY

Signs, Symptoms and Effects of Overexposure

- Ingestion (swallowing)** Ingestion of this material may cause vomiting. Aspiration into the lungs during ingestion or vomiting can result in severe pulmonary damage.
- Skin Contact** May cause skin irritation upon direct contact. Prolonged contact may cause drying, cracking, redness, & defatting of skin.
- Eye Contact** May cause moderate eye irritation.
- Inhalation (breathing)** May cause irritation to nose, throat and respiratory tract. May cause dizziness, headache.

Other Effects of Prolonged/Repeated Overexposure

This material has not been identified as a carcinogen by NTP, IARC or OSHA.
CHRONIC EFFECT: Repeated and prolonged overexposure to vapors may result in brain, nervous system, kidney and liver damage.

EMERGENCY AND FIRST AID PROCEDURES

- Ingestion (swallowing)** DO NOT induce vomiting. Call a physician immediately.
- Skin Contact** Wash affected area with soap and water. Remove contaminated clothing.
- Eye Contact** Flush with water for 15 minutes. If irritation persists, call a physician.
- Inhalation (breathing)** Remove person to fresh air to avoid further inhalation.

SPILL OR RELEASE CONTROL PROCEDURES

Steps to be taken in case material is released or spilled

Remove all sources of ignition. Ventilate area. Avoid breathing of vapors. Remove with inert absorbent.

Waste Disposal Method

DO NOT incinerate. Dispose of in accordance with Federal, State and Local regulations.

EPA Reportable Quantity (RQ), 40CFR302 (CERCLA104)

N/A

EPA Toxic Chemical Release Reporting, 40CFR372(SARA313)

Chemical	CAS NO.	% in Product
N/A	N/A	N/A

HANDLING AND STORAGE

Handling and Storage Precautions

Warning: Contains combustible petroleum distillates. Avoid skin contact and breathing of vapors. USE ONLY IN A WELL VENTILATED AREA. Keep container closed. Keep away from flame, sparks or hot surfaces.

Other Precautions

KEEP OUT OF REACH OF CHILDREN.

PERSONAL PROTECTION - EXPOSURE CONTROL

Ventilation

General or local exhaust.

Respiratory Protection

Normal use, none required.

Eye Protection

Safety glasses.

Protective Gloves

Impervious gloves.

Other Protective Clothing or Equipment

None.

Work/Hygienic Practices

Personal cleanliness is always appropriate. Frequent washing minimizes chance of inadvertent exposure.

TRANSPORTATION INFORMATION

Department of Transportation (DOT) Classification

	Flammable Liquid		Corrosive
	Flammable Solid		Non-Flammable Gas
XXX	Flammable Gas		Not Hazardous by DOT
	Combustible Liquid		Other:

DOT Proper Shipping Name

Aerosols, flammable.
(Consumer commodity, ORM-D may be used for ground transportation within the USA.)

DOT ID Number

UN 1950

DOCUMENTATION

Product Code No.: 31001, 31002, 31003
Previous Code No.: New

Issue Date: 1-11-00
Prior Date: New

This information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.