

MATERIAL SAFETY DATA SHEET

Revised 07/19/96

Page 1

WESMAR PRODUCTS, INC.

1440 N.W. 45th STREET

SEATTLE, WA 98107

(206) 782-8186

Product Code:

SF 1506

SECTION I PRODUCT DESCRIPTION

Product Name: **Windshield Resealant**

Synonyms: **N/A**

Chemical Family: **Hydrocarbon**

SECTION II PRODUCT COMPOSITION

Ingredients	%	CAS#	ACGIH TLV
Heptane	15	142-82-5	400PPM
Aromatic Process Oil	13	64742-04-7	5mg/m3 TWA-8HR
Rubber, Resin, Fillers	72		

SECTION III PHYSICAL PROPERTIES

Boiling Range: 200/212F

Specific Gravity (Water=1): 1.33

Vapor Pressure at 20C (MM of HG): 45MM

Solubility in Water: Insoluble

Evaporation Rate: (n.BuAc=1) 4.5

% Volatile by Volume: 27.7

Appearance and odor: Black lightly jelled paste with mild solvent odor.

Vapor Density (AIR=1): 3.4

Reactivity in water: None

SECTION IV FIRE AND EXPLOSION DATA

Lower Flammability Limits (% in Air): 1.0

Upper Flammability Limits (% in Air): 7.0

Flash Point (And Method): 14F TCC

Flammability Classification: Flammable Liquid UN1133

Recommended Extiguishing Media: NFPA Class B Extinguisher (CO2, Foam, Dry Chemical)

Special Firefighting Procedures:

Water spray may be ineffective, but may be used to cool closed containers. If water is used, use fog nozzles.

Unusual Fire/Explosion Hazards: May form flammable and/or explosive mixtures with air if ignited. Closed containers may explode if exposed to extreme heat. Vapors may travel considerable distance to ignition source and flash back.

SECTION V HEALTH INFORMATION

Threshold Limit Value: 400PPM

OSHA PEL: 400 PPM

Effects of Overexposure: Acute: Central nervous system depression. Inebriation followed by headache, nausea. Severe Cases: Dizziness, convulsions and unconsciousness. Anorexia and nervousness may persist for several months following acute overexposure. Chronic: Skin, Conjunctiva and mucous membranes of upper respiratory tract may be irritated. Dermatitis and de-fatting of skin.

Chemical listed as carcinogen or potentiation carcinogen? Yes

Agency(s) Listed: IARC Monographs list aromatic process oil.

SF 1506**Emergency First Aid Procedures:**

Eye Contact: Flush with water for at least 15 minutes.

Skin Contact: Wash with hand cleaner; then soap and water.

Inhalation: Remove to fresh air; If breathing has stopped begin artificial respiration; Call Doctor.

Ingestion: Do Not induce vomiting; Call Doctor at once.

Special Information: Contains an aromatic process oil which has caused skin tumors in laboratory animals after excessive long term overexposure. After skin contact wash with hand cleaner; follow with soap and water.

SECTION VI**REACTIVITY DATA**

Stability: Stable

Conditions to avoid: Heat, sparks and open flame; ignition sources. Vapors are heavier than air and may travel considerable distance to ignition source and flash back.

Incompatibility with other materials: Keep away from strong oxidizers.

Hazardous decomposition products: Carbon monoxide from burning.

Hazardous polymerization: Will not occur.

SECTION VII**SPILL OR LEAK PROCEDURES**

Procedures if material is spilled or released: Remove all sources of ignition, avoid breathing vapor, ventilate area. Remove with non sparking tools to a safe area free from ignition sources. Expose material to air until solid.

Waste disposal procedures: Observe local regulations. Do not incinerate in closed containers.

SECTION VIII**SPECIAL PROTECTION INFORMATION**

Respiratory protection: Ventilate to keep air below TLV. NIOSH approved air supply masks for areas of concentrated vapors.

Local Exhaust: Preferable.

Mechanical Equipment: Acceptable.

Protective Gloves: Optional-must not dissolve in solvents.

Eye Protection: Optional

Other Protective Equipment: None

SECTION IX**ADDITIONAL PRECAUTIONS**

Precautions to be taken in handling and storage:

Extremely flammable. Vapor harmful. Harmful or fatal if ingested. Contains: Petroleum Distillates. If swallowed do not induce vomiting. Call Physician at once. Keep away from heat, sparks or open flame. Avoid contact with skin or eyes; flush thoroughly with water for at least 15 minutes. Do not store in open or unlabeled containers. Use with adequate ventilation. For industrial use only. Keep out of reach of children.

Other Precautions:

Do not store above 120F. Containers should be grounded when pouring. Avoid free fall of liquid. Do not flame cut, braze or weld.

The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based on supplier-issued Material Safety Data Sheets and may be subject to error. If apprised of changes, updated MSDS will be promptly issued. Users must make their own determination regarding the suitability of the product for their own purposes prior to use.