

SF 1514

1514
5-19-99

MATERIAL DATA SAFETY SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER'S NAME:
ADDRESS:Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

PHONE: 24 HOUR EMERGENCY (INFOTRAC) 800-535-5053 Information Phone (800) 451-7206

PRODUCT IDENTIFICATION: Interthane (Black) Urethane Adhesive Sealer 1514

Generic Description: Adhesive Sealer
 Physical Form: Black Paste
 Odor: Neutral Odor
 NFPA Profile: Health 2 Flammability 2 Reactivity 0
 Note: NFPA = National Fire Protection Association

SECTION 2 - OSHA HAZARDOUS COMPONENTS

CAS NO.	INGREDIENT	WT %	EXPOSURE LIMITS
68130-40-5	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-hydroxy-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1), polymer with .alpha.-hydro.-omega.-hydroxypoly[oxy(methyl-1,2-ethanediyl)] and 1,1'-methylenebis[4-isocyanatobenzene], isocyanate terminated	10-20	Not Established
1333-86-4	Carbon Black	20-30	OSHA: TWA: 3.5 mg/m ³ ACGIH: TWA: 3.5 mg/m ³
61788-32-7	Hydrogenated Terphenyl	10-25	OSHA: TWA: 0.5 ppm ACGIH: TWA: 0.5 ppm
66402-68-4	Aluminum Silicate	10-20	OSHA: TWA: 5 mg/m ³ , STEL: 10 ACGIH: TWA: 5 mg/m ³ , STEL: 10
7631-86-9	Silica	5-10	None
108-88-3	Toluene	5-10	OSHA: TWA: 100 ppm, STEL 150 ACGIH: TWA: 50 ppm
101-68-8	4-4" Diphenylmethane Diisocyanate	<0.45	OSHA: CEIL: 0.02 ppm ACGIH: TWA: 0.005 ppm

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Emergency Planning and Community Right To Know Act of 1986 and 40 CFR part 372:

108-88-3	Toluene	5-10%
101-68-8	4-4" Diphenylmethane Diisocyanate	<0.45% (Below De Minimus)

SECTION 3 - EFFECTS OF OVEREXPOSURE

Eye:	Moderate eye irritation: signs / symptoms can include redness, swelling, pain, tearing, and hazy vision.
Skin:	Allergic Skin Reaction: signs / symptoms can include redness, swelling, blistering, and itching. Moderate skin irritation: signs / symptoms can include redness, swelling, itching, and dryness.
Inhalation:	Allergic Respiratory Reaction: signs / symptoms can include difficulty breathing, wheezing, tightness of chest, and respiratory failure. Central nervous system depression: signs / symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness, and unconsciousness.

MATERIAL DATA SAFETY SHEET

Oral: Irritation of upper respiratory tract: signs / symptoms can include soreness of the nose and throat, coughing, and sneezing.
Gastro-intestinal effect:s: signs / symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

SECTION 4 - FIRST AID MEASURES

Eyes: Immediately flush with water for 15 minutes. Get medical attention.
Skin: Wash affected area with soap and water.
Inhalation: If signs / symptoms occur, remove person to fresh air. If signs / symptoms continue, call a physician.
Oral: Do not induce vomiting. Drink two glasses of water. Call a physician.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point (Closed Cup): 90°F PMCC
Autoignition Temperature: Not Determined
Flammability Limits in Air: Not Determined
Extinguishing Media: Carbon Dioxide (CO₂). Water. Dry chemical. Foam.
Unsuitable Extinguishing Media: None
Fire Fighting Procedures: Wear full protective clothing including helmet, self contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist, and legs, face mask, and protective covering for exposed areas of the head.
Unusual Fire Hazards: None known
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.
NFPA Hazard codes: Health: 2 Fire: 2 Reactivity: 0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Containment/Clean-up: Ventilate area. Extinguish all ignition sources. Contain spill. Evacuate unprotected personnel from hazard area. Cover with absorbent, place in approved drum, do not seal drum for 48 hours to avoid possible pressure build-up. Disposal of collected product, residues, and cleanup materials may be governmentally regulated. Observe all applicable local, state and federal waste management regulations. Observe all personal protective equipment recommendations described in Sections 5 and 8. Local, state, and federal reporting requirements may apply to spills or releases of this material into the environment. See applicable regulatory compliance information in Section 15.
Recommended disposal: Incinerate in a permitted hazardous waste incinerator.

SECTION 7 - HANDLING AND STORAGE

Handling: Material is a flammable liquid.
Storage: Keep container closed and store away from water or moisture.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls

Local Exhaust: Recommended
General Ventilation: Recommended

Personal Protective Equipment:

MATERIAL DATA SAFETY SHEET

Eyes: Avoid eye contact. Wear unvented goggles during operations in which exposure is likely.

Skin: Avoid skin contact. Wear appropriate gloves when handling this product.

Inhalation: Avoid breathing of vapors. Use respiratory protection unless adequate local exhaust ventilation is provided or air sampling data show exposures are within recommended exposure guidelines. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator, full-face organic vapor respirator. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

Wash hands after handling and before eating.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste

Color: Black

Odor: Neutral

Specific Gravity (at 77°F/25°C): 1.2

Viscosity: Not Determined

Freezing / Melting Point: Not Determined

Boiling Point (at 760 mm Hg): Not Determined

Vapor Pressure (at 77°F/25°C): Not Determined

Vapor Density: Not Determined

Solubility in Water (%): Nil

pH: Not Applicable

Volatile Organics: 80 grams / liter SCAQMD, Rule 443.1, calculated

VOC less H₂O & exempt solvent: 80 grams / liter SCAQMD, Rule 443.1, calculated

Note: The above information is not intended for use in preparing product specifications.

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Materials to Avoid: None known

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

Complete information not yet available.

SECTION 12 - ECOLOGICAL INFORMATION

Not a marine pollutant. Complete information not yet available.

SECTION 13 - DISPOSAL INFORMATION

When a decision is made to discard this material, as received, is it classified as a hazardous waste?
Yes.

U.S. EPA Hazardous Waste Number: D001 (Ignitable).

State or local laws may impose additional regulatory requirements regarding disposal.

MATERIAL DATA SAFETY SHEET

SECTION 14 - TRANSPORT INFORMATION

DOT Information (49CFR 172.101)

DOT Shipping Name: Not Regulated
DOT Hazard Class: Not Applicable
DOT Label: None
UN/NA Number: Not Applicable

SECTION 15 - REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

TSCA Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

EPA SARA Title III Chemical Listings:

Section 302 Extremely Hazardous Substances: None.
Section 304 CERCLA Hazardous Substances: None.
Section 312 Hazard Class:

Acute: Yes
Chronic: No
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals:

108-88-3	Toluene	5-10%
101-68-8	4-4" Diphenylmethane Diisocyanate	<0.45% (Below De Minimus)

Supplemental State Compliance Information:

California:

Warning: This product contains the following chemicals listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer: None Known.

Warning: This product contains the following chemicals listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause birth defects or other reproductive harm: Toluene.

New Jersey:

CAS NO.	INGREDIENT
68130-40-5	Polyurethane prepolymer
1333-86-4	Carbon black
61788-32-7	Hydrogenated terphenyl
64402-68-4	Aluminum silicate
7631-86-9	Silica
101-68-8	4-4" Diphenylmethane Diisocyanate

SECTION 16 - OTHER INFORMATION

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.