

SF 4186

MATERIAL SAFETY DATA SHEET**4186**
8/23/00Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186**SECTION I - PRODUCT IDENTIFICATION**PART NUMBER: **4186**
PRODUCT NAME: **Self-Etching Primer**
TRADE NAME/SYNONYMS: **Self-Etching Primer**
CHEMICAL FAMILY: **Aerosol Primer**

Health	2
Flammability	4
Reactivity	0

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	WT%	ACGIH/TLV	OSHA/PEL	UNITS	V.P.
Propane	74-98-6	11	2500	1000	PPM	760.00
Butane	106-97-8	11	800	800	PPM	760.00
Toluene	108-88-3	2	50	100	PPM (skin)	22.00
		STEL		150	PPM (skin)	
Xylene	1330-20-7	5	100	100	PPM	5.90
		STEL	150	150	PPM	
Acetone	67-64-1	31	500	1000	PPM	180.00
		STEL	750		PPM	
Methyl Isobutyl Ketone	108-10-1	18	50	50	PPM	16.00
		STEL	75	75	PPM	
Ethyl 3-Ethoxypropionate	763-69-9	2	Not Established			1.11
Talc	14807-96-6	7	2	2	MG/M3 as Resp. Dust	
Titanium Dioxide	13463-67-7	3	10	10(5)	MG/M3 as Dust ***	

***Total Dust (Respirable Fraction)

SECTION III - PHYSICAL DATA

Product Weight: 6.68 lb/gal 800 g/l
Boiling Point: < 0° - 342°F < -18° - 172°C
Volatile Volume: 92%
Vapor Density: Heavier than air
Volatile Organic Compounds (VOC Theoretical)
Volatile Weight: 50.87% Less Federally Exempt Solvents
HMIS: 2 4 0

Specific Gravity: 0.80**Melting Point:** N/A**Evaporation Rate:** Faster than ether**Solubility In Water:** N/A**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Flash Point: LEL UEL
 Propellant < 0°F 1.0 12.8

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire And Explosion Hazards: Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Special Fire Fighting Procedures: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION V - HEALTH HAZARD DATA

Routes Of Exposure: Exposure may be by inhalation and/or skin or eye contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation and personal protective equipment.

continued

SECTION V - HEALTH HAZARD DATA CONTINUED**Acute Health Hazards:**

Effects Of Overexposure: Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Signs And Symptoms Of Overexposure: Headache, dizziness, nausea and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MATERIAL SAFETY DATA SHEET

4186
8/23/00

Medical Conditions Aggravated by Exposure: None generally recognized.

Emergency And First Aid Procedures:

If Inhaled: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If On Skin: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

If In Eyes: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If Swallowed: Get medical attention.

Chronic Health Hazards:

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Rats exposed to titanium dioxide dust 250 mg/m³ developed lung cancer, however, such exposure levels are not attainable in the workplace. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

SECTION VI - REACTIVITY DATA

Stability: Stable

Conditions To Avoid: None known

Incompatibility: None known

Hazardous Decomposition Products: By fire: Carbon Dioxide, Carbon Monoxide

Hazardous Polymerization: Will not occur

SECTION VII - SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled: Remove all sources of ignition. Ventilate and remove with inert absorbent.

Waste Disposal Method: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate.

Depressurize container. Dispose of in accordance with Federal, State and Local regulations regarding pollution.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Precautions To Be Taken In Use: Use with only adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

Ventilation: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

Respiratory Protection: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

Protective Gloves: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

Eye Protection: Wear safety spectacles with unperforated sideshields.

SECTION IX - PRECAUTIONS

DOL Storage Category: 1A

Precautions To Be Taken In Handling And Storing: Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively.

During Use And Until All Vapors Are Gone: Keep area ventilated. DO NOT SMOKE. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water and other heat sources could cause container to burst. Do not take internally. Keep out of reach of children.

Other Precautions: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SECTION X - OTHER REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) Supplier Notification

CAS No.	Chemical Compound	% by WT	% Element
---------	-------------------	---------	-----------

108-88-3	Toluene	2	
1330-20-7	Xylene	5	
108-10-1	Methyl Isobutyl Ketone	18	

California Proposition 65

Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Certification: All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and INTERNATIONAL EPOXIES & SEALERS disclaims any and all liability or legal responsibility or use or reliance upon same.