

Tm 1750
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	WESMAR KUT OUT Heavy-Duty Compound
Product code	CBWPB090-03-U
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, solvent, beige

WARNING! Combustible Liquid, Highly toxic by inhalation, Moderate skin irritant, Moderate eye irritant, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

May cause eye irritation.

Skin Contact

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of dust, vapor, and/or fume is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

amounts may be harmful. Prolonged or repeated breathing of this material may result in chronic bronchitis (inflammation of the airways of the lungs). Symptoms include coughing and shortness of breath. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidney. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material. Silicosis predisposes the individual to the development of mycobacterial infections including tuberculosis or to fungal infections. This is most likely to occur after the age of 50 and in association with moderate to severe silicosis.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, cough, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, loss of coordination, confusion, difficult breathing, irregular heartbeat, narcosis (dazed or sluggish feeling), convulsions, coma, and death. Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Chronic feeding studies with white oils (greater than 0.5% in the diet) have resulted in increased organ weights (liver, kidney, spleen), and in microscopic areas of oil accumulation in the liver and the

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

lymph nodes of the gut in experimental animals. These changes have occasionally been associated with cell damage. In humans, cell damage resulting from accumulation of these oil droplets has only occurred following prolonged ingestion of mineral oil. These effects are not expected to occur as a result of occupational exposure to white oils., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:, mild, reversible liver effects, mild, reversible kidney effects, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans:, chronic bronchitis, emphysema, kidney damage

Carcinogenicity

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke. White mineral oil was not carcinogenic in laboratory animals by any route of exposure other than by injection into the abdomen. Results of abdominal injection are not relevant to possible human exposure to this material.

Reproductive Hazard

No data

Other Information

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of immunological disorders and autoimmune diseases such as scleroderma (a disorder manifested by fibrosis of the lungs, skin and other internal organs), systemic lupus erythematosus and sarcoidosis (chronic inflammatory diseases).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
KEROSENE	8008-20-6	>=15-<20%
SILICA, CRYSTALLINE TRIPOLI	1317-95-9	>=15-<20%
FLUX CALCINED DIATOMACEOUS EARTH	68855-54-9	>=10-<15%

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

MINERAL SPIRITS REGULAR (BASE DATA)	8052-41-3	>=5-<10%
SILICA AMORPHOUS (SIO2)	7631-86-9	>=5-<10%
GLYCERINE	56-81-5	>=1.5-<5%
Fatty Acid	NJTS# 800986-5166P	>=1.5-<5%
MORPHOLINE	110-91-8	>=1-<1.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse. If skin contact with molten material occurs, flush exposed area with cool water. Do not forcibly remove material adhering to the skin. Seek immediate medical attention.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Flammability Class for Flammable Liquids

Combustible Liquid Class IIIA

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

KEROSENE		8008-20-6	
ACGIH	time weighted average	200 mg/m3	Non-aerosol
NIOSH	Recommended exposure limit (REL):	100 mg/m3	
SILICA, CRYSTALLINE TRIPOLI		1317-95-9	
ACGIH	time weighted average	0.025 mg/m3	Respirable fraction.
FLUX CALCINED DIATOMACEOUS EARTH		68855-54-9	
OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
Z3	time weighted average	0.8 mg/m3	

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

NIOSH	Recommended exposure limit (REL):	6 mg/m3	
MINERAL SPIRITS REGULAR (BASE 8052-41-3 DATA)			
ACGIH	time weighted average	100 ppm	
NIOSH	Recommended exposure limit (REL):	350 mg/m3	
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3	
OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,900 mg/m3	
OSHA Z1A	time weighted average	100 ppm	
OSHA Z1A	time weighted average	525 mg/m3	
US CA OEL	Time Weighted Average (TWA)	100 ppm	
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	525 mg/m3	
	Permissible Exposure Limit (PEL):		
SILICA AMORPHOUS (SIO2) 7631-86-9			
NIOSH	Recommended exposure limit (REL):	6 mg/m3	
ACGIH	time weighted average	10 mg/m3	
OSHA Z1A	time weighted average	6 mg/m3	
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
Z3	time weighted average	0.8 mg/m3	
GLYCERINE 56-81-5			
ACGIH	time weighted average	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
MORPHOLINE 110-91-8			
ACGIH	time weighted average	20 ppm	
NIOSH	Recommended exposure limit (REL):	20 ppm	
NIOSH	Recommended exposure limit (REL):	70 mg/m3	
NIOSH	Short term exposure limit	30 ppm	
NIOSH	Short term exposure limit	105 mg/m3	
OSHA Z1	Permissible exposure limit	20 ppm	
OSHA Z1	Permissible exposure limit	70 mg/m3	

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	beige
Odour	solvent
Boiling point/range	150 °F / 66 °C@ 760.00 mmHg
pH	8.5
Flash point	153.9 °F / 67.7 °C
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	1.15 g/cm3

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

Solubility	9.56 lb/gal @ 60.00 °F / 15.56 °C
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

KEROSENE	LD 50 Rat: 5,000 mg/kg
MINERAL SPIRITS REGULAR (BASE DATA)	LD 50 Rat: 5 g/kg
SILICA AMORPHOUS (SIO2)	LD 50 Rat: 10,000 mg/kg
GLYCERINE	LD 50 Rat: 12,600 mg/kg
Fatty Acid	LD 50 Rat: 10,000 mg/kg

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

MORPHOLINE

LD 50 Rat: 1,050 mg/kg

Acute Inhalation Toxicity

KEROSENE

LC 50 Rat: 5,000 mg/m3, 4 h

SILICA AMORPHOUS (SIO2)

LC 50 Rat: 0.139 mg/l, 4 h

GLYCERINE

LC 50 Rat: 570 mg/m3, 1 h

MORPHOLINE

LC 50 Rat: 8000 ppm, 8 h

Acute Dermal Toxicity

KEROSENE

LD 50 Rabbit: 2 g/kg

MINERAL SPIRITS REGULAR (BASE
DATA)

LD 50 Rabbit: 3 g/kg

SILICA AMORPHOUS (SIO2)

LD 50 Rabbit: 5,000 mg/kg

GLYCERINE

LD 50 Rabbit: 10 g/kg

Fatty Acid

LD 50 Rabbit: 2,000 mg/kg

MORPHOLINE

LD 50 Rabbit: 500 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

ASHLAND

SAFETY DATA SHEET

Page: 11
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

SILICA, CRYSTALLINE TRIPOLI

ETHYL BENZENE

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

TOLUENE

BENZENE

SARA Hazard Classification

Fire Hazard

Acute Health Hazard

Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards

Combustible Liquid

Highly toxic by inhalation

ASHLAND

SAFETY DATA SHEET

Page: 12
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405367
Version: 1.

WESMAR KUT OUT Heavy-Duty
Compound CBWPB090-03-U

Moderate skin irritant
Moderate eye irritant
Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	1	2	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).