

U-POL

PRODUCTS

MATERIAL SAFETY DATA SHEET

COMMERCIAL PRODUCT NAME: UPOL PLASTIC REPAIR SYSTEM (AEROSOLS)

PREPARATION: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

EMERGENCY TELEPHONE NO:- 1-800-424 9300(CHEMTREC)
1-703 527 3887(CHEMTREC INTERNATIONAL)

FAX NO:- 1-800 787 5150

SANDERS AND ASSOCIATES INC.,
Three Werner Way,
Suite 300
Lebanon NJ 08833
U.S.A.

COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>LEVEL</u>	<u>SYMBOL</u>	<u>RISK</u>
WHITE SPIRIT	64742-82-1	0 -25%	Xn - Harmful.	R22
ALIPHATIC HYDROCARBON	6472-49-0	0 -50%	Xn - Harmful	R22
BUTANE	106-97-8	0 - 25%	F+ - Extremely flammable.	R12
PROPANE	74-98-6	0 - 25%	F+ - Extremely flammable.	R12
XYLENE	1330-20-7	0 -50%	Xn - Harmful.	R10 R20/21 R38
DICHLOROMETHANE	75-09-2	0 - 50%	Xn - Harmful	R40
2-BUTOXYL ETHANOL	111-76-2	0 - 5%	Xn - Harmful	R20/21 R37
ACETONE	67-64-1	0 - 50%	F - Highly flammable.	R11
TOLUENE	108-88-3	0 - 50%	F - Highly flammable.	R11
			Xn - Harmful.	R20
DME	115-10-6	0 - 50%	F+ - Harmful	R12
MIBK	108-10-1	0 - 25%	F - Highly Flammable	R11

HAZARDS IDENTIFICATION

INHALATION: May cause drowsiness and irritation of respiratory tract.

SKIN: May cause irritation on prolonged contact, which can lead to dermatitis.

EYES: Irritation and soreness.

INGESTION: Sore throat, stomachache, nausea, but unlikely to be ingested.

UP0200/UP0201/UP0202/UP0203/UP0204/UP0205/UP0206/UP0207/
UP0208/UP0209/UP0210/UP0211

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear, black or grey liquid.
ODOUR:	Distinctive..
FLASH POINT:	- 40°C.
AUTOFLAMMABILITY TEMPERATURE:	230 - 500°C
EXPLOSIVE LIMITS:	Lower 0.6 - 1.3% Upper 9 – 66%
VOLATILE CONTENT:	70 - 100%.
SOLUBILITY:	Insoluble in water.

STABILITY AND REACTIVITY

Stable under normal conditions. Avoid named flames. Heat increase may be sufficient to raise the temperature above the product flash point. Thermal decomposition can give rise to acrid fumes.

TOXICOLOGICAL INFORMATION*

For Xylene, the following values have been reported:-

An oral LD50 in rats of 4.3g/Kg.
LC50 in rats of 5000 ppm/4 hours.

For Toluene, the following values have been reported:-

LD50 7000 mg/Kg.
LC50 8000 ppm.

For Acetone, the following values have been reported:-

LD50 5.8g/Kg.
LC50 50 mg/L.

For White Spirit the following values have been reported:

An oral LD50 in rats of 50000mg/Kg.

For Dichloromethane the following values have been reported:

An oral LD50 in dogs of 3000 mg/Kg.

For 2-butoxyethanol the following values have been reported:

An oral LD50 in rats of 15g/kg.

For MIBK the following values have been reported:-

An oral LD50 in rats of 2100 mg/Kg

ECOLOGICAL INFORMATION

Marine pollutant and non biodegradeable.

Paints are low viscosity compositions which lose solvents by evaporation, leaving a relatively inert residue which will not degrade significantly.

DISPOSAL CONSIDERATIONS

The material and any contaminated container should be disposed of in accordance with the Environmental Protection Act.

UP0200/UP0201/UP0202/UP0203/UP0204/UP0205/UP0206/UP0207/
UP0208/UP0209/UP0210/UP0211

FIRST AID MEASURES

INHALATION: Move affected person to the fresh air without delay.
If drowsiness persists seek medical attention.

SKIN CONTACT: Wash affected area with warm soapy water. Do not use solvents.

EYE CONTACT: Irrigate with copious quantities of water and seek medical attention immediately.

INGESTION: Do not induce vomiting, drink plenty of water and seek medical attention.

FIRE FIGHTING MEASURES

Fight fires with CO₂, dry powder, or chemical foam. Do not use water jets. Burning material emits toxic fumes and smoke, so avoid inhalation of burning products.

ACCIDENTAL RELEASE MEASURES

The product will readily flow. Contain and collect any spillage with sand or earth. Keep product away from drains. Avoid sources of ignition. Dispose of in accordance with the requirements of the Environmental Protection Act.

HANDLING AND STORAGE

HANDLING: Keep away from heat. Keep away from sources of ignition.
Avoid contact with skin and eyes. Use only in well ventilated areas, and for extensive spraying, in a suitable booth.

STORAGE: Store below 25°C in a dry well ventilated space in original containers. Keep away from sources of heat.

EXPOSURE CONTROLS/PERSONAL PROTECTION

A good standard of personal and industrial hygiene should be maintained at all times. Persons who suffer from skin complaints or other allergic effects should not work with the product.

OEL (UK)	Component	8 HR TWA	10 mins STEL
	Xylene	100 ppm	150 ppm
	Butane	600 ppm	750 ppm
	Toluene	50 ppm	150 ppm
	Acetone	750 ppm	1500 ppm
	White spirit	100 ppm	125 ppm
	Dichloromethane	100 ppm	300 ppm
	DME	400 ppm	500 ppm
	MIK	50 ppm	100 ppm

EYE PROTECTION: Not necessary.

PROTECTIVE CLOTHING: Recommended.

RESPIRATORY PROTECTION: Suitable respiratory protection necessary, when spraying in areas of poor ventilation.

SKIN PROTECTION: Barrier cream recommended.

UP0200/UP0201/UP0202/UP0203/UP0204/UP0205/UP0206/UP0207/
UP0208/UP0209/UP0210/UP0211

TRANSPORT INFORMATION

SHIPPING NAME: AEROSOLS.

UNITED NATION NO: UN 1950.

CLASS NO: 2.1.

HARMONISED SYSTEMS NO: 320890 91 5.

PACKING GROUP: Not allocated.

Complies with The Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations.

For current International Maritime Dangerous Goods Declaration, please contact our Export Department
Telephone No: 44-(0)181-445-0372.

REGULATORY INFORMATION*

	<u>PLAS 1//4F/5</u>	<u>PLAS 2</u>	<u>PLAS 3</u>	<u>PLAS4C</u>
CONTAINS:	Mixture of solvents.	Dichloromethane and Xylene mixture of Isomers.	Mixture of solvents.	Toluene
SYMBOL:	Xn - Harmful. F+ -Extremely flammable.	Xn - Harmful F+ - Extremely flammable.	Xn Harmful F+ - Extremely flammable.	Xn - Harmful F+ - Extremely flammable.
RISK PHRASES:	R20/21 Harmful by inhalation and in contact with skin.	R20/21 Harmful by inhalation And in contact with skin R38 Irritating to the skin. R40 Possible risk of irreversible effects	R20/21 Harmful by inhalation and in contact with skin R38 Irritating to the skin.	R20 Harmful by inhalation.
SAFETY PHRASES:	S16 Keep away from sources of ignition – No smoking. S23 Do not breathe vapour/spray. S25 Avoid contact with the eyes. S51 Use only in well ventilated areas.	S16 Keep away from sources of ignition – No smoking. S23 Do not breathe vapour/spray. S25 Avoid contact with the eyes. S51 Use only in well ventilated areas.	S16 keep away from sources of ignition – No Smoking S23 Do not breathe vapour/spray S25 Avoid contact with the eyes. S51 Use only in well ventilated areas.	S16 Keep away from sources of ignition – No smoking. S23 Do not breathe vapour spray. S25 Avoid contact with the eyes. S51 Use only in well ventilated areas.

Pressurised container, protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn even after use.

Do not spray on a naked flame or any incandescent material.

UP0200/UP0201/UP0202/UP0203/UP0204/UP0205/UP0206/UP0207/
UP0208/UP0209/UP0210/UP0211

FURTHER INFORMATION

Reference should be made to the following official publications:-

EH40, COSHH Regulations, Environmental Protection Act.

ISSUE NUMBER: 0004

* Changes from previous issue.

ISSUE DATE: 15/05/00