

UP 2401-2402

U-POL™

SAFETY DATA SHEET

UP2401, UP2402 2K SYSTEM 20 SLOW THINNERS

Page 1

Issued: 25/09/2006

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UP2401, UP2402 2K SYSTEM 20 SLOW THINNERS

Product code: S2040

Use / description of product: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

Company name: Wesmar Products
1440 NW 45th St
Seattle, WA 98107
(206) 787-8186

Emergency tel: 1-800-424-9300 (CHEMTREC)

2. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** N-BUTYL ACETATE 1-10%
- EINECS: 204-658-1 CAS: 123-86-4
- [-] R10; [Xi] R66; [-] R67
- 2-METHOXY-1-METHYLETHYL ACETATE 10-30%
 - EINECS: 203-603-9 CAS: 108-65-6
 - [-] R10; [Xi] R36
 - LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY 10-30%
 - EINECS: 265-185-4 CAS: 64742-82-1
 - [-] R10; [N] R51/53; [Xn] R65
 - LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. 50-70%
 - EINECS: 265-199-0 CAS: 64742-95-6
 - [F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

[cont...]

SAFETY DATA SHEET

UP2401, UP2402 2K SYSTEM 20 SLOW THINNERS

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.
Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
Ingestion: Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.
Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.
Protection of fire-fighters: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.
Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.
Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.
Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.
Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits
WEL (8 hr exposure limit): 50 ppm
WEL (15 min exposure limit): 100 ppm
Hazardous ingredients: N-BUTYL ACETATE
 TWA 724 mg/m³ STEL 966 mg/m³

- 2-METHOXY-1-METHYLETHYL ACETATE

TWA 274 mg/m³ STEL 822 mg/m³**Engineering measures:** Ensure there is sufficient ventilation of the area.**Respiratory protection:** Compressed airline breathing apparatus (EN139).**Hand protection:** Nitrile gloves.**Eye protection:** Face-shield.**Skin protection:** Protective clothing with elasticated cuffs and closed neck.**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Liquid**Colour:** Colourless**Odour:** Aromatic**Evaporation rate:** Moderate**Solubility in water:** Miscible**Viscosity:** Non-viscous**Flammability limits %: lower:** 0.7**upper:** 7.5**Flash point°C:** 27**Autoflammability°C:** 420**Relative density:** 0.9**VOC g/l:** 875 (7.33 lb/gal)**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Direct sunlight. Sources of ignition.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** N-BUTYL ACETATE

ORL MUS LD50 6 gm/kg

ORL RAT LD50 10768 mg/kg

- 2-METHOXY-1-METHYLETHYL ACETATE

IPR MUS LD50 750 mg/kg

ORL RAT LD50 8532 mg/kg


- LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM),
LIGHT AROM.

ORL RAT LD50 8400 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION**Mobility:** Volatile. Floats on water.**Persistence and degradability:** Only slightly biodegradable.**Bioaccumulative potential:** No data available.**Other adverse effects:** No data available.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D10 Incineration on land.

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1263**ADR Class:** 3**Packing group:** III**Classification code:** F1**Shipping name:** PAINT RELATED MATERIAL**Labelling:** 3**Hazard ID no:** 30**IMDG / IMO****UN no:** 1263**Class:** 3**Packing group:** III**EmS:** F-E,S-E**Marine pollutant:** .**Labelling:** 3**IATA / ICAO****UN no:** 1263**Class:** 3**Packing group:** III**Packing instructions:** 309(P&CA); 310(CAO)**Labelling:** 3**15. REGULATORY INFORMATION****Hazard symbols:** Dangerous for the environment.

Harmful.



Risk phrases: R10: Flammable.
R36/38: Irritating to eyes and skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.

Safety phrases: S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe vapour/spray

VbF: All

Water hazard class: 1 Classification by VwVwS

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.
FOR PROFESSIONAL USE ONLY. Read full instructions before use.
IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.
Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.
U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Risk phrases used in s.2: R10: Flammable.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R36: Irritating to eyes.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R12: Extremely flammable.
R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the

Issued: 25/09/2006

SAFETY DATA SHEET

UP2401, UP2402 2K SYSTEM 20 SLOW THINNERS

Page 6

product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.