

UP 2411/2412
Standard Reducer

U-POLTM

SAFETY DATA SHEET

UP2411, UP2412 2K SYSTEM 20 STANDARD THINNERS

Page 1

Issued: 28/04/2004

Revision No: 6

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UP2411, UP2412 2K SYSTEM 20 STANDARD THINNERS

Product code: S2041

Use / description of product: PAINT PRODUCT CONTAINING XYLENE, MIXTURE OF ISOMERS

Company name:

Wesmar Products, Inc.
1440 NW 45th St
Seattle, Wa 98107
(206) 782-8186

Emergency tel: 1-800-424-9300 (CHEMTREC)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: N-BUTYL ACETATE 30-50%

EINECS: 204-658-1 CAS: 123-86-4

[-] R10; [Xi] R66; [-] R67

- 2-METHOXY-1-METHYLETHYL ACETATE 30-50%

EINECS: 203-603-9 CAS: 108-65-6

[-] R10; [Xi] R36

- XYLENE 30-50%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.
- Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.
- Protection of fire-fighters:** Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.
- Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

- Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** N-BUTYL ACETATE
TWA (8 hr exposure limit): 724 mg/m³ STEL (15 min exposure limit): 966 mg/m³ (OES)
- 2-METHOXY-1-METHYLETHYL ACETATE
TWA (8 hr exposure limit): 274 mg/m³ STEL (15 min exposure limit): 822 mg/m³ (OES)
 - XYLENE
TWA (8 hr exposure limit): 220 mg/m³ STEL (15 min exposure limit): 441 mg/m³ (OES)
- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Compressed airline breathing apparatus (EN139).
- Hand protection:** Nitrile gloves.
- Eye protection:** Face-shield.
- Skin protection:** Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Liquid
- Colour:** Colourless
- Odour:** Aromatic
- Evaporation rate:** Moderate

Solubility in water: Miscible

Viscosity: Non-viscous

Flammability limits %: lower: 1.0

upper: 6.6

Flash point°C: 24

Autoflammability°C: 490

Relative density: 0.9

VOC g/l: 900

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Direct sunlight. Sources of ignition.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: N-BUTYL ACETATE

ORL MUS LD50 6 gm/kg

ORL RAT LD50 10768 mg/kg

- 2-METHOXY-1-METHYLETHYL ACETATE

IPR MUS LD50 750 mg/kg

ORL RAT LD50 8532 mg/kg

- XYLENE

ORL MUS LD50 2119 mg/kg

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Volatile. Floats on water.

Persistence and degradability: Only slightly biodegradable.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D10 Incineration on land.

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no:	1263	ADR Class:	3
Packing group:	III	Classification code:	F1
Shipping name:	PAINT RELATED MATERIAL		
Labelling:	3	Hazard ID no:	30

**IMDG / IMO**

UN no:	1263	Class:	3
Packing group:	III	EmS:	F-E,S-E
Marine pollutant:	.	Labelling:	3

IATA / ICAO

UN no:	1263	Class:	3
Packing group:	III	Packing instructions:	309(P&CA); 310(CAO)
Labelling:	3		

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R36/38: Irritating to eyes and skin.
R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S16: Keep away from sources of ignition - No smoking.
S23 Do not breathe vapour/spray
S36/37: Wear suitable protective clothing and gloves.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

VbF: All

Water hazard class: 1 Classification by VwVwS

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

[cont...]

16. OTHER INFORMATION

Risk phrases used in s.2: R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R36: Irritating to eyes.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.