

Material Safety Data Sheet

SAP REMOVER

WESMAR CO.

5720 204TH ST. SW
LYNNWOOD, WA 98036
(206) 783-5344

DATE PREPARED: MAR 1, 2008

DATE REVISED: MAR 1, 2008

24 HOUR EMERGENCY PHONE NUMBER

CHEMTREC: 800-424-9300

SECTION I – IDENTIFICATION

PRODUCT NAME: SAP REMOVER

CHEMICAL FAMILY: ALCOHOL: FLAMMABLE LIQUID

FORMULA: N/A

CAS NUMBER: N/A

SECTION II – HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW:

EYES: May cause severe eye irritation with possible permanent eye damage and impairment of vision.

SKIN (DERMAL): May cause mild irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

SWALLOWING (INGESTION): May cause severe gastrointestinal irritation and/or ulceration of the mouth and throat. Single dose oral LD50 has not been determined.

INHALATION: Vapors and mist may cause respiratory tract irritation.

MEDICAL CONDITION AGGRAVATED

BY EXPOSURE: Existing skin and/or respiratory disorders may be aggravated by exposure.

CHRONIC OVEREXPOSURE:... None known

OSHA REGULATORY STATUS: Since this product is a mixture, there is no defined PEL's (Personal Exposure Limits) established by OSHA. ACGIH TLV's (Threshold Limit Values) for hazardous components are listed in the Hazardous Ingredients Section of this MSDS.

SECTION III – COMPOSITION INFORMATION ON INGREDIENTS

THRESHOLD LIMIT VALUE:... The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

HAZARDOUS INGREDIENT	PERCENT	CAS NO.	ACGIH/TWA	STEL/TLV
Isopropanol	80-85	67-63-0	200 PPM	400 PPM

SECTION IV – FIRST AID DATA

EYES: If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Material Safety Data Sheet

SAP REMOVER

SKIN (DERMAL):..... Immediately flush skin with lots of cool running water for at least 15 minutes while removing contaminated clothing and/or shoes. Wash contaminated clothing and/or shoes before reuse.

SWALLOWING (INGESTION): NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. (If available, give several glasses of milk) If vomiting occurs spontaneously, keep airway clear and give more water. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:..... If exposure by inhalation is suspected, immediately move exposed individual to fresh air. If individual experiences nausea, headache, dizziness, has difficulty in breathing or is cyanotic, seek a health care professional immediately. Never give anything by mouth to an unconscious person.

SECTION V – FIRE FIGHTING MEASURES

FLASHPOINT:..... 53° F (11.6° C)

LOWER EXPLOSIVE LIMIT:... 2%

UPPER EXPLOSIVE LIMIT:..... 12.0%

EXTINGUISHING MEDIA: Use extinguishing media appropriate to primary cause of fire.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid contact with fire fighting personnel as burns may result from contact with skin. when fighting a fire near or involving this product, wear a self-contained breathing apparatus. (SCBA)

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE LIQUID, AVOID HEAT, SPARKS AND OPEN FLAME. This material may produce a floating fire hazard.

SECTION VI – ACCIDENTAL RELEASE MEASURES

SPILL/ LEAK PROCEDURES:.. Wear proper protective clothing to prevent skin contact and inhalation. Eliminate any source of ignition. Do not smoke. Small spills may be wiped up. Large spills should be absorbed with inert material and held for disposal.

SECTION VII – HANDLING AND STORAGE

HANDLING INFORMATION: .. Store away from acids, oxidizing compounds and other incompatible materials. Keep containers tightly closed when not in use. Store away from heat or flames. Do not weld, cut or grind on or near any empty containers as vapors may ignite. KEEP OUT OF REACH OF CHILDREN.

STORAGE REQUIREMENTS:.. Keep containers tightly closed when not in use. Empty container completely and dispose of in accordance with applicable regulations.

SECTION VIII – EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE PROTECTION:..... Chemical safety goggles and full face shield to protect against splashing in compliance with OSHA regulations are advised. OSHA regulations also permit

Material Safety Data Sheet

SAP REMOVER

other type safety glasses. (Consult your industrial hygienist) Contact lenses should not be worn when working with any chemicals.

RESPIRATORY PROTECTION: Respiratory protection should be worn if levels exceed defined PEL's for this product or any hazardous component listed in the Hazardous Ingredient Section of this MSDS.

OTHER PROTECTIVE

EQUIPMENT: Impervious protective clothing and chemical resistant safety shoes should be worn to minimize contact. Emergency shower and eyewash facility should be in close proximity. (ANSI Z358.1)

VENTILATION: Local exhaust sufficient to maintain TLV below permissible exposure limits.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear colorless liquid with mild odor.

BOILING POINT: Approx. 212° F.

VAPOR PRESSURE: N/A

VAPOR DENSITY (AIR=1): N/A

SPECIFIC GRAVITY: 0.8

pH: NOT EST.

SOLUBILITY IN WATER: Completely soluble in water.

SECTION X – STABILITY AND REACTIVITY DATA

STABILITY: Stable

HAZARDOUS

POLYMERIZATION: Will not occur

INCOMPATIBILITY: Avoid contact with: acetaldehyde, acids, chlorine, ethylene oxide isocyanates, strong oxidizing agents. Do not use with aluminum equipment at temperatures above 120 degrees F..

HAZARDOUS

DECOMPOSITION: Carbon monoxide and carbon dioxide upon thermal decomposition.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL

INFORMATION: **ISOPROPYL ALCOHOL (IPA):** Toxicity to animals: Acute oral (LD50) 3450 mg/kg (mouse), Acute dermal toxicity (LD50) 12800 mg/kg (rabbit) (Isopropyl alcohol). Chronic Effects on Humans: Classified A4 (not classifiable for human or animal) by ACGIH, 3 (Not classifiable for humans) by IARC (IPA). Development Toxicity: Classified Reproductive System/toxin/female, Development Toxin, (probable) (IPA). Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly Hazardous in case of skin contact (permeator).

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL

Material Safety Data Sheet

SAP REMOVER

INFORMATION: **ISOPROPYL ALCOHOL (ISOPROPANOL):** Ecotoxicity: Not available. BODS and COD: Not available. Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Consult all LOCAL, STATE, and FEDERAL regulations with regard to proper and suitable disposal methods.

SECTION XIV – TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Isopropanol, solution 3 UN-1219 PG-II

HAZARD CLASS AND LABEL: 3 (FLAMMABLE)

UN NUMBER: UN-1219

PACKAGING GROUP: PG - II

SECTION XV – REGULATORY INFORMATION

LISTED CARCINOGEN: None known

TSCA STATUS: All components in this product are listed on the TSCA inventory.

SARA SECTION 313: This product **does not** contain any EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning Community Right-To-Know Act of 1986 (40CFR 372):

NFPA HEALTH: 2

NFPA FLAMMABILITY: 3

NFPA REACTIVITY: 0

SECTION XVI – OTHER INFORMATION

REFERENCES: The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

FOOT NOTES: NOT EST. = Not Established, N/A = Not Applicable, (Ceil) = TLV ceiling limit.